



Last information update: July 2021

**Product code**

BU25: Wall/ceiling mounted, ø89mm luminaire without an electronic transformer - Warm White - 180° blade effect

Technical description

Wall and ceiling-mounted luminaire, designed for use with LED lamps and a patented, 180° blade effect optic. The product consists of a support base and screen. The base is made of phosphocromatization treated, die-cast aluminium, with a double base coat and passivation at 120°C. It is coated with liquid acrylic paint, cured at 150 °C to guarantee a high level of weather and UV ray resistance. The optic is made of methacrylate and fixed to the body via a zamak cover. All the screws used are made of A2 stainless steel.

Installation

Wall and ceiling mounted by means of a stainless steel wall fixture plate.

Colour

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

Mounting

wall surface|ceiling surface

Wiring

Product supplied with an outlet cable L=200mm. 350 mA electronic ballast to be ordered separately.

Notes

Compatible with the Master Pro DMX control system.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	606 (*)	CRI:	80
W system:	5.8 (*)	Colour temperature [K]:	3000
Im source:	606 (*)	Number of lamps for optical 1 assembly:	
W source:	5.8 (*)	ZVEI Code:	LED
Luminous efficiency (Im/W, 30.06 (*) real value):		Number of optical assemblies:	1
Im in emergency mode:	-	Ambient operating temperature range:	from -20 °C to +35 °C. (*)
Beam angle [°]:	0 (*)	LED Current [mA]:	

* Preliminary data