

SPECIFICATION SHEET

LED AC DRIVERLESS FLOODLIGHTS

The LED AC Driverless Floodlights are available in 10W-300W and have a black finish.

Applications:

- Commercial Sites
- Factories
- Leisure Centres

SIGNATURE
LED LIGHTING



Image shown FLAC100B

Specification

LED: 15-360pcs of SMD 2835

Material: Aluminium

Guarantee: 2 Years

Life Expectancy: >30,000 Hours

Working Temperature: -20°C - 45°C

Power Factor: >0.9


Beam Angle: >120°

CRI: >80 Ra

Additional Information

- 75/80lm/W • Aluminium tray • Black finish
- Driverless technology • 3G 0.75mm² 1m Cable included
- Mounting bracket included • Internal white reflector
- HO5RN-F

Dimensions



Code	Wattage	Colour Temperature	Lumen Output	Dimensions (L x W x D mm)
FLAC10B	10W	6000K	800lm	103 x 83 x 24
FLAC10B-31	10W	3100K	750lm	103 x 83 x 24
FLAC20B	20W	6000K	1600lm	160 x 122 x 25
FLAC20B-31	20W	3100K	1500lm	160 x 122 x 25
FLAC30B	30W	6000K	2400lm	160 x 122 x 25
FLAC30B-31	30W	3100K	2250lm	160 x 122 x 25
FLAC50B	50W	6000K	4000lm	206 x 160 x 31
FLAC50B-31	50W	3100K	3750lm	206 x 160 x 31
FLAC100B	100W	6000K	8000lm	270 x 210 x 31
FLAC150B	150W	6000K	12,000lm	379 x 279 x 43
FLAC200B	200W	6000K	16,000lm	379 x 279 x 43
FLAC300B	300W	6000K	24,000lm	445 x 335 x 45

T: 0151 420 6000

E: sales@signatureledlighting.co.uk

SIGNATURE
LED LIGHTING

Signature LED Lighting
Unit 2, 34a Kershaw Street
Widnes,
WA8 7JA