

Cooling	Model	63Hz	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	8000Hz	PWL dB(A)
	(E)P200	77.5	76.0	74.5	73.0	71.5	68.0	64.0	59.0	76.0
	(E)P250	80.5	78.5	77.0	75.0	73.0	70.5	69.0	61.5	78.5
	(E)P300	79.0	78.5	77.5	76.5	76.0	72.5	66.0	59.0	80.0
	(E)P350	77.5	77.5	77.5	77.5	77.5	73.5	67.0	58.0	81.0
	(E)P400	79.5	79.5	79.5	79.0	79.5	76.0	68.5	62.5	83.0
	(E)P450	79.5	79.5	79.5	79.0	79.5	76.0	69.0	62.5	83.0
	(E)P500	77.5	77.5	77.5	77.0	77.0	76.0	71.5	62.5	82.0
	(E)P550	79.5	79.5	79.0	79.0	79.0	77.5	72.0	64.5	83.5
	(E)P400S	80.5	79.0	77.5	76.0	74.5	71.0	67.0	62.0	79.0
	(E)P450S	82.0	80.5	79.0	77.0	75.5	72.5	70.5	63.5	80.5
	(E)P500S	83.5	81.5	80.0	78.0	76.0	73.5	72.0	64.5	81.5
	(E)P550S	83.0	81.5	80.5	79.0	78.0	75.0	71.5	63.5	82.5
	(E)P600S	82.0	81.5	80.5	79.5	79.0	75.5	69.0	62.0	83.0
	(E)P650S	81.5	81.0	80.5	80.0	79.5	76.0	69.5	61.5	83.5
	(E)P700S	80.5	80.5	80.5	80.5	80.5	76.5	70.0	61.0	84.0
	(E)P750S	82.0	82.0	82.0	81.5	82.0	78.0	71.0	64.5	85.5
	(E)P800S	82.5	82.5	82.5	82.0	82.5	79.0	71.5	65.5	86.0
	(E)P850S	82.5	82.5	82.5	82.0	82.5	79.0	71.5	65.5	86.0
	(E)P900S	82.5	82.5	82.5	82.0	82.5	79.0	72.0	65.5	86.0
	(E)P950S	81.5	81.5	81.5	81.5	81.5	79.0	73.0	65.5	85.5
	(E)P1000S	80.5	80.5	80.5	80.0	80.0	79.0	74.5	65.5	85.0
	(E)P1050S	82.0	82.0	81.5	81.5	81.0	80.0	75.0	67.0	86.0
	(E)P1100S	82.5	82.5	82.0	82.0	82.0	80.5	75.0	67.5	86.5

Heating	Model	63Hz	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	8000Hz	PWL dB(A)
	(E)P200	79.5	78.0	76.5	74.5	73.0	69.0	69.5	61.5	78.0
	(E)P250	81.0	79.5	78.0	76.5	75.0	71.0	72.0	63.0	80.0
	(E)P300	83.0	83.0	83.0	82.5	82.5	79.0	75.0	68.0	86.5
	(E)P350	78.5	78.5	78.5	78.5	78.5	76.0	73.5	67.5	83.0
	(E)P400	88.0	87.0	85.5	84.5	83.5	81.0	76.0	68.0	88.0
	(E)P450	88.5	87.5	86.5	85.5	84.0	82.0	78.0	69.5	89.0
	(E)P500	81.0	80.0	79.5	79.0	78.5	78.0	75.0	67.5	84.0
	(E)P550	88.5	87.5	86.5	85.0	84.0	82.0	78.0	73.0	89.0
	(E)P400S	82.5	81.0	79.5	77.5	76.0	72.0	72.5	64.5	81.0
	(E)P450S	84.0	82.0	80.5	79.0	77.5	73.5	74.5	65.5	82.5
	(E)P500S	84.0	82.5	81.0	79.5	78.0	74.0	75.0	66.0	83.0
	(E)P550S	85.0	84.5	84.0	83.5	83.5	79.5	77.0	69.0	87.5
	(E)P600S	86.0	86.0	86.0	85.5	85.5	82.0	78.0	71.0	89.5
	(E)P650S	84.5	84.5	84.5	84.5	84.5	81.0	78.0	71.0	88.5
	(E)P700S	81.5	81.5	81.5	81.5	81.5	79.0	76.5	70.5	86.0
	(E)P750S	89.0	88.0	87.0	86.0	85.0	82.5	78.5	71.0	89.5
	(E)P800S	91.0	90.0	88.5	87.5	86.5	84.0	79.0	71.0	91.0
	(E)P850S	91.5	90.0	89.0	88.0	86.5	84.5	80.0	72.0	91.5
	(E)P900S	91.5	90.5	89.5	88.5	87.0	85.0	81.0	72.5	92.0
	(E)P950S	89.5	88.5	87.5	86.5	85.5	84.0	80.0	72.0	90.5
	(E)P1000S	84.0	83.0	82.5	82.0	81.5	81.0	78.0	70.5	87.0
	(E)P1050S	91.0	90.0	89.0	88.0	87.0	85.5	81.5	76.0	92.0
	(E)P1100S	91.5	90.5	89.5	88.0	87.0	85.0	81.0	76.0	92.0

Difference	Model	63Hz	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	8000Hz	PWL dB(A)
	(E)P200	2.0	2.0	2.0	1.5	1.5	1.0	5.5	2.5	2.0
	(E)P250	0.5	1.0	1.0	1.5	2.0	0.5	3.0	1.5	1.5
	(E)P300	4.0	4.5	5.5	6.0	6.5	6.5	9.0	9.0	6.5
	(E)P350	1.0	1.0	1.0	1.0	1.0	2.5	6.5	9.5	2.0
	(E)P400	8.5	7.5	6.0	5.5	4.0	5.0	7.5	5.5	5.0
	(E)P450	9.0	8.0	7.0	6.5	4.5	6.0	9.0	7.0	6.0
	(E)P500	3.5	2.5	2.0	2.0	1.5	2.0	3.5	5.0	2.0
	(E)P550	9.0	8.0	7.5	6.0	5.0	4.5	6.0	8.5	5.5