

Piccadilly Warehouse Refurbishment Project NBS Specification

11 April 2021

Table of Contents

Title		Page
P	Building fabric sundries	3
P20	Unframed isolated trims/ skirtings/ sundry items	5

P

Building fabric sundries

P20

Unframed isolated trims/ skirtings/ sundry items

P20 Unframed isolated trims/ skirtings/ sundry items

To be read with Preliminaries/ General conditions

200 MEDIUM DENSITY FIBREBOARD SKIRTING BOARDS

- Manufacturer: Contractor's choice.
 - Product reference: Submit proposals.
- Standard: To BS EN 622-5.
 - Type: MDF.
 - Formaldehyde class: To BS EN 622-1, Class E1.
- Fire rating: Not applicable.
- Thickness: To match the profile of the existing skirtings.
Edges: To match the profile of the existing skirtings.
- Finish: Prepared and primed as Section M60.
- Recycled content: Contractor's choice.
- Support/ Fixing: Plugged, screwed and pelleted at 450mm Centres.

200A MEDIUM DENSITY FIBREBOARD WINDOW CILL BOARDS

- Manufacturer: Contractor's choice.
 - Product reference: Submit proposals.
- Standard: To BS EN 622-5.
 - Type: MDF.
 - Formaldehyde class: To BS EN 622-1, Class E1.
- Fire rating: Not applicable.
- Thickness: 22 mm x length & width to suit existing openings with 50 mm overhang at cill and jambs.
Edges: Square edge.
- Finish: Prepared and primed as Section M60.
- Recycled content: Contractor's choice.
- Support/ Fixing: Plugged, screwed and pelleted at 450mm Centres.

200B MEDIUM DENSITY FIBREBOARD DOOR ARCHITRAVES

- Manufacturer: Contractor's choice.
 - Product reference: Submit proposals.
- Standard: To BS EN 622-5.
 - Type: MDF.
 - Formaldehyde class: To BS EN 622-1, Class E1.
- Fire rating: Not applicable.
- Thickness: 18 mm x 68 mm with a 1.5 mm arriss to each long edge.
Edges: 1.5 mm arriss to each long edge.
- Finish: Prepared and primed as Section M60.
- Recycled content: Contractor's choice.
- Support/ Fixing: Plugged, screwed and pelleted at 450mm Centres.

415 LEG SUPPORTS FOR FITTED FURTNITURE GENERALLY

- Manufacturer: Contractor's choice.
 - Product reference: Submit proposals.
- Type/Size: To suit the application.
- Finish/Colour: N/A unless the supports are visible.
- Height: To suit the application.
- Fixing: To suit the application and screw fixings to soffit of wood panel.

420 BRACKET SUPPORTS FOR FITTED FURNITURE GENERALLY

- Material: Contractor's choice.
 - Finish: Submit proposals.
 - Colour: N/A unless the supports are visible.
- Size: To suit the application.
- Fixing: To suit the application and plugged and screwed to substrate.

EXECUTION

510 INSTALLATION GENERALLY

- Joinery workmanship: As section Z10.
- Metal workmanship: As section Z11.
- Methods of fixing and fasteners: As section Z20 where not specified.
- Straight runs: To be in one piece, or in long lengths with as few joints as possible.
- Running joints: Location and method of forming to be agreed where not detailed.
- Joints at angles: Mitre, unless shown otherwise.
- Position and level: To be agreed where not detailed.