

Air Quality Assessment
High Lane, Chorlton

Client: Southway Devco Limited

Reference: 4043r1

Date: 26th November 2021



Report Issue

Report Title: Air Quality Assessment - High Lane, Chorlton

Report Reference: 4043

Field	Report Version			
	1	2	3	4
Prepared by	Ceri Haines			
Position	Graduate Air Quality Consultant			
Reviewed by	Emily Macey			
Position	Air Quality Consultant			
Authorised by	Jethro Redmore			
Position	Director			
Date of Issue	26 th November 2021			
Comments	-			

Taylor Road, Urmston, Manchester, M41 7JQ

info@red-env.co.uk | 0161 706 0075 | www.red-env.co.uk

This report has been prepared by Redmore Environmental Ltd in accordance with the agreed terms and conditions of appointment. Redmore Environmental Ltd cannot accept any responsibility for any use of or reliance on the contents of this report by any third party.

Executive Summary

Redmore Environmental Ltd was commissioned by Southway Devco Limited to undertake an Air Quality Assessment in support of a planning application for a residential development on land at the Chorlton Irish Club, High Lane, Chorlton.

The proposals have the potential to cause air quality impacts as a result of fugitive dust emissions during construction and road traffic exhaust emissions associated with vehicles travelling to and from the site during operation, as well as expose future residents to any existing air quality issues. As such, an Air Quality Assessment was undertaken in order to determine baseline conditions and assess potential effects as a result of the development.

Potential construction phase air quality impacts from fugitive dust emissions were assessed as a result of earthworks, construction and trackout activities. It is considered that the use of good practice control measures would provide suitable mitigation for a development of this size and nature and reduce potential impacts to an acceptable level.

During the operational phase of the development there is the potential for air quality impacts as a result of traffic exhaust emissions associated with vehicles travelling to and from the site. These were assessed using standard screening criteria. Due to the size of the proposals, air quality impacts were not predicted to be significant.

The potential for the exposure of future residents to elevated pollution levels was assessed based on the results of a desk-top study. This indicated that pollutant concentrations are likely to be below the relevant criteria at the development location. As such, the site is considered suitable for the proposed end use from an air quality perspective.

Based on the assessment results, air quality issues are not considered a constraint to planning consent for the development.

Table of Contents

1.0	INTRODUCTION	1
1.1	Background	1
1.2	Site Location and Context	1
2.0	LEGISLATION AND POLICY	2
2.1	Legislation	2
2.2	World Health Organisation Guidelines	4
2.3	Local Air Quality Management	5
2.4	Dust	5
2.5	National Planning Policy	6
2.6	National Planning Practice Guidance	7
2.6.3	Local Planning Policy	8
3.0	METHODOLOGY	10
3.1	Introduction	10
3.2	Construction Phase Assessment	10
	Step 1	11
	Step 2	11
	Step 3	16
	Step 4	17
3.3	Operational Phase Assessment	17
	Potential Development Impacts	17
	Potential Future Exposure	18
4.0	BASELINE	19
4.1	Introduction	19
4.2	Local Air Quality Management	19
4.3	Air Quality Monitoring	19
4.4	Background Pollutant Concentrations	20
4.5	Sensitive Receptors	21
5.0	ASSESSMENT	23
5.1	Introduction	23
5.2	Construction Phase Assessment	23
	Step 1	23
	Step 2	23
	Step 3	25
	Step 4	27

5.3	Operational Phase Assessment	27
	Potential Development Impacts	27
	Potential Future Exposure	27
	Mitigation	30
6.0	CONCLUSION	32
7.0	ABBREVIATIONS	34

Appendix

Appendix 1 - Curricula Vitae

1.0 INTRODUCTION

1.1 Background

1.1.1 Redmore Environmental Ltd was commissioned by Southway Devco Limited to undertake an Air Quality Assessment in support of a planning application for a residential development on land at the Chorlton Irish Club, High Lane, Chorlton.

1.1.2 The proposals have the potential to cause air quality impacts as a result of fugitive dust emissions during construction and road traffic exhaust emissions associated with vehicles travelling to and from the development during operation, as well as expose future residents to any existing air quality issues at the site. As such, an Air Quality Assessment was undertaken in order to determine baseline conditions and assess potential effects as a result of the development.

1.2 Site Location and Context

1.2.1 The site is located on the existing car park of the Chorlton Irish Club, High Lane, Chorlton, at approximate National Grid Reference (NGR): 381715, 393585. Reference should be made to Figure 1 for a map of the site and surrounding area.

1.2.2 The proposals comprise the redevelopment of the Chorlton Irish Club car park to provide 29 residential units over four storeys and associated infrastructure.

1.2.3 The proposals have the potential to cause impacts at sensitive locations during the construction and operational phases. These may include fugitive dust emissions associated with construction works and road traffic exhaust emissions from vehicles travelling to and from the development during the operational phase. There is also the potential for the exposure of future residents to any existing air quality issues at the site. An Air Quality Assessment was therefore undertaken in order to determine baseline conditions and consider potential air quality effects as a result of the proposals. This is detailed in the following report.

2.0 LEGISLATION AND POLICY

2.1 Legislation

2.1.1 The Air Quality Standards Regulations (2010) came into force on 11th June 2010 and include Air Quality Limit Values (AQLVs) for the following pollutants:

- Nitrogen dioxide (NO₂);
- Sulphur dioxide;
- Lead;
- Particulate matter with an aerodynamic diameter of less than 10µm (PM₁₀);
- Particulate matter with an aerodynamic diameter of less than 2.5µm (PM_{2.5});
- Benzene; and,
- Carbon monoxide.

2.1.2 Air Quality Target Values (AQTVs) were also provided for several additional pollutants.

2.1.3 Part IV of the Environment Act (1995) requires UK government to produce a national Air Quality Strategy (AQS) which contains standards, objectives and measures for improving ambient air quality. The most recent AQS was produced by the Department for Environment, Food and Rural Affairs (DEFRA) and published in July 2007¹. The AQS sets out Air Quality Objectives (AQOs) that are maximum ambient pollutant concentrations that are not to be exceeded either without exception or with a permitted number of exceedences over a specified timescale. These are generally in line with the AQLVs, although the requirements for the determination of compliance vary.

2.1.4 Table 1 presents the AQOs and AQLVs for pollutants considered within this assessment.

Table 1 Air Quality Objectives/Air Quality Limit Values

Pollutant	Air Quality Objective/Air Quality Limit Value	
	Concentration (µg/m ³)	Averaging Period
NO ₂	40	Annual mean

¹ The Air Quality Strategy for England, Scotland, Wales and Northern Ireland, DEFRA, 2007.

Pollutant	Air Quality Objective/Air Quality Limit Value	
	Concentration ($\mu\text{g}/\text{m}^3$)	Averaging Period
	200	1-hour mean, not to be exceeded on more than 18 occasions per annum
PM ₁₀	40	Annual mean
	50	24-hour mean, not to be exceeded on more than 35 occasions per annum
PM _{2.5}	25	Annual mean

2.1.5 Table 2 summarises the advice provided in DEFRA guidance² on where the AQOs for pollutants considered within this report apply.

Table 2 Examples of Where the Air Quality Objectives Apply

Averaging Period	Objective Should Apply At	Objective Should Not Apply At
Annual mean	All locations where members of the public might be regularly exposed Building façades of residential properties, schools, hospitals, care homes etc.	Building façades of offices or other places of work where members of the public do not have regular access Hotels, unless people live there as their permanent residence Gardens of residential properties Kerbside sites (as opposed to locations at the building façade), or any other location where public exposure is expected to be short term
24-hour mean	All locations where the annual mean objective would apply, together with hotels Gardens of residential properties	Kerbside sites (as opposed to locations at the building façade), or any other location where public exposure is expected to be short term

² Local Air Quality Management Technical Guidance (TG16), DEFRA, 2021.

Averaging Period	Objective Should Apply At	Objective Should Not Apply At
1-hour mean	All locations where the annual mean and 24 and 8-hour mean objectives apply. Kerbside sites (for example, pavements of busy shopping streets) Those parts of car parks, bus stations and railway stations etc which are not fully enclosed, where members of the public might reasonably be expected to spend one hour or more Any outdoor locations where members of the public might reasonably be expected to spend one hour or longer	Kerbside sites where the public would not be expected to have regular access

2.2 World Health Organisation Guidelines

2.2.1 The World Health Organisation (WHO) provides recommended limits for health-harmful concentrations of key air pollutants both outdoors and inside buildings and homes, based on global synthesis of scientific evidence. These are often utilised by national and international governing bodies when determining appropriate air quality standards for inclusion in relevant legislation. For example, the WHO guidelines were used to inform the AQLVs and AQTVs stated within Directive 2008/50/EC, as transposed into UK legislation through the Air Quality Standards Regulations (2010). The most recent WHO air quality guidelines were published on 22nd September 2021.

2.2.2 The WHO guideline for annual mean PM_{2.5} concentrations was considered within the assessment. This is outlined in Table 3. At the request of Laura Miller, Environmental Protection Officer at Manchester City Council (MCC)³, the previous WHO guideline has been considered in contrast to the most recent value.

Table 3 WHO Guideline

Pollutant	WHO Guideline	
	Concentration (µg/m ³)	Averaging Period
PM _{2.5}	10	Annual mean

³ Email correspondence with Laura Miller, MCC, 2021.

- 2.2.3 It should be noted that the WHO values are guidelines only and there is no legislative or planning requirement to consider these criteria within the UK. As such, when determining the potential for air quality impacts at sensitive receptor locations, the assessment predictions were compared with the relevant AQOs and AQLVs stated within UK Legislation, rather than the WHO guideline levels.

2.3 Local Air Quality Management

- 2.3.1 Under Section 82 of the Environment Act (1995) (Part IV) Local Authorities (LAs) are required to periodically review and assess air quality within their area of jurisdiction under the system of Local Air Quality Management (LAQM). This review and assessment of air quality involves comparing present and likely future pollutant concentrations against the AQOs. If it is predicted that levels at locations of relevant exposure, as summarised in Table 2, are likely to be exceeded, the LA is required to declare an Air Quality Management Area (AQMA). For each AQMA the LA is required to produce an Air Quality Action Plan (AQAP), the objective of which is to reduce pollutant concentrations in pursuit of the AQOs.

2.4 Dust

- 2.4.1 The main requirements with respect to dust control from industrial or trade premises not regulated under the Environmental Permitting (England and Wales) Regulations (2016) and subsequent amendments, such as construction sites, is that provided in Section 79 of Part III of the Environmental Protection Act (1990). The Act defines nuisance as:

"any dust, steam, smell or other effluvia arising on industrial, trade or business premises and being prejudicial to health or a nuisance."

- 2.4.2 Enforcement of the Act, in regard to nuisance, is currently under the jurisdiction of the local Environmental Health Department, whose officers are deemed to provide an independent evaluation of nuisance. If the LA is satisfied that a statutory nuisance exists, or is likely to occur or happen again, it must serve an Abatement Notice under Part III of the Environmental Protection Act (1990). The only defence is to show that the process to which the nuisance has been attributed and its operation are being controlled according to best practicable means.

2.5 **National Planning Policy**

2.5.1 The revised National Planning Policy Framework⁴ (NPPF) was published in July 2021 and sets out the Government's planning policies for England and how these are expected to be applied.

2.5.2 The purpose of the planning system is to contribute to the achievements of sustainable development. In order to ensure this, the NPPF recognises three overarching objectives including the following of relevance to air quality:

"c) An environmental objective - to protect and enhance our natural, built and historic environment; including making effective use of land, improving biodiversity, using natural resources prudently, minimising waste and pollution, and mitigating and adapting to climate change, including moving to a low carbon economy."

2.5.3 Chapter 15 of the NPPF details objectives in relation to conserving and enhancing the natural environment. It states that:

"Planning policies and decisions should contribute to and enhance the natural and local environment by:

[...]

e) preventing new and existing development from contributing to, being put at unacceptable risk from, or being adversely affected by, unacceptable levels of soil, air, water or noise pollution or land instability. Development should, wherever possible, help to improve local environmental conditions such as air and water quality [...]"

2.5.4 The NPPF specifically recognises air quality as part of delivering sustainable development and states that:

⁴ NPPF, Ministry of Housing, Communities and Local Government, 2021.

"Planning policies and decisions should sustain and contribute towards compliance with relevant limit values or national objectives for pollutants, taking into account the presence of Air Quality Management Areas and Clean Air Zones, and the cumulative impacts from individual sites in local areas. Opportunities to improve air quality or mitigate impacts should be identified, such as through traffic and travel management, and green infrastructure provision and enhancement. So far as possible these opportunities should be considered at the plan-making stage, to ensure a strategic approach and limit the need for issues to be reconsidered when determining individual applications. Planning decisions should ensure that any new development in Air Quality Management Areas and Clean Air Zones is consistent with the local air quality action plan."

2.5.5 The implications of the NPPF have been considered throughout this assessment.

2.6 National Planning Practice Guidance

2.6.1 The National Planning Practice Guidance⁵ (NPPG) web-based resource was launched by the Department for Communities and Local Government on 6th March 2014 and updated on 1st November 2019 to support the NPPF and make it more accessible. The air quality pages are summarised under the following headings:

1. What air quality considerations does planning need to address?
2. What is the role of plan-making with regard to air quality?
3. Are air quality concerns relevant to neighbourhood planning?
4. What information is available about air quality?
5. When could air quality considerations be relevant to the development management process?
6. What specific issues may need to be considered when assessing air quality impacts?
7. How detailed does an air quality assessment need to be?
8. How can an impact on air quality be mitigated?

2.6.2 These were reviewed and the relevant guidance considered as necessary throughout the undertaking of this assessment.

⁵ <https://www.gov.uk/guidance/air-quality--3>.

2.6.3 Local Planning Policy

2.6.4 The Manchester Local Development Framework consists of a series of planning documents of which the Core Strategy⁶ is central. This was adopted by MCC on 11th July 2012 and provides policies which guide the determination of planning applications within the city.

2.6.5 A review of the Core Strategy indicated the following policies of relevance to the assessment:

"Policy EN 16

Air Quality

The Council will seek to improve the air quality within Manchester, and particularly within Air Quality Management Areas, located along Manchester's principal traffic routes and at Manchester Airport. Developers will be expected to take measures to minimise and mitigate the local effect of emissions from traffic generated by the development, as well as emissions created by the use of the development itself, including from Combined Heat and Power and biomass plant.

When assessing the appropriateness of locations for new development the Council will consider the effects on air quality, alongside other plan objectives. This includes cumulative effects, particularly in Air Quality Management Areas."

"Policy DM 1

Development Management

All development should have regard to the following specific issues for which more detailed guidance may be given within a supplementary planning document:-

[...]

⁶ Core Strategy, MCC, 2012.

Effects on amenity, including privacy, light, noise, vibration, air quality, odours, litter, vermin, birds, road safety and traffic generation. This could also include proposals which would be sensitive to existing environmental conditions, such as noise."

- 2.6.6 The implications of the above policies were taken into consideration throughout the undertaking of the assessment.

3.0 METHODOLOGY

3.1 Introduction

3.1.1 The proposed development has the potential to cause air quality impacts during the construction and operational phases, as well as expose future residents to elevated pollution levels. These issues have been assessed in accordance with the following methodology, which was agreed with Laura Miller, Environmental Protection Officer at MCC, on 22nd November 2021.

3.2 Construction Phase Assessment

3.2.1 There is the potential for fugitive dust emissions to occur as a result of construction phase activities. These have been assessed in accordance with the methodology outlined within the Institute of Air Quality Management (IAQM) document 'Guidance on the Assessment of Dust from Demolition and Construction V1.1'⁷.

3.2.2 Activities on the proposed construction site have been divided into three types to reflect their different potential impacts. These are:

- Earthworks;
- Construction; and,
- Trackout.

3.2.3 The potential for dust emissions was assessed for each activity that is likely to take place and considered three separate dust effects:

- Annoyance due to dust soiling;
- Harm to ecological receptors; and,
- The risk of health effects due to a significant increase in exposure to PM₁₀.

3.2.4 The assessment steps are detailed below.

⁷ Guidance on the Assessment of Dust from Demolition and Construction V1.1, IAQM, 2016.

Step 1

- 3.2.5 Step 1 screens the requirement for a more detailed assessment. Should human receptors be identified within 350m from the boundary or 50m from the construction vehicle route up to 500m from the site entrance, then the assessment proceeds to Step 2. Additionally, should ecological receptors be identified within 50m of the site or the construction vehicle route up to 500m from the site entrance, then the assessment also proceeds to Step 2.
- 3.2.6 Should sensitive receptors not be present within the relevant distances then **negligible** impacts would be expected and further assessment is not necessary.

Step 2

- 3.2.7 Step 2 assesses the risk of potential dust impacts. A site is allocated a risk category based on two factors:
- The scale and nature of the works, which determines the magnitude of dust arising as: small, medium or large (Step 2A); and,
 - The sensitivity of the area to dust impacts, which can be defined as low, medium or high sensitivity (Step 2B).
- 3.2.8 The two factors are combined in Step 2C to determine the risk of dust impacts without mitigation applied.
- 3.2.9 Step 2A defines the potential magnitude of dust emission through the construction phase. The relevant criteria are summarised in Table 4.

Table 4 Construction Dust - Magnitude of Emission

Magnitude	Activity	Criteria
Large	Earthworks	• Total site area greater than 10,000m² • Potentially dusty soil type (e.g. clay, which will be prone to suspension when dry due to small particle size) • More than 10 heavy earth moving vehicles active at any one time • Formation of bunds greater than 8m in height • More than 100,000 tonnes of material moved

Magnitude	Activity	Criteria
	Construction	- Total building volume greater than 100,000m³ - On site concrete batching - Sandblasting
	Trackout	- More than 50 Heavy Duty Vehicle (HDV) trips per day - Potentially dusty surface material (e.g. high clay content) - Unpaved road length greater than 100m
Medium	Earthworks	- Total site area 2,500m² to 10,000m² - Moderately dusty soil type (e.g. silt) 5 to 10 heavy earth moving vehicles active at any one time - Formation of bunds 4m to 8m in height - Total material moved 20,000 tonnes to 100,000 tonnes
	Construction	- Total building volume 25,000m³ to 100,000m³ - Potentially dusty construction material (e.g. concrete) - On site concrete batching
	Trackout	10 to 50 HDV trips per day - Moderately dusty surface material (e.g. high clay content) - Unpaved road length 50m to 100m
Small	Earthworks	- Total site area less than 2,500m² - Soil type with large grain size (e.g. sand) - Less than 5 heavy earth moving vehicles active at any one time - Formation of bunds less than 4m in height - Total material moved less than 20,000 tonnes - Earthworks during wetter months
	Construction	- Total building volume less than 25,000m³ - Construction material with low potential for dust release (e.g. metal cladding or timber)
	Trackout	- Less than 10 HDV trips per day - Surface material with low potential for dust release - Unpaved road length less than 50m

3.2.10 Step 2B defines the sensitivity of the area around the development to potential dust impacts. The influencing factors are shown in Table 5.

Table 5 Construction Dust - Examples of Factors Defining Sensitivity of an Area

Receptor Sensitivity	Examples	
	Human Receptors	Ecological Receptors
High	• Users expect high levels of amenity • High aesthetic or value property • People expected to be present continuously for extended periods of time • Locations where members of the public are exposed over a time period relevant to the AQO for PM₁₀. e.g. residential properties, hospitals, schools and residential care homes	• Internationally or nationally designated site e.g. Special Area of Conservation
Medium	• Users would expect to enjoy a reasonable level of amenity • Aesthetics or value of their property could be diminished by soiling • People or property wouldn't reasonably be expected to be present here continuously or regularly for extended periods as part of the normal pattern of use of the land e.g. parks and places of work	• Nationally designated site e.g. Sites of Special Scientific Interest
Low	• Enjoyment of amenity would not reasonably be expected • Property would not be expected to be diminished in appearance • Transient exposure, where people would only be expected to be present for limited periods. e.g. public footpaths, playing fields, shopping streets, farmland, short term car parks and roads	• Locally designated site e.g. Local Nature Reserve

3.2.11 The guidance also provides the following factors to consider when determining the sensitivity of an area to potential dust impacts:

- Any history of dust generating activities in the area;
- The likelihood of concurrent dust generating activity on nearby sites;
- Any pre-existing screening between the source and receptors;
- Any conclusions drawn from analysing local meteorological data which accurately represent the area; and if relevant the season during which works will take place;
- Any conclusions drawn from local topography;
- Duration of the potential impact, as a receptor may become more sensitive over time; and,

- Any known specific receptor sensitivities which go beyond the classifications given in the document.

3.2.12 These factors were considered in the undertaking of this assessment.

3.2.13 The criteria for determining the sensitivity of the area to dust soiling effects on people and property is summarised in Table 6.

Table 6 Construction Dust - Sensitivity of the Area to Dust Soiling Effects on People and Property

Receptor Sensitivity	Number of Receptors	Distance from the Source (m)			
		Less than 20	Less than 50	Less than 100	Less than 350
High	More than 100	High	High	Medium	Low
	10 - 100	High	Medium	Low	Low
	1 - 10	Medium	Low	Low	Low
Medium	More than 1	Medium	Low	Low	Low
Low	More than 1	Low	Low	Low	Low

3.2.14 Table 7 outlines the criteria for determining the sensitivity of the area to human health impacts.

Table 7 Construction Dust - Sensitivity of the Area to Human Health Impacts

Receptor Sensitivity	Background Annual Mean PM ₁₀ Concentration	Number of Receptors	Distance from the Source (m)				
			Less than 20	Less than 50	Less than 100	Less than 200	Less than 350
High	Greater than 32µg/m ³	More than 100	High	High	High	Medium	Low
		10 - 100	High	High	Medium	Low	Low
		1 - 10	High	Medium	Low	Low	Low
	28 - 32µg/m ³	More than 100	High	High	Medium	Low	Low
		10 - 100	High	Medium	Low	Low	Low
		1 - 10	High	Medium	Low	Low	Low

Receptor Sensitivity	Background Annual Mean PM ₁₀ Concentration	Number of Receptors	Distance from the Source (m)				
			Less than 20	Less than 50	Less than 100	Less than 200	Less than 350
	24 - 28µg/m ³	More than 100	High	Medium	Low	Low	Low
		10 - 100	High	Medium	Low	Low	Low
		1 - 10	Medium	Low	Low	Low	Low
	Less than 24µg/m ³	More than 100	Medium	Low	Low	Low	Low
		10 - 100	Low	Low	Low	Low	Low
		1 - 10	Low	Low	Low	Low	Low
	Medium	Greater than 32µg/m ³	More than 10	High	Medium	Low	Low
			1 - 10	Medium	Low	Low	Low
	28 - 32µg/m ³	More than 10	Medium	Low	Low	Low	Low
		1 - 10	Low	Low	Low	Low	Low
	24 - 28µg/m ³	More than 10	Low	Low	Low	Low	Low
		1 - 10	Low	Low	Low	Low	Low
	Less than 24µg/m ³	More than 10	Low	Low	Low	Low	Low
		1 - 10	Low	Low	Low	Low	Low
	Low	-	1 or more	Low	Low	Low	Low

3.2.15 Table 8 outlines the criteria for determining the sensitivity of the area to ecological impacts.

Table 8 Construction Dust - Sensitivity of the Area to Ecological Impacts

Receptor Sensitivity	Distance from the Source (m)	
	Less than 20	Less than 50
High	High	Medium
Medium	Medium	Low

Receptor Sensitivity	Distance from the Source (m)	
	Less than 20	Less than 50
Low	Low	Low

3.2.16 Step 2C combines the dust emission magnitude with the sensitivity of the area to determine the risk of unmitigated impacts.

3.2.17 Table 9 outlines the risk category from earthworks and construction activities.

Table 9 Construction Dust - Dust Risk Category from Earthworks and Construction Activities

Receptor Sensitivity	Dust Emission Magnitude		
	Large	Medium	Small
High	High	Medium	Low
Medium	Medium	Medium	Low
Low	Low	Low	Negligible

3.2.18 Table 10 outlines the risk category from trackout activities.

Table 10 Construction Dust - Dust Risk Category from Trackout Activities

Receptor Sensitivity	Dust Emission Magnitude		
	Large	Medium	Small
High	High	Medium	Low
Medium	Medium	Low	Negligible
Low	Low	Low	Negligible

Step 3

3.2.19 Step 3 requires the identification of site specific mitigation measures within the IAQM guidance⁸ to reduce potential dust impacts based upon the relevant risk categories

⁸ Guidance on the Assessment of Dust from Demolition and Construction V1.1, IAQM, 2016.

identified in Step 2. For sites with **negligible** risk, mitigation measures beyond those required by legislation are not required. However, additional controls may be applied as part of good practice.

Step 4

3.2.20 Once the risk of dust impacts has been determined and the appropriate mitigation measures identified, the final step is to determine the significance of any residual impacts. For almost all construction activity, the aim should be to control effects through the use of effective mitigation. Experience shows that this is normally possible. Hence the residual effect will normally be **not significant**.

3.2.21 The determination of significance relies on professional judgement and reasoning should be provided as far as practicable. The IAQM guidance suggests the provision of details of the assessor's qualifications and experience. These are provided in Appendix 1.

3.3 Operational Phase Assessment

Potential Development Impacts

3.3.1 The development has the potential to increase concentrations of NO₂, PM₁₀ and PM_{2.5} as a result of road traffic exhaust emissions associated with vehicles travelling to and from the site during the operational phase. An assessment was therefore undertaken using the criteria contained within the IAQM 'Land-Use Planning & Development Control: Planning for Air Quality'⁹ guidance to determine the potential for trips generated by the development to affect local air quality.

3.3.2 The following criteria are provided to help establish when an assessment of potential impacts on the local area is likely to be considered necessary:

- A change of Light Duty Vehicle (LDV) flows of more than 100 Annual Average Daily Traffic (AADT) within or adjacent to an AQMA or more than 500 AADT elsewhere;
- A change of HDV flows of more than 25 AADT within or adjacent to an AQMA or more than 100 AADT elsewhere;

⁹ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

- Realignment of roads where the change is 5m or more and the road is within an AQMA; or,
- Introduction of a new junction or removal of an existing junction near to relevant receptors.

3.3.3 Should these criteria not be met, then the IAQM guidance¹⁰ considers air quality impacts associated with a scheme to be **not significant** and no further assessment is required.

3.3.4 Should screening of the relevant data indicate that any of the above criteria are met, then potential impacts at sensitive receptor locations can be assessed by calculating the change in pollutant concentrations as a result of the proposed development. The significance of predicted impacts can then be determined in accordance with the methodology outlined in the IAQM guidance¹¹.

Potential Future Exposure

3.3.5 The proposed development comprises residential land use. This is considered a location of relevant exposure for long and short term AQOs in accordance with the criteria provided within DEFRA guidance¹², as summarised in Table 2. Existing air quality conditions at the site were therefore assessed through consideration of the following factors:

- AQMA designations;
- Proximity to significant pollution sources;
- Local monitoring results; and,
- Background pollutant concentration predictions.

3.3.6 The findings were subsequently used to determine the potential for AQO exceedences at the development location. Should the assessment indicate significant uncertainty over air quality conditions at the site then further quantitative methods, such as detailed dispersion modelling, could be utilised to refine predictions.

¹⁰ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

¹¹ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

¹² Local Air Quality Management Technical Guidance (TG16), DEFRA, 2021.

4.0 BASELINE

4.1 Introduction

- 4.1.1 Existing air quality conditions in the vicinity of the proposed development were identified in order to provide a baseline for assessment. These are detailed in the following Sections.

4.2 Local Air Quality Management

- 4.2.1 As required by the Environment Act (1995), MCC has undertaken Review and Assessment of air quality within their area of jurisdiction. This process has indicated that annual mean NO₂ concentrations are above the AQO within the city. As such, a number of roads within Manchester have been included within the Greater Manchester Combined Authority (GMCA) AQMA. This is described as follows:

"This is the part of the Greater Manchester Combined Authority AQMA located within the Manchester City Council area."

- 4.2.2 The development is located 50m west of the AQMA. As such, there is the potential for vehicles travelling to and from the site to increase pollution levels in this sensitive area. This has been considered throughout the assessment.
- 4.2.3 MCC has concluded that concentrations of all other pollutants considered within the AQs are currently below the relevant AQOs. As such, no further AQMAs have been designated.

4.3 Air Quality Monitoring

- 4.3.1 Monitoring of pollutant concentrations is undertaken by MCC throughout their area of jurisdiction. Recent annual mean NO₂ results recorded in the vicinity of the development are shown in Table 11. Exceedences of the AQO are shown in **bold**.

Table 11 Monitoring Results

Monitoring Site		Monitored NO ₂ Concentration (µg/m ³)		
		2017	2018	2019
MA37NO	Princess Road	42.6	39.3	38.7

4.3.2 As shown in Table 11, annual mean NO₂ concentrations were above the AQO at the MA37NO - Princess Road monitoring site during 2017. As this monitor is located in close proximity to an A-road within an AQMA, elevated concentrations would be expected. It should be noted that NO₂ levels at this location have since dropped below the relevant AQO.

4.3.3 Reference should be made to Figure 2 for a map of the survey position.

4.3.4 MCC do not undertake PM₁₀ or PM_{2.5} monitoring within the vicinity of the site.

4.4 Background Pollutant Concentrations

4.4.1 Predictions of background pollutant concentrations on a 1km by 1km grid basis have been produced by DEFRA for the entire of the UK to assist LAs in their Review and Assessment of air quality. The proposed development site is located in grid square NGR: 381500, 393500. Data for this location was downloaded from the DEFRA website¹³ for the purpose of the assessment and is summarised in Table 12.

Table 12 Background Pollutant Concentration Predictions

Pollutant	Predicted 2021 Background Pollutant Concentration (µg/m ³)
NO ₂	16.14
PM ₁₀	12.06
PM _{2.5}	8.22

4.4.2 As shown in Table 12, predicted background NO₂, PM₁₀ and PM_{2.5} concentrations are below the relevant AQOs and AQLV at the development site. The annual mean PM_{2.5} concentration is also below the WHO guideline.

¹³ <http://uk-air.defra.gov.uk/data/laqm-background-maps?year=2018>.

4.5 Sensitive Receptors

- 4.5.1 A sensitive receptor is defined as any location which may be affected by changes in air quality as a result of a development. Receptors sensitive to potential dust impacts during earthworks and construction were identified from a desk-top study of the area up to 350m from the development boundary. These are summarised in Table 13.

Table 13 Earthworks and Construction Dust Sensitive Receptors

Distance from Site Boundary (m)	Approximate Number of Human Receptors	Approximate Number of Ecological Receptors
Up to 20	10 - 100	0
Up to 50	10 - 100	0
Up to 100	More than 100	-
Up to 350	More than 100	-

- 4.5.2 Receptors sensitive to potential dust impacts from trackout were identified from a desk-top study of the area up to 50m from the road network within 500m of the site access. These are summarised in Table 14.

Table 14 Trackout Dust Sensitive Receptors

Distance from Site Access Route (m)	Approximate Number of Human Receptors	Approximate Number of Ecological Receptors
Up to 20	More than 100	0
Up to 50	More than 100	0

- 4.5.3 There are no ecological receptors within 50m of the development boundary or the access route within 500m of the site entrance. As such, ecological impacts have not been assessed further within this report.
- 4.5.4 A number of additional factors have been considered when determining the sensitivity of the surrounding area. These are summarised in Table 15.

Table 15 Additional Area Sensitivity Factors to Potential Fugitive Dust Impacts

Guidance	Comment
Whether there is any history of dust generating activities in the area	The desk top study did not indicate any dust generating activities in the local area
The likelihood of concurrent dust generating activity on nearby sites	A review of the planning portal did not indicate any additional development proposals likely to result in concurrent dust generation in the vicinity of the site
Pre-existing screening between the source and the receptors	The site is screened by existing buildings to the north, east and west with trees located to the south. These may act as a constraint to dust dispersion during parts of the construction phase
Conclusions drawn from analysing local meteorological data which accurately represent the area: and if relevant the season during which works will take place	As shown in Figure 3, the predominant wind bearing at the site is from the south-west. As such, receptors to the north-east of the boundary are most likely to be affected by dust releases
Conclusions drawn from local topography	There are no significant topographical constraints to dust dispersion
Duration of the potential impact, as a receptor may become more sensitive over time	Currently it is unclear as to the duration of the construction phase. However, it is possible that it will extend over one year
Any known specific receptor sensitivities which go beyond the classifications given in the document	No specific receptor sensitivities identified during the baseline assessment

4.5.5 Based on the criteria shown in Table 5, the sensitivity of the receiving environment to potential dust impacts was determined as **high**. This was because the identified receptors included residential properties.

4.5.6 The sensitivity of the receiving environment to specific potential dust impacts, based on the criteria shown in Section 3.2, is shown in Table 16.

Table 16 Sensitivity of the Surrounding Area to Potential Dust Impacts

Potential Impact	Sensitivity of the Surrounding Area		
	Earthworks	Construction	Trackout
Dust Soiling	High	High	High
Human Health	Low	Low	Medium

5.0 ASSESSMENT

5.1 Introduction

- 5.1.1 There is the potential for air quality impacts as a result of the construction and operation of the proposed development, as well as exposure of future residents to any existing air quality issues. These factors are assessed in the following Sections.

5.2 Construction Phase Assessment

Step 1

- 5.2.1 The undertaking of activities such as excavation, ground works, cutting, construction, concrete batching and storage of materials has the potential to result in fugitive dust emissions throughout the construction phase. Vehicle movements on the local road network also have the potential to result in the re-suspension of dust from highway surfaces.
- 5.2.2 The potential for impacts at sensitive locations depends significantly on local meteorology during the undertaking of dust generating activities, with the most significant effects likely to occur during dry and windy conditions.
- 5.2.3 The desk-study undertaken to inform the baseline identified a number of sensitive receptors within 350m of the site boundary. As such, a detailed assessment of potential dust impacts was required.

Step 2

Earthworks

- 5.2.4 Earthworks will primarily involve excavating material, haulage, tipping and stockpiling, as well as site levelling and landscaping. The area of the proposed development site is less than 2,500m². In accordance with the criteria outlined in Table 4, the magnitude of potential dust emissions from earthworks is therefore **small**.

5.2.5 Table 16 indicates the sensitivity of the area to dust soiling effects on people and property is **high**. In accordance with the criteria outlined in Table 9, the development is considered to be a **low** risk site for dust soiling as a result of earthworks.

5.2.6 Table 16 indicates the sensitivity of the area to human health impacts is **low**. In accordance with the criteria outlined in Table 9, the development is considered to be a **negligible** risk site for human health impacts as a result of earthworks.

Construction

5.2.7 Due to the size of the proposals, the total building volume is likely to be less than 25,000m³. In accordance with the criteria outlined in Table 4, the magnitude of potential dust emissions from construction is therefore **small**.

5.2.8 Table 16 indicates the sensitivity of the area to dust soiling effects on people and property is **high**. In accordance with the criteria outlined in Table 9, the development is considered to be a **low** risk site for dust soiling as a result of construction activities.

5.2.9 Table 16 indicates the sensitivity of the area to human health impacts is **low**. In accordance with the criteria outlined in Table 9, the development is considered to be a **negligible** risk site for human health impacts as a result of construction activities.

Trackout

5.2.10 Based on the site area and existing hard standing provision, it is anticipated that the unpaved road length will be less than 50m. In accordance with the criteria outlined in Table 4, the magnitude of potential dust emissions from trackout is therefore **small**.

5.2.11 Table 16 indicates the sensitivity of the area to dust soiling effects to people and property is **high**. In accordance with the criteria outlined in Table 10, the development is considered to be a **low** risk site for dust soiling as a result of trackout activities.

5.2.12 Table 16 indicates the sensitivity of the area to human health impacts is **medium**. In accordance with the criteria outlined in Table 10, the development is considered to be a **negligible** risk site for human health impacts as a result of trackout activities.

Summary of the Risk of Dust Effects

5.2.13 A summary of the risk from each dust generating activity is provided in Table 17.

Table 17 Summary of Potential Unmitigated Dust Risks

Potential Impact	Risk		
	Earthworks	Construction	Trackout
Dust Soiling	Low	Low	Low
Human Health	Negligible	Negligible	Negligible

5.2.14 As indicated in Table 17, the potential risk of dust soiling is **low** from earthworks, construction and trackout. The potential risk of human health impacts is **negligible** from earthworks, construction and trackout.

5.2.15 It should be noted that the potential for impacts depends significantly on the distance between the dust generating activity and receptor location. Risk was predicted based on a worst-case scenario of works being undertaken at the site boundary closest to each sensitive area. Therefore, actual risk is likely to be lower than that predicted during the majority of the construction phase.

Step 3

5.2.16 The IAQM guidance¹⁴ provides potential mitigation measures to reduce impacts as a result of fugitive dust emissions during the construction phase. These have been adapted for the development site as summarised in Table 18. These may be reviewed prior to the commencement of construction works and incorporated into a Construction Environmental Management Plan (CEMP) or similar if required by the LA.

¹⁴ Guidance on the Assessment of Dust from Demolition and Construction V1.1, IAQM, 2016.

Table 18 Fugitive Dust Emission Mitigation Measures

Issue	Control Measure
Site management	• Display the name and contact details of person(s) accountable for air quality pollutant emissions and dust issues on the site boundary • Display the head or regional office contact information • Record and respond to all dust and air quality pollutant emissions complaints • Make the complaints log available to the LA upon request • Carry out regular site inspections, record inspection results, and make an inspection log available to the LA upon request • Increase the frequency of site inspections when activities with a high potential to produce dust and emissions and dust are being carried out, and during prolonged dry or windy conditions • Record any exceptional incidents, either on or off the site, and the action taken to resolve the situation is recorded in the log book
Preparing and maintaining the site	• Plan site layout: machinery and dust causing activities should be located away from receptors • Erect solid screens or barriers around dust activities or the site boundary that are, at least, as high as any stockpiles on site • Avoid site runoff of water or mud • Keep site fencing, barriers and scaffolding clean using wet methods • Remove materials from site as soon as possible
Operating vehicle/machinery and sustainable travel	• Ensure all vehicles switch off engines when stationary - no idling vehicles • Avoid the use of diesel or petrol powered generators and use mains electricity or battery powered equipment where practicable
Operations	• Only use cutting, grinding or sawing equipment fitted or in conjunction with suitable dust suppression techniques • Ensure an adequate water supply on the site for effective dust/particulate matter mitigation (using recycled water where possible) • Use enclosed chutes and conveyors and covered skips • Minimise drop heights and use fine water sprays wherever appropriate
Waste management	• Reuse and recycle waste to reduce dust from waste materials • Avoid bonfires and burning of waste materials
Construction	• Avoid scabbling (roughening of concrete surfaces) if possible • Ensure sand and other aggregates are stored in bunded areas and are not allowed to dry out
Trackout	• Ensure vehicles entering and leaving site are covered to prevent escape of materials • Implement a wheel washing system, if required

Step 4

- 5.2.17 Assuming the relevant mitigation measures outlined in Table 18 are implemented, the residual impacts from all dust generating activities is predicted to be **not significant**, in accordance with the IAQM guidance¹⁵.

5.3 Operational Phase Assessment

Potential Development Impacts

- 5.3.1 Any vehicle movements associated with the development will generate exhaust emissions on the local and regional road networks. Information provided by Mode Transport Planning, the Transport Consultants for the scheme, indicated the proposals are predicted to generate 69 vehicle movements per day.
- 5.3.2 Based on the provided information, the proposals are not anticipated to result in an increase of LDV flows of more than 500 AADT on any individual road link, or 100 AADT within the AQMA, include significant highway realignment or the introduction of a junction and there will not be a requirement for more than 25 HDV deliveries per day. As such, potential air quality impacts associated with operational phase road vehicle exhaust emissions are predicted to be **not significant**, in accordance with the IAQM¹⁶ screening criteria shown in Section 3.3.

Potential Future Exposure

- 5.3.3 The proposed development comprises land use sensitive to long and short term pollutant concentrations. As such, the proposed development has the potential to introduce new receptors into an area of poor air quality. Existing conditions at the site are therefore considered in the following Sections.

¹⁵ Guidance on the Assessment of Dust from Demolition and Construction V1.1, IAQM, 2016.

¹⁶ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

AQMA Designation

- 5.3.4 The site is located approximately 50m west of the GMCA AQMA which has been declared due to exceedences of the annual mean AQO for NO₂. The designation does not cover 1-hour NO₂ or annual mean or 24-hour mean PM₁₀ concentrations, indicating exceedences of these AQOs have not been identified within MCC's administrative extents. As such, they have not been considered further in the context of this assessment.
- 5.3.5 As the site is located within a residential area, it would be anticipated that there would be a need for an AQMA to cover nearby housing if exceedences of the AQOs had been recorded or predicted locally. As this is not the case, it is considered that exceedences of the AQOs are unlikely to occur at the proposed development.

Proximity to Significant Pollution Sources

- 5.3.6 A desk-top study was undertaken in order to identify any significant pollution sources within the vicinity of the site. The findings are provided in Table 19.

Table 19 Significant Pollution Sources

Source	Distance to Site (m)	Comment
A5145 - High Lane	40	The A5145 is a classified 'A' road with an AADT flow of 17,927 and HDV proportion of fleet of 3.4% during 2019 ^(a)
Cross Road	5	Cross Road is an unclassified minor road and is unlikely to be subject to high volumes of traffic

Note: (a) Source: Department for Transport, <https://roadtraffic.dft.gov.uk/manualcountpoints/57780>

- 5.3.7 As shown in Table 19, there are two identified pollutant sources within the vicinity of the site. The A5145 - High Lane is distanced from the boundary of the site and Cross Road is minor in nature. As such, it is considered unlikely these sources will contribute significantly to pollution levels above background at the proposed development.

Local Monitoring Results

- 5.3.8 As shown in Table 11, MCC undertake monitoring of NO₂ concentrations at one location in the vicinity of the proposed development. The MA37NO - Princess Road monitor is

situated at a roadside location in the GMCA AQMA. The annual mean NO₂ concentrations recorded at this site were below the relevant AQO in 2018 and 2019.

5.3.9 As the monitor is positioned in close proximity to the A5145 within an AQMA, elevated concentrations would be expected at this location. The proposed development is distanced from the A5145 and is 50m west of the AQMA. It should be noted that pollutant levels decrease with distance from pollutant sources. As such, lower NO₂ concentrations than those recorded at the MA37NO - Princess Road monitor would be expected at the site.

5.3.10 Based on the above, exceedences of the relevant AQO are considered unlikely at the development location.

Background Pollutant Concentration Predictions

5.3.11 As shown in Table 12, predicted background pollutant concentrations for the grid square containing the site were below the AQOs and AQLV during 2021.

5.3.12 Predicted background PM_{2.5} concentrations were also below the WHO guideline during 2021.

5.3.13 Based on the predicted background concentrations, exceedences of the AQOs, AQLV and WHO guideline are considered unlikely at the development location.

Summary

5.3.14 It is considered likely that pollutant concentrations are below the relevant AQO at the proposed development site for the following reasons:

- The site is not located within an AQMA;
- The site is distanced from major pollutant sources;
- Review of local monitoring results has indicated likely compliance with the AQO for NO₂ at the development; and,
- Predicted background concentrations are below the relevant AQOs, AQLV and WHO guideline.

5.3.15 Based on the assessment results, exposure of future residents to exceedences of the relevant AQOs and AQTV is not considered likely. As such, the site is considered suitable for the proposed use from an air quality perspective.

Mitigation

5.3.16 As air quality impacts associated with the proposals were predicted to be **negligible**, further mitigation to control effects is not considered necessary. However, a number of additional measures have been included within the scheme in accordance with the requirements of the IAQM document 'Land-Use Planning & Development Control: Planning for Air Quality'¹⁷ to encourage the use of sustainable transport modes, manage vehicle flow and reduce pollution around the site. Table 20 describes the good practice principles detailed in the IAQM guidance along with how each has been addressed with regards to the proposals.

Table 20 Good Practice Design Principles

Phase	Principle	Action
Design Phase	New developments should not contravene the Council's Air Quality Action Plan ¹⁸ , or render any of the measures unworkable	It is confirmed that the proposals will not contravene MCC's Air Quality Action Plan, or render any of the measures unworkable
	Wherever possible, new developments should not create a new "street canyon", or a building configuration that inhibits effective pollution dispersion	The proposals will not lead to the generation of a street canyon
	Delivering sustainable development should be the key theme of any application	The proposals have been designed to encourage sustainable behaviours, such as active and public transport, due to its close proximity to local bus routes and amenities

¹⁷ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

¹⁸ Greater Manchester Air Quality Action Plan (GMAQAP) 2016-2021, GMCA, 2016.

Phase	Principle	Action
Operational Phase	As requested by Laura Miller, Environmental Protection Officer at MCC, MCC's Electric Vehicle (EV) Charging Best Practice Recommendations have been considered. These are: If car parking is being provide for residential units: - On-site/allocated parking: 1 EV charge point for each dwelling; or, - Unallocated parking: minimum 25% EV, and cable routes for all other spaces.	25% of parking spaces will be equipped with an EV charging point and cable routes will be provided for all other spaces
	Where development generates significant additional traffic, provision of a detailed Travel Plan (with provision to measure its implementation and effect) which sets out measures to encourage sustainable means of transport (public, cycling and walking) via subsidised or free-ticketing, improved links to bus stops, improved infrastructure and layouts to improve accessibility and safety	A Travel Plan can be produced for the development if requested by MCC
	All gas-fired boilers to meet a minimum standard of <40mgNO_x/kWh. All gas fired CHP plant to meet a minimum emissions standard of: - Spark ignition engine: 250mgNO_x/Nm³; - Compression ignition engine: 400mgNO_x/Nm³; - Gas turbine: 50mgNO_x/Nm³. A presumption should be to use natural gas-fired installations. Where biomass is proposed within an urban area it is to meet minimum emissions standards of - Solid biomass boiler: 275mgNO_x/Nm³ and 25mgPM/Nm³	Any boilers to be included in the development will be provisioned in accordance with the relevant requirements

5.3.17 It is considered the above methods would further reduce potential impacts associated with the proposals. Specific mitigation suited to the development may be stipulated as a planning condition if deemed necessary by the LA.

6.0 CONCLUSION

- 6.1.1 Redmore Environmental Ltd was commissioned by Southway Devco Limited to undertake an Air Quality Assessment in support of a planning application for a residential development on land at the Chorlton Irish Club, High Lane, Chorlton.
- 6.1.2 The proposals have the potential to cause air quality impacts as a result of fugitive dust emissions during construction and road traffic exhaust emissions associated with vehicles travelling to and from the site during operation, as well as expose future residents to any existing air quality issues. As such, an Air Quality Assessment was undertaken in order to determine baseline conditions and assess potential effects as a result of the development.
- 6.1.3 During the construction phase of the development there is the potential for air quality impacts as a result of fugitive dust emissions from the site. These were assessed in accordance with the IAQM methodology. Assuming good practice dust control measures are implemented, the residual significance of potential air quality impacts from dust generated by earthworks, construction and trackout activities was predicted to be **not significant**.
- 6.1.4 Potential impacts during the operational phase of the proposed development may occur due to road traffic exhaust emissions associated with vehicles travelling to and from the site. These were assessed against the screening criteria provided within the IAQM¹⁹ guidance document. Due to the scale of the proposals, impacts were predicted to be **not significant**.
- 6.1.5 The potential for exposure of future residents to exceedences of the AQOs was assessed based on the AQMA designation, proximity of pollution sources to the site, local monitoring results and predicted background concentrations. This indicated that concentrations of NO₂, PM₁₀ and PM_{2.5} are likely to be below the relevant AQOs, AQLV and WHO guideline at the development location. As such, the site is considered suitable for the proposed use from an air quality perspective.


¹⁹ Land-Use Planning & Development Control: Planning for Air Quality, IAQM, 2017.

6.1.6 Based on the assessment results, air quality issues are not considered a constraint to planning consent for the development.

7.0 **ABBREVIATIONS**

AADT	Annual Average Daily Traffic
AQAP	Air Quality Action Plan
AQLV	Air Quality Limit Value
AQMA	Air Quality Management Area
AQO	Air Quality Objective
AQS	Air Quality Strategy
AQTV	Air Quality Target Value
CEMP	Construction Environmental Management Plan
DEFRA	Department for Environment, Food and Rural Affairs
EV	Electric Vehicle
GMCA	Greater Manchester Combined Authority
HDV	Heavy Duty Vehicle
IAQM	Institute of Air Quality Management
LA	Local Authority
LAQM	Local Air Quality Management
LDV	Light Duty Vehicle
MCC	Manchester City Council
NGR	National Grid Reference
NO ₂	Nitrogen dioxide
NPPF	National Planning Policy Framework
NPPG	National Planning Policy Guidance
PM ₁₀	Particulate matter with an aerodynamic diameter of less than 10µm
PM _{2.5}	Particulate matter with an aerodynamic diameter of less than 2.5µm
WHO	World Health Organisation

Figures



Legend



Site Boundary

Title

Figure 1 - Site Location Plan

Project

Air Quality Assessment
High Lane, Chorlton

Project Reference

4043


Client


Southway Devco Limited

Contains Ordnance Survey Data
© Crown Copyright and Database Act 2019



www.red-env.co.uk | 0161 7060075





Legend

Title

Figure 3 - Wind Rose of 2019
Manchester Airport Meteorological
Data

Project

Air Quality Assessment
High Lane, Chorlton

Project Reference

4043

Client

Southway Devco Limited



www.red-env.co.uk | 0161 7060075

Appendix 1 - Curricula Vitae

KEY EXPERIENCE:

Jethro is a Chartered Environmentalist and Director of Redmore Environmental with specialist experience in the air quality and odour sectors. His key capabilities include:

- Production and management of Air Quality, Dust and Odour Assessments for a wide-range of clients from the retail, residential, infrastructure, commercial and industrial sectors.
- Production and co-ordination of Environmental Permit applications for a variety of industrial sectors.
- Detailed dispersion modelling of road vehicle and industrial emissions using ADMS-Roads, ADMS-5, AERMOD-PRIME and BREEZE-ROADS. Studies have included impact assessment of ground level pollutant and odour concentrations and assessment of suitability of development sites for proposed end-use.
- Project management and co-ordination of Environmental Impact Assessments and scoping reports for developments throughout the UK.
- Provision of expert witness services at Planning Inquiries.
- Design and project management of pollutant monitoring campaigns.
- Co-ordination and management of large-scale multi-disciplinary projects and submissions.
- Provision of expert advice to local government and international environmental bodies, as well as involvement in production of industry guidance.

SELECT PROJECTS SUMMARY:

Industrial

Shanks Waste Management - Odour Assessments of two waste management facilities to support Environmental Permit Applications.

Tatweer Petroleum - dispersion modelling of Bahrain oil field.

Doha South Sewage Treatment Works - AQA for works extension in Qatar.

IRIS Environmental Appraisal Report Reviews, Isle of Man Government - odour assessment reviews.

Lankem, Greater Manchester - Environmental Permit Application for chemical manufacturing plant.

Newport Docks Bulk Drying, Pelleting and CHP Facility - air quality EIA for gas CHP.

Springshades, Leicester - Environmental Permit Variation Application for textile manufacturing plant.

Valspar, Chester - Odour Assessment and production of Odour Management Plan for a paint manufacturing plant in response to neighbour complaints.

Agrivert - dispersion modelling of odour and CHP emissions from numerous AD plants.

James Cropper Paper Mill, Cumbria - air quality EIA, Environmental Permit Variation and Human Health Risk Assessment for new biomass boiler adjacent to SSSI.

Rigg Approach, Leyton - Air Quality Assessment in support of waste transfer site.

Lynchford Lane Waste Transfer Station - biomass facility energy recovery plant.

Barnes Wallis Heat and Power, Cobham - biomass facility adjacent to AQMA.

Residential

Wood St Mill, Bury - residential development adjacent to scrap metal yard.

Hyams Lane, Holbrook - Odour Assessment to support residential development adjacent to sewage works.

North Wharf Gardens, London - peer review of EIA undertaken for large residential development.

Loxford Road, Alford - Air Quality EIA for residential development, included consideration of impacts from associated package sewage works

Elephant and Castle Leisure Centre - baseline AQA for redevelopment.

Carr Lodge, Doncaster - EIA for large residential development.

Queensland Road, Highbury - residential scheme including CHP.

Bicester Ecotown - dispersion modelling of energy centre.

Castleford Growth Delivery Plan - baseline air quality constraints assessment for town redevelopment.

York St, Bury - residential development adjacent to AQMA.

Temple Point Leeds - residential development adjacent to M1.

Commercial and Retail

Etihad Stadium - Air Quality EIA for the extension to the capacity of the Etihad Stadium, Manchester.

Wakefield College - redevelopment of city centre campus in AQMA.

Manchester Airport Cargo Shed - commercial development.

Manchester Airport Apron Extension - EIA including aircraft emission modelling.

National Youth Theatre, Islington - redevelopment to provide new arts space and accommodation.

KEY EXPERIENCE:

Ceri is a Graduate Environmental Consultant with specialist experience in the air quality sector. Her key capabilities include:

- Production of Air Quality Assessments in accordance with Department for Environment, Food and Rural Affairs (DEFRA) methodologies for a range of residential, commercial and industrial sectors.
- Detailed dispersion modelling of road vehicle exhaust emissions using ADMS-Roads. Studies have included assessment of road traffic exhaust emissions on sensitive receptors and exposure of new residents to poor air quality.
- Advanced Canyon Modelling to evaluate the impact of altered urban topography on air quality in built up areas.
- Assessment of construction dust impacts from a range of development sizes.
- Definition of baseline air quality and identification of sensitive areas across the UK.
- Odour surveys to assess amenity and suitability of sites for potential future development for residential use.

SELECT PROJECTS SUMMARY:

Warren Street, Stockport

Air Quality Assessment in support of a residential-led development comprising 553 apartments and two commercial units located in an Air Quality Management Area (AQMA). The development had the potential to expose future occupants to poor air quality and cause impacts at sensitive locations. Detailed dispersion modelling and a construction dust assessment indicated air quality factors were not a constraint to the development.

Belgrave Gate, Leicester

Air Quality Assessment in support of the conversion of an existing building to provide three residential units on Belgrave Gate, Leicester. The scheme was located in an AQMA, alongside a bus station. As such, the development had potential to expose future residents to elevated pollution levels and adverse air quality effects. Results of detailed dispersion modelling utilising advanced canyons and a volume source to represent the bus station indicated air quality issues were not a constraint to planning consent for the development.

Kings Arms Hotel, Stansted

Odour Assessment in support of a Discharge of Condition application for a consented development on land to the rear of the Kings Arms Hotel, Stansted. The site was located in close proximity to several fast food restaurants which have the potential to cause odour emissions during normal operation. A mitigation scheme was therefore identified to protect future residents from loss of amenity. Subject to the inclusion of the specified mitigation, overall effects of odour were considered to be not significant at the development.

Manchester Road West, Little Hulton

Odour Assessment in support of construction of 152 residences on land off Manchester Road West, Little Hulton. The development was located in the vicinity of several waste management facilities which may form a source of odour emissions and cause loss of amenity for future residents. A two stage Odour Assessment was undertaken to assess baseline conditions across the site and consider the risk of reduced amenity. Results of the assessment indicated odour effects at the site did not represent a constraint to planning consent.

Gravel Pit Farm, Sand Hutton

Odour Assessment in support of the conversion of existing buildings into two residential dwellings on land at Gravel Pit Farm, Sand Hutton. The development was located in the vicinity of the Sand Hutton Anaerobic Digestion Plant, which may form a source of odour emissions and cause loss of amenity for future residents. Results of a two stage Odour Assessment indicated odour effects at the site were not significant. As such, odour was not considered to represent a constraint to planning consent.

A1 Trunk Road, Long Bennington

Odour Assessment in support of a residential development on land off the A1 Trunk Road, Long Bennington. The development was located in the vicinity of a maggot farm growing bait for fishermen. Results of a two stage Odour Assessment indicated that at the location of the proposed dwellings, impacts were not at a level considered to cause loss of amenity as a result of emissions. As such, odour was not considered to represent a constraint to planning consent.

KEY EXPERIENCE:

Emily is an Environmental Consultant with specialist experience in the air quality sector. Her key capabilities include:

- Production of Air Quality Assessments in accordance with Department for Environment, Food and Rural Affairs (DEFRA) methodologies for a range of residential, commercial and industrial sectors.
- Detailed dispersion modelling of road vehicle exhaust emissions using ADMS-Roads. Studies have included assessment of road traffic exhaust emissions on sensitive receptors and exposure of new residents to poor air quality.
- Advanced canyon modelling to evaluate the impact of altered urban topography on air quality in built up areas.
- Assessment of construction dust impacts from a range of development sizes.
- Definition of baseline air quality and identification of sensitive areas across the UK.
- Production of air quality mitigation strategies specifically tailored to address issues at individual sites.
- Air quality monitoring at industrial sites to quantify pollutant concentrations
- Odour surveys to assess amenity and suitability of sites for potential future development for residential use.

SELECT PROJECTS SUMMARY:

Bowlers Yard, Manchester

Air Quality Assessment in support of an eleven storey residential development to provide circa 65 units on land known as Bowlers Yard, Manchester. The site was located in an Air Quality Management Area (AQMA) and concerns were raised regarding the exposure of future occupants to poor air quality due to road traffic emissions. Detailed dispersion modelling was undertaken using ADMS-roads to assess PM_{2.5}, PM₁₀ and NO₂ concentrations across the site. Results indicated that pollution levels were below the air quality objectives across the development.

Freemasons Arms Hotel, Heywood

Air Quality Assessment to support a residential-led development in an AQMA. Detailed dispersion modelling was undertaken with the inclusion of advanced canyon modelling to evaluate the impact of the urban topography within the locality on the dispersion of traffic related pollutants. Predicted concentrations of NO₂ were found to exceed air quality criteria at the building façade fronting Market Place at first floor level. As such, mitigation was specified for the affected units to ensure future residents would not be exposed to poor air quality.

Griffin Road, London

Air Quality Assessment in support of a residential development located in an AQMA. Detailed dispersion modelling was undertaken using ADMS-roads to assess PM₁₀ and NO₂ concentrations across the site. Results indicated that pollution levels were classified as APEC - A in accordance with the London Councils Air Quality and Planning Guidance.

High Street, Dudley

Odour Impact Assessment in support of a proposed residential-led development. Due to the location of the site, being above an existing hot food takeaway, odour surveys were required to assess the level of odour across the development. A risk assessment was also undertaken in accordance with the relevant odour guidance. An appropriate ventilation system was identified on the basis of the assessment results.

East Common Lane, Selby

Air Quality Assessment in support of an industrial development on land associated with Access 63 Business Park, East Common Lane Selby. Due to the size of the development it was possible that traffic generated from the scheme may cause negative impacts on sensitive receptors nearby. NO₂ and PM₁₀ concentrations were quantified at specific receptor points to ensure there would be no significant increases in pollution levels. Results revealed negligible impacts.

Wharton Road, Winsford

Air Quality Assessment in support of a residential development of circa 138 units on land off Wharton Road, Winsford. Using sensitive receptors, located in areas where increased road traffic may affect NO₂ concentrations, a comparison was made between overall concentrations with and without the development in place. Results revealed pollutant concentrations were below the relevant standards across the site and impacts were not significant.