

Product Stock Code	Load Profile	Energy Efficiency Class	Heat Loss		Energy Efficiency %	Annual Consumption (kWh/annum)	Thermostat Temperature Setting	Sound Power Level	Capacity (Total Volume)	Pressure Regulator 3 bar inlet group c/w balance cold supply, expansion vessel connection and expansion valve set at 4.5 bar	Expansion Vessel size. Pre-charged to 3 bar	Overall Height		Overall Diameter		Weight Empty	Weight Full	kW Rating of Primary Coil		Pressure Loss Across Primary Heater Coil
			Watts	kWh/24h	%	kWh	°C	db	Litres	bar	Litres	mm	mm	KG	KG	kW	bar			
Direct																				
GESINPDR090	L	C	36	0.87	37%	2737	62	15	93	3	12	706	530	15	108	n/a	n/a			
SESINPDR120	L	C	43	1.03	37%	2755	62	15	118	3	12	832	530	19	137	n/a	n/a			
SESINPDR150	M	C	52	1.24	36%	1410	62	15	149	3	19	1012	530	22	171	n/a	n/a			
SESINPDR170	M	C	57	1.37	36%	1417	62	15	169	3	19	1131	530	24	193	n/a	n/a			
SESINPDR200	L	C	65	1.56	37%	2773	62	15	198	3	25	1305	530	27	225	n/a	n/a			
SESINPDR250	L	C	79	1.89	37%	2763	62	15	248	3	25	1603	530	33	281	n/a	n/a			
Indirect																				
SESINPIN090	n/a	B	36	0.87	n/a	n/a	n/a	n/a	93	3	12	706	530	17	110	13.4	0.15			
SESINPIN120	n/a	B	43	1.03	n/a	n/a	n/a	n/a	118	3	12	832	530	20	138	14.6	0.16			
SESINPIN150	n/a	B	52	1.24	n/a	n/a	n/a	n/a	149	3	19	1012	530	23	172	14.0	0.14			
SESINPIN170	n/a	B	57	1.37	n/a	n/a	n/a	n/a	169	3	19	1131	530	26	195	16.2	0.19			
SESINPIN200	n/a	C	65	1.56	n/a	n/a	n/a	n/a	198	3	25	1305	530	29	227	16.0	0.18			
SESINPIN250	n/a	C	79	1.89	n/a	n/a	n/a	n/a	248	3	25	1603	530	35	283	16.7	0.21			
SESINPIN300	n/a	C	92	2.20	n/a	n/a	n/a	n/a	295	3	35	1895	530	41	336	18.3	0.23			

1 Red
2 Red