


Technical Specification

Control Point	Head (m)	Flow (l/s)
Primary Design	1.500	5.000
Flush-Flo	0.431	4.879
Kick-Flo®	0.878	3.900
Mean Flow		4.321



PT/329/0412

hydro-int.com/patents



Head (m)	Flow (l/s)
0.000	0.000
0.052	1.259
0.103	3.316
0.155	4.142
0.207	4.464
0.259	4.667
0.310	4.789
0.362	4.853
0.414	4.878
0.466	4.874
0.517	4.850
0.569	4.809
0.621	4.750
0.672	4.668
0.724	4.555
0.776	4.398
0.828	4.184
0.879	3.914
0.931	4.007
0.983	4.108
1.034	4.206
1.086	4.302
1.138	4.396
1.190	4.487
1.241	4.576
1.293	4.664
1.345	4.749
1.397	4.833
1.448	4.915
1.500	4.996

DESIGN ADVICE



The head/flow characteristics of this SHE-0098-5000-1500-5000 Hydro-Brake Optimum® Flow Control are unique. Dynamic hydraulic modelling evaluates the full head/flow characteristic curve.

The use of any other flow control will invalidate any design based on this data and could constitute a flood risk.

Hydro
International

DATE 06/04/2021 19:53

Site Gorebrook

DESIGNER Andrew Mulligan

Ref 12454

SHE-0098-5000-1500-5000

Hydro-Brake Optimum®