

BS - Lift Cap
21130

The installation of the dry lining works are to be in accordance with NBS Clause K10/435. The setting out of the metal framing for the external wall linings are to be in accordance with NBS Clause K10/455.

Flush glazed Roof light to NBS doc L10

Single ply membrane dressed onto Timber wall plate to SE details and Specification, all to be installed as per specialist manufacturer's details and specification.

Timber block to to SE details and specification contained within SFS wall stud head, supporting Roof light fixing details to specialists manufacturer's details and specifications

Single ply Protan membrane to NBS clause J42 110A 400 or similar approved, adhered to insulation.

Warm roof insulation system, to NBS clause J42 230 430, mechanically fixed to 18mm plywood decking system on timber firings.

Timber joists fixed to timber blocking to web of steel via joist hanger all to SE details and specifications.

Refer to Reflected Ceiling Plans drawing series 35.

Beech Wall Type 09 as NBS Clause K10/175C fixed in accordance with manufacturer's standard details and specification.

Prior to areas being closed up by dry lining an inspection of the fire stopping works should be undertaken in accordance with NBS Clause P12/920.

1 LIGHT WELL - ROOF LIGHT SLOPED KERB SECTION

1 : 10

2 LIGHT WELL - ROOF LIGHT KERB SECTION

1 : 10

Single ply Protan membrane to NBS clause J42 110A 400 or similar approved, adhered to 9mm ply board fixed over concrete lift cap to SE details and specifications

Flashing to be dressed into block work wall with plyboard fixed above and single ply adhered over, detail to specialist installer and manufacturer specifications and arrangements

Flush glazed Roof light to NBS doc L10

Timber block to to SE details and specification supporting Roof light fixing details to specialists manufacturer's details and specifications. Element of structure to be fire proofed to Fire engineers details, 2 x layers of Fireline board to be fixed to face of blocks.

Internal Wall Type 09 (22 series) refer to detail sheets 013-MDB-BS-ZZ-DT-A-2301/2302
Knauf 30mm vertical top hat framing channel with 1x 10mm Rockpanel Ply to achieve a Fire Rating of A2, board to be paint RAL 9010 (Pure White)

Internal Wall Type 08 (22 series) refer to detail sheets 013-MDB-BS-ZZ-DT-A-2301/2302
Blockwork to SE details and specification

Prior to areas being closed up by dry lining an inspection of the fire stopping works should be undertaken in accordance with NBS Clause P12/920.

3 LIGHT WELL - ROOF LIGHT TO LIFT WALL SECTION

1 : 10

GENERAL NOTES

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE STATED.
2. ALL LEVELS ARE IN METRES UNLESS OTHERWISE STATED.
3. DIMENSIONS ARE NOT TO BE SCALED FROM THE DRAWING.
4. ALL WORK TO BE CARRIED OUT IN ACCORDANCE WITH THE CURRENT EDITION OF THE BUILDING REGULATIONS 1991 (INCLUDING AMENDMENTS) AND ALL RELEVANT BRITISH STANDARDS/CODES OF PRACTICE.
5. CONTRACTOR IS RESPONSIBLE FOR THE CORRECT SETTING OUT OF THE WORKS ON SITE. ALL DIMENSIONS TO BE CHECKED PRIOR TO FABRICATION OF MATERIALS.
6. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL RELEVANT DRAWINGS AND SPECIFICATIONS.
7. THIS DRAWING SHALL NOT BE DUPLICATED WITHOUT THE EXPRESS WRITTEN PERMISSION OF BEECH DESIGN AND BUILD LIMITED.

A ISSUED FOR TENDER NP 14-05-21

Rev Description By Date



CLIENT:

PICCADILLY WAREHOUSE

PROJECT:

BLOOM STREET
ROOF LEVEL
DETAIL DRAWINGS 1

DRAWING TITLE

TENDER

DRAWING STATUS

DRAWN: NP | CHECKED: NP

SCALE: 1 : 10 | DATE: 12.05.21

013-MDB-BS-RF-DT-A-2700 | A
DRAWING NUMBER REV

(A3)