

Due to high demand, bespoke colours will be dispatched within 7-10 working days. (Excluding weekends & Bank Holidays) [News](#)

[Home](#)[Call Us : 0845 838 2225 or 0330 122 4771](#)[Sign In](#)**Secure Payments****WE ARE OPEN FOR BUSINESS****WEBSITE ONLINE ORDERS 24/7****COVID-19 SAFE DELIVERY**[Metal Paint](#) ▾ [Intumescent Fire Retardant Paint](#) ▾ [Floor Paint](#) ▾ [Maintenance Paint](#) ▾ [Marine Paint](#) ▾ [Resins](#) ▾ [Vehicle Paint](#) ▾ [Aerosol Paint](#)[Paint Stripper | Remover](#) [Paint Thinners](#) | [Solvent](#) [Airless Paint Sprayers](#) [Stencil Kits](#) [Sundries](#) ▾ [Brands](#) ▾[« Back](#) [Home > Brands > Thermoguard Fire Paints](#)[Free Technical Advice](#)[COVID-19 Safe Delivery](#)[100's Of Colours](#)[Secure Checkout](#)

Thermoguard Fire Varnish Intumescent Wood Basecoat

Please choose your required colour



Clear

Select Options

Pack Size**Quantity****£121.99**

£101.66 ex VAT

[You'll earn 121 loyalty points with this purchase](#)[All BS | Ral Colours Manufactured To Order](#)**Add to Cart**

Product Description

Thermoguard Fire Varnish Wood Basecoat Overview

Thermoguard Fire Varnish Basecoat is a clear intumescent, fire retardant coating that is the first coat of a 2 coat system for the decorative Fire Protection of timber, wood and timber derivative substrates.

The systems special formula provides a tough, durable finish to internal and external panelling, cladding and trim.

Please see [Thermoguard Fire Varnish Overcoat](#).

The clear finish enhances the natural beauty of the substrate while fire protecting new and previously varnished surfaces. The protective Fire Varnish Overcoat provides protection against UV and wear, while offering a choice of sheen levels.

Thermoguard Fire Varnish achieves Class 1, Class O, EN Class B and can also achieve 30 minutes and 60 minutes Fire Resistance and provides Low Smoke Emission.

Tested to :

BS 476 Parts 7; Class 1 surface spread of flame.

BS 476 Part 6; Achieved – Fire propagation.

System is designated Class O in accordance with UK Building Regulations : European EN Class B.

Due to high demand, bespoke colours will be dispatched within 7-10 working days. (Excluding weekends & Bank Holidays) [News](#)

These certificates are most often referred to as a "Fire Certificate" but in fact are really a certificate of supply. They indicate the amount of product supplied and the fire rating that this quantity of product would achieve over an agreed specified surface area/substrate. After your application is approved: Thermoguard will then supply the certificate Free of Charge by email. All that remains is for the contractor to confirm by signature that the product was applied correctly in accordance with the relevant instructions and data sheets. There are many people who may need this certification: Building Managers, Insurance Companies, Building Control Departments etc. Thermoguard quickly issue a certificate of supply that is universally recognised and accepted.

Not only is it easy to apply for the certificate, it also free of charge and normally supplied to you by email within five days.

[APPLY FOR CERTIFICATE](#)

Specification

Brand	Thermoguard
Application	Brush, Roller, Spray
Drying Time	18 Hours
Overcoating Time	24 Hours
Finish	Matt
Size	20m² Packs
Recommended Thinner	Water
MPN	PT1984
GTIN	5021887047808

Related Products



Thermoguard Fire Varnish Interior Intumescent Overcoat

£61.99

[More Information](#)

Newsletter Sign Up

Name

Email

[Sign Up](#)

Due to high demand, bespoke colours will be dispatched within 7-10 working days. (Excluding weekends & Bank Holidays) [News](#)

[Colour Card](#)

[Delivery | Returns](#)

[FAQ's](#)

[Loyalty Points](#)

[A To Z](#)


[Sign In](#)

[Important Updates | News](#)

[Contact Us](#)

[Terms and Conditions](#)

[Privacy Policy](#)



Contact Us

Call : 0845 838 2225 or 0330 122 4771

Our Warehouse & Office Opening Hours

Mon - Fri 9.00am - 5.00pm
(Excluding Bank Holidays)