

SPECIFICATION FOR SHOP FRONTS.

- 1/ All of the joinery is to be manufactured from Utile, and is to be given one coat of GREY primer at our factory for further coats of paint by others.
- 2/ The two sets of straight sliding doors are to have three door leafs per set. One set of doors is to slide to the right as viewed from the outside (structural opening size 2990mm high x 3440mm wide), and the other set is to slide to the left as viewed from the outside (structural opening size 2990mm high x 3415mm wide). The end door leaf in both configurations will be fixed and will be to the inside.
- 3/ The centre section to the shop is to be in three equal width segments (structural opening size 2990mm high x 3710mm wide). The door is to be in the centre segment and is to open in and is to be right hand pull. It is to be hung on 4no free issue black butt hinges. All other ironmongery and furniture for this door is to be supplied and fitted by others. The left and right segments are to have fixed infills to match the opening centre door.
- 4/ The door frames for the straight sliding doors and under the fixed infill panels to the centre section, are to have Utile thresholds, but an aluminium threshold is to be supplied and fitted under the side hung door (see attached detail)
- 5/ All of the doors are to be 2050mm high and 57mm thick, with 150mm wide stiles and heads, and 220mm bottom rails. They are to be factory glazed with 6.4/12/6.4 clear laminated safety double glazed units with black spacer bars, using black glazing tape.
- 6/ The transom in all three door frames is to be the same.
- 7/ The fanlights are to be glazed with 6.4/12/6.4 clear laminated safety double glazed units with black spacer bars, using black glazing tape.
- 8/ The straight sliding doors are to be hung using the Rullo Plus system with high security locking mechanisms, operating handles, cylinders, and escutcheons. The ironmongery and furniture are to be satin stainless steel.