

* ALL NEW WINDOWS TO COMPLY FULLY WITH
CURRENT BUILDING REGULATIONS TO BE UPVC DOUBLE
GLAZED 16mm cavity Pilkington 1/2" GLASS SECTION
FILLED FOR 1.8 MAX U VALUE 1/20th OPENED &
BACKGROUND VENTILATION FITTED TO WINDOW HEADS
RETAIN SOLID CORE CHARACTER OVER WINDOWS WHERE
NECESSARY.

an **PLANNING**

ACK'D _____

REPLIED _____

REC'D **- 9 JAN 2009**

	NOT RECD	DATE
M		
N ☒		
M		

FOR ACTION _____

ALL INTERNAL DOORS TO BE FD 201/30 FIRE DOORS, INC US CURBOWED DOOR.

* ALL NEW BRICKWORK TO MATCH EXISTING, HUE, TINT AND COLOR AS NEAR AS POSSIBLE & TO BIND INTO EXISTING EXACTLY ALTERNATE COURSE OR OTHER PATTERN NOTED.

CAUTION: WHILE AS: FACING BRICKWORK WITH 30MM CAVITY CRITICAL WIND BATTERS - 100MM THICKENING SHIELD BLOCKWORK - PLASTERBOARD + TOBS + FACING (RE 2.310) VALUE MAX.

ROOF AS ABOVE SPECIFICATION BUT USING
SLATES TO MATCH EXISTING, HOUSE TYPE
AND COLOUR & RAFTERS TO BE 180X38MM
@ 400C/S

25MM MIN
WIDE CONTINUOUS
VENT GRILLES TO
GABLES

* BOND IN
NEW
BRICKWORK
TO EXISTING
EXTERIOR
CARSE

proposed rear elevation



proposed side elevation

