



# MOBILE & STATIC COMPACTORS

|      |   |                          |
|------|---|--------------------------|
| PAGE | 2 | MOBILE COMPACTORS        |
|      | 3 | STATIC COMPACTORS        |
|      | 4 | TECHNICAL SPECIFICATIONS |





# Mobile compactors

Keeping all compacted waste contained inside a QCR mobile compactor leaves any site safe, tidy and odour free; making this product an ideal waste solution for retailers, restaurants, hospitals, hotels, printers, factories, and distribution centres. With a minimum compaction ratios of 6:1, the QCR mobile compactors will not only significantly reduce your waste disposal costs but revenue can be created with the recycling of certain materials. Furthermore, by compacting your waste using our compactor, you will reduce the number of uplifts and can save up to 85% on your transport costs.

## VARIOUS LOADING OPTIONS AVAILABLE

- Bin lift from left, right or rear
- Hopper from left or right
- Sliding door
- Conveyor fed
- Vacuum fed
- Chute fed

## KEY FEATURES

- Minimum 6:1 compaction ratio
- Low loading height
- Easy to clean
- Automatic shut down
- Produces a 10m<sup>3</sup>-26m<sup>3</sup> skip of recyclables or general waste
- Can be easily modified





# Static compactors

The QCR static compactor is a 30 yard compactor designed to help you reduce waste costs as well as make the process as easy as possible for you. With various loading options available, you can choose the best way to save your business precious time and money. It is the perfect product for retailers, restaurants, hospitals, hotels, printers, factories, distribution centres, and of course recyclers looking to improve their carbon credentials.

## VARIOUS LOADING OPTIONS AVAILABLE

- Bin lift from left, right or rear
- Hopper from left or right
- Sliding door
- Conveyor fed
- Vacuum fed
- Chute fed



## KEY FEATURES

- Easy, quick and safe to operate
- Reduces uplifts and storage costs
- Creates immediate savings
- Keeps your site clean and tidy
- 3/4 full and full indicator
- Reduces carbon footprint





# Technical specifications

## STATIC COMPACTOR WITH & WITHOUT BIN LIFT

- Overall height 2493mm
- Overall width 2280mm
- Overall length 3320mm
- Machine weight 3500kg
- Electrics 415V, 3ph, 32amp
- Control panel voltage 24V
- Motor size 7.5kW
- Cycle time 45 seconds
- System pressure 145 bar
- Compaction force 32 tonnes
- Feed height 1240mm
- Back wall clearance 500mm
- Side wall clearance 1000mm
- Charge box volume 2m<sup>3</sup>
- Charge box width 1500mm



## MOBILE COMPACTOR

- Overall height 2539mm
- Overall width 2493mm
- Overall length 6898mm
- Machine weight 5800kg
- Electrics 415V, 3ph, 32amp
- Control panel voltage 24V
- Motor size 5.5kW
- Cycle time 45 seconds
- System pressure 230 bar
- Compaction force 38 tonnes

