

LIGHTING LEGEND

Ⓐ

WALL MOUNTED LIGHT - LIGHTINGSTYLES
NARROW SQUARE UP & DOWN IP44

Colour: Anthracite.
IP44 rated, protection from splashed water.

SPECIFICATION
Number Of Lamps 2
Lamp Type G10 Base Mains Lamps
Part L Compliant Luminaire No
Lamps Included No
Dimmable? Yes - on standard dimmer
(0-10VAC or leading edge)
Max Wattage/Use 70w
Total Wattage
Width 70mm
Height 225mm
Depth/Projection 70mm
Wiring Details Class 1 - Requires an Earth Connection
IP Rating IP44

Ⓑ

WALL MOUNTED LIGHT - THORN LIGHTING PIAZZA II LED 2700-840 HF

A robust IP65 outdoor wall mounted luminaire with a unique light distribution, ideal for building perimeter applications. Wall mountable.

Body: polycarbonate in anthracite colour (RAL 7016)
Diffuser: textured clear polycarbonate

Luminous emittance 1
Fitting: 1xLED 25 W
Light Output Ratio: 100%
Lamp luminous flux: 2910 lm
Luminaire luminous flux: 2910 lm
Power: 25.0W
Light yield: 116.4 lm/W
Colour temperature: 3000 K
Colour rendering index: 100

Ⓒ

SOFFIT SPOT LIGHTS - MIRAGE IP65 LED - WHITECROFT LIGHTING

DETAILS
Light output options:
2500 lumens, 21W - 4000K
2325 lumens, 21W - 3000K
Wide beam symmetrical distribution
3000 and 4000K colour temperature options

BODY
Die-cast aluminium body and bezel
IP65, IK10 rated protection
Finished in Anthracite Grey
Clear flat acrylic diffuser in bezel
Matt anodised aluminium reflector
Supplied complete with driver contained within main body
To suit ceiling thickness 5 - 50mm
DALI dimming driver as standard



C2	LIGHTING AMENDED.	10.04.20	R/J	PM	MF
C1	CONSTRUCTION ISSUE	20.03.17	R/J	PM	MF
P2	COMMENTS INCORPORATED	06.07.17	R/J	PM	MF
P1	PRELIMINARY	26.05.17	R/J	PM	MF
Rev.	Revision note	Date	CAO	SM	PM

DRAWING TITLE

EXTERNAL LIGHTING LAYOUT

PROJECT
X1 NORTH BUILDING - PHASE 2
EAST BANK, MANCHESTER

CLIENT
BRIDGESTONE CONSTRUCTION



Liberty Group: Garden Works, Charley Wood Road,
Knowsley Industrial Estate, Liverpool L33 7SG
Tel: 0330 995 8007

SCALE	DATE	DRAWING NUMBER	REV.
1:150 (A0)	15.01.17		
DRAW	DESIGN	PRO-0342-E800	C2
CAD	PM		