

Arch.: Delugan Meissl Associated Architects

EQUITONE

Fibre cement facade materials



Arch.: RDBM Architecten & Adviseurs





3

Arch.: Delugan Meissl Associated Architects
Photo: Brigida González

EQUITONE fibre cement facade materials

When Ludwig Hatschek invented fibre cement in the late 19th century, he combined the basic elements of the earth: mineral materials, water, air and fire (heat) in a simple filtration process. He named the resulting material “Eternit”, hinting at the superior durability of this new material. Our mother company, Etex, has been manufacturing fibre cement materials since 1905. The most prestigious incarnation in this proud heritage of unique materials is the EQUITONE® facade material range. The Hatschek production process makes each EQUITONE facade panel unique with an individual fibre cement texture.

In the 1950s leading architects such as Walter Gropius pioneered the use of coated fibre cement panels using the ventilated facade (rainscreen) system. Designer Willy Guhl created the famous “loop chair” from 1 piece of fibre cement in 1954. This design still bears witness to the core qualities of the fibre cement base material: thin, light, durable and beautiful. In 1987, Herzog & De Meuron designed the Ricola storage building in Laufen using uncoated fibre cement panels. The resulting shutter facade, which is a reference to the cardboard boxes inside, inspired our company to start the industrial development of raw untreated fibre cement materials.


Today, EQUITONE has a range of through-coloured, untreated fibre cement materials. Leading architects of our time are exploring and transforming the EQUITONE material in remarkable facade designs.












Design potential

EQUITONE facade materials offer unparalleled design flexibility. The fibre cement material is through-coloured, which means the surface displays the inner texture and colour of the core fibre cement material. No matter what facade design options you explore, the through-coloured materials can be transformed into crisp, monolithic facade details.

EQUITONE facade materials come in a maximum panel size of 1.25 x 3m (4´x 10´) and can be transformed into any size or shape using standard tools in the workshop or on site. The material can be perforated using waterjet or CNC machines, large or very small cuts can be made, it can even be embossed and printed. Some designers have used it for interiors or furniture. The through-coloured material allows you to achieve flawless intricate details.



Arch.: ARTE Leuven Belgium



Arch.: Regina Schineis




Arch.: Boguslaw Worwzezcka i zespol




Arch.: Busmann + Haberer



Arch.: Astrid Bornheim



EQUITONE [linea]



Arch.: Studio Weave

EQUITONE [linea]*

Design

Unique 3D shaped, through-coloured facade material that plays with light and shadow.

Finish

The linear surface highlights the raw inner texture of the core fibre cement material.

Expression

Every moment of the day, the changing angle of the daylight gives the facade material a different aspect.

Thickness	Sheet sizes	Nominal weight
10mm	2500 x 1220, 3050 x 1220 mm	16.8kg/m^2

* Naturally occurring white flecks may be visible which adds to the aesthetics of the material

For additional information and technical advice

Tel: 01283 722588

Email: facadesuk@etexgroup.com

Visit: www.equitone.co.uk





Arch.: Studio Weave

The nature of things

EQUITONE shadow art by Fred Eerdekens



EQUITONE [tectiva]



Arch.: RDBM Architecten & Adviseurs

EQUITONE [tectiva]*

Authenticity

Original through-coloured material with highly expressive fibre cement structure.

Individuality

The production process makes each panel unique in colour, texture and surface.

Tactility

Rough, unpolished fibre cement surface with delicate linen touch.

Thickness	Sheet sizes	Nominal weight
8mm	2500 x 1220, 3050 x 1220mm	14.9kg/m^2

* Naturally occurring white flecks may be visible which adds to the aesthetics of the material

For additional information and technical advice

Tel: 01283 722588

Email: facadesuk@etexgroup.com

Visit: www.equitone.co.uk





Arch.: B-architecten,



EQUITONE [materia]



Arch. K. Reubens, M. Muylaert (Bonheiden)

EQUITONE [materia]*

Appearance

Through-coloured facade material that accentuates the beauty of fibre cement.

Distinct

The material encompasses the characteristics of cement, whereas the fibres render its surface textured yet velvety.

Aspect

The ever-changing atmosphere, gives the material natural subtle shade variations.

Thickness	Sheet sizes	Nominal weight
8mm	2500 x 1250, 3100 x 1250 mm	15.4kg/m^2
12mm	2500 x 1250, 3100 x 1250 mm	22.8kg/m^2

* The surface may show variations in tone and appearance which adds to the aesthetics of the material.

For additional information and technical advice

Tel: 01283 722588

Email: facadesuk@etexgroup.com

Visit: www.equitone.co.uk



Storm Grey [MA400]

Grey Mist [MA200]



Arch. K. Reubens, M. Muylaert (Bonheiden)



EQUITONE [natura]

Arch.: DRP Baukunst

EQUITONE [natura]

Sophistication

Natural material with clearly visible yet subtle fibre cement matrix, in a range of through-colours.

Soft touch

Matt, silk smooth surface finish.

Protection

Transparent protective layer. Optional EQUITONE ¨PRO¨ anti-graffiti protection.

Thickness	Sheet sizes	Nominal weight
8mm	2500 x 1250, 3100 x 1250 mm	15.4kg/m^2
12mm	2500 x 1250, 3100 x 1250 mm	22.8kg/m^2

For additional information and technical advice

Tel: 01283 722588

Email: facadesuk@etexgroup.com

Visit: www.equitone.co.uk





Charcoal (N073)


Obsidian (N074)


Ash Grey (N252)


Anthracite (N251)


Natural Grey (N250)


Nimbus (N281)


Fossil Grey (N892)


Portland (N294)


Beach Stone (N891)


Classic Grey (N211)



Cream White (N154)


Soft Grey (N163)


Chalk Grey (N162)


Pale Mist (N161)


Green Mist (N593)


Muted Yellow (N661)


Jadeite Green (N594)


Summer Haze (N662)



Sea Mist (N411)

Tawny Hue (N861)


Blue Grey (N412)


Ecru (N961)



Sepia (N972)


Autumn Dusk (N991)


Agate Red (N331)


Ruby (N359)





EQUITONE [pictura]

Arch.: Jo Coenen Architects and Urbanists

EQUITONE [pictura]

Colour

EQUITONE [pictura] offers a selection of contemporary colour coatings.

Matt surface

Smooth and ultra-matt finish for high class architectural look.

Anti-graffiti

EQUITONE [pictura] is treated with the EQUITONE ¨PRO¨ UV coating for everlasting anti-graffiti protection.


Thickness	Sheet sizes	Nominal weight
8mm	2500 x 1250, 3100 x 1250mm	15.4kg/m^2
12mm	2500 x 1250, 3100 x 1250mm	22.8kg/m^2

For additional information and technical advice

Tel: 01283 722588

Email: facadesuk@etexgroup.com

Visit: www.equitone.co.uk



Matt Black (PA041)

Espresso* (PA944)

Gunmetal Grey (PG241)

Mocha* (PG844)

Moonstone (PG243)

Fawn Grey* (PG843)

Porcelain (PW141)

Parchment (PW841)

Sky Blue* (PG442)

Powder Yellow* (PG641)

Regency Blue* (PG443)

Antique Yellow* (PG642)

Navy Blue* (PG444)

Olive* (PG542)

Teal* (PG546)

Pale Orange (PG742)


Autumn Green* (PG545)

Volcanic Red (PG341)

Bright Green* (PG544)

Deep Purple* (PG342)

* These colours are made to order and may be subject to longer lead times.



Ventilated facade

Originated in Scandinavia centuries ago, the ventilated facade (rainscreen) technique is now very prominent in areas with demanding climatic conditions.

In the rainscreen system, the outer panel deflects rain and solar heat away from the building. The ventilation space allows air to freely circulate behind the panel, creating a well ventilated and comfortable inner building.

Versatility


The ventilated facade construction principle combines the capability of curtain wall construction with the creative versatility and adaptability offered by traditional building techniques.


Less is more


A ventilated facade system has minimal thickness and weight, yet it offers maximum performance.

Healthy


The ventilated facade construction principle avoids cold bridges, eliminating condensation and mould growth.









Insulation



Rainwater removal



Removal of interstitial condensation



Minimisation of thermal bridging

A range of fixing systems are available to meet the variety of EQUITONE facade materials. Careful choice of product and system will allow any specification to be met.

Secret fix systems

The fixing method chosen can have a fundamental and dramatic effect upon the final appearance of the facade. Employing a secret fix method will result in a sheer, smooth facade unobstructed by fixings. In practice, many versions of secret fixing exist, including infill or composite panels.

For additional information and technical advice

Tel: 01283 722588

Email: facadesuk@etexgroup.com

Visit: www.equitone.co.uk



Site bonding

The structural bonding system utilises structural adhesive to fix both internal and external cladding panels to a support framework. It will bond panels to either a timber or aluminium framework.

Site bonding is limited to application within the temperature range 5°C to 35°C and only in dry weather (check with adhesive manufacturer).



Mechanical secret fix

In facade applications where a smooth unbroken surface is required, a concealed mechanical fixing system can be used. Hangers are fixed to the rear face of 12mm thick EQUITONE [materia], EQUITONE [natura] and EQUITONE [pictura] panels. An 8mm fixing is available for EQUITONE [linea] and EQUITONE [tectiva]. The hangers hook onto horizontal rails, which, in turn, are fixed to vertical rails.



Approved undercut anchor plugs are available for fixing into pre-drilled holes in the backs of panels. These ensure a positive fixing for bolts into the panels.



Arch: TP Bennett

Face fix systems



Timber battens

An economical method of application for EQUITONE facade panels is that of mounting on a timber framework using rainscreen construction principles.


Unless specific fire performance requirements or irregularities to the substrate are encountered (where other adjustable systems are employed), timber battens will provide an economical and speedy installation.

For additional information and technical advice

Tel: 01283 722588


Email: facadesuk@etexgroup.com

Visit: www.equitone.co.uk









Omega and Zed

As an alternative to timber battens, particularly where there is a specific requirement for non-combustible frameworks, a lightweight aluminium framework can be used. These can be fixed either directly to a concrete, brick or block wall, or to a purpose-designed rail system. Marley Eternit's EQUITONE facade materials can then be rivet-fixed to the Omega and Zed.

Helping Hand

An aluminium frame fixing system able to provide adjustable void depths to accommodate insulation, and able to overcome irregularities in the supporting substrate.

Floor Spanning System

A highly adjustable system allowing for irregularities in substrate surface, and is ideal where poor quality infill material on existing buildings dictates that fixings can only be secured at floor slab positions.



Arch: Astrid Bornheim





This publication is based on the latest data available at the time of printing. Due to product changes, improvements and other factors, the Company reserves the right to change or withdraw information contained herein without prior notice. For specific applications users should refer to the Technical Advisory Service and relevant Standards and Codes of Practice for guidance.


The photography shown in the document should not necessarily be taken as recommendations of good practice. The printing process restricts the exact representation of colours. For true colour reference, please request product samples.

Arch.: Metaform, Atelier d'architecture Sari



EQUITONE

Fibre cement facade materials



Arch: Arkitekterne Bjørk & Maigård ApS

For further information, please contact

Tel: 01283 722588 Fax: 01283 722219 E-mail: facadesuk@etexgroup.com

Marley Eternit Limited, Lichfield Road, Branston, Burton-upon-Trent, DE14 3HD

equitone.com

Follow us:

equitone.facade

@equitoneuk

equitoneuk

equitone-uk