DOCUMENT REFERENCES

This design is to be read in conjunction with the following design drawings and/or documents;

APPENDIX A - CRE-8657-003_CALCS

APPENDIX B - CRE-8657-003-1,2,3,4,5,6,7,8,GENERAL NOTES_DRG

LEGEND

- Structural Steel
- Scaffold Beams
- Timber Products / Scaffold Boards
- Building Line
- Facade Brace (Plan, Section)
- Kentledge Hatch
- Ledger Brace (Plan, Elevation)
- Plan Brace (Plan, Section, Elevation)
- Scaffold Centre Line (Plan)
- 48.3mm Diameter Scaffold Tube
- Cladding Material (Sheeting / Netting)
- Splice Detail
- Supplementary Coupler / Check Fitting
- Tie Location (Plan, Section, Elevation)
- Puncheon
- Upright Cut Off
- Residual Risk
- Ledger Brace (Elevation, Section)
- Facade Brace (Elevation, Section)

* Some of the above 'key' items may not be present in design but are indicated on all designs for conformity.

NOTES:
- Scaffold to be tested to the value
- Scaffold to be in accordance with NASC TG4:11

TYPICAL CLADDING DETAIL scale 1:50

Indicative fixing locations

Sheeting to be secured to scaffold structure using manufacturers fixings at 500mm c/c horizontally by 1000mm c/c vertically in accordance with manufacturers details

HOOK TIE DETAIL scale 1:50

Apollo hook tie in conjunction with scaffold screw and nylon insert

Tie tubes fixed to ledgers or uprights using Class A double couplers

FOUNDATION DETAIL 225 x 38 x 450mm (BS EN 2482) Scaffold Board Solepad Scale 1:25

152 x 152 x 4.76mm (EN 74) baseplate with scaffold upright centered about the plate

48.3 x 4.0mm CHS (BS 1139) scaffold tube as upright

150 MAX.

Torsional bracing
Plan bracing
Supplementary coupler / check fitting
Prefabricated transoms
Toe board
Scaffold tied in at locations indicated using tie detail as method of fixing
Scaffold board decking
Scaffold tied in at locations indicated using tie detail as method of fixing
Spur brace
Monarflex sheeting
Ledger bracing
Board transoms at 1200mm c/c
Facade bracing
Scaffold tube uprights at centres indicated
See foundation detail

1372 2000 2000 2000 2000 2000 1938 2000 1800 344 = 17385

769 500 1269

One level at 2kN/m²
One level at 1kN/m²
1.287kN at ULS
901kN at SLS
1.589kN at ULS
9.844kN at SLS

ENLARGED SPUR DETAIL scale 1:25

Any connection about the last tie must be spliced as per detail

One number Class A swivel coupler either side of sleeve joint

EN 74 Steeve Coupler joining two number 48.3 x 4.0mm CHS scaffold tubes

One number band and plate coupler either side of sleeve joint abutting one another

SPLICE DETAIL scale 1:25

SECTION B-B scale 1:50

PEDESTRIAN LIFT MAY BE INSTALLED ON THIS ELEVATION

2400 HEADROOM

1269

16851 300 1180 2002 2000 2000 2000 2000 2000 2000 1369

RISK OF CRUSHING
Control Measure: Principle contractor to employ a structural engineer to ensure the applied loads from the scaffold do not overload the existing structure. Creator Ltd to be contacted where structure is deemed unsafe to support scaffold structure.

RISK OF FALLING FROM HEIGHT
Control Measure: Principle contractor to ensure that the maximum bay size installed are as indicated and should not be exceeded. It is the responsibility of the scaffold contractor to remedy any defects.

RISK OF FALLING OBJECTS
Control Measure: The scaffold contractor must ensure that the maximum heights to be installed as detailed by the scaffold contractor and have a maximum tolerance of ±100mm

RISK OF COLLISION
Control Measure: Principle contractor to closely site manage, ensure clear signage is installed and where required temporary crash barriers (TCB) to be installed to prevent collision with the scaffold structure

RISK OF CONTACT WITH OVERHEAD POWER LINES
Control Measure: The design service loads indicated should be closely site managed to ensure that only 2 number of working levels are present at one time. The load conditions of the scaffold should be clearly identified on the scaffold tag.

RISK OF FALLING FROM HEIGHT
Control Measure: Cladding materials for scaffolding are prone to blowing free due to limited capacity of fixings so install cladding on inside of uprights ensuring safer install and less risk of large sheets blowing free and causing hazards external to the site

AMENDMENTS / REVISIONS

REV.	BY.	DATE.	CHECK.	DATE.	APP'D.	DATE.
-	DJB	03/04/18	MDB	03/04/18	RWB	03/04/18

Prepared For:

ibn

Drawing Status:

FOR COMMENT

Project Number: CRE-8657-0034 | Drawing Number: 4 | Scale: 1 : 50,25 @ A2

Project Title/Description:

TEMPORARY ROOF
KAMPUS
CHORLTON STREET
MANCHESTER, M1

Principal Contractor:

SEE QUOTE

CREATOR SCAFFOLD DESIGNS & TEMPORARY WORKS CONSULTANTS LTD

Company Address

Fullerton House, Fullerton Road, Rotherham, S60 1DH
Email: info@creator-scaffolddesigns.co.uk
www.creator-scaffolddesigns.co.uk

RISK OF FALLING OBJECTS - Cladding materials
Control Measure: Principle contractor to closely site manage, ensure clear signage is installed and where required temporary crash barriers (TCB) to be installed to prevent collision with the scaffold structure

RISK OF COLLAPSE OF SCAFFOLD DUE TO STRUCTURAL FAILURE
Control Measure: The design service loads indicated should be closely site managed to ensure that only 2 number of working levels are present at one time. The load conditions of the scaffold should be clearly identified on the scaffitag.

RISK OF FALLING OBJECTS - OVERLOADING OF SCAFFOLD
Control Measure: Principal contractor to employ a structural engineer to ensure the applied loads from the scaffold do not overload the existing structure. Creator Ltd to be contacted where structure is deemed unsafe to support scaffold structure.

RISK OF FALLING OBJECTS - OVERLOADING OF SCAFFOLD
Control Measure: Principal contractor to employ a structural engineer to ensure the applied loads from the scaffold do not overload the existing structure. Creator Ltd to be contacted where structure is deemed unsafe to support scaffold structure.

RISK OF COLLAPSE OF SCAFFOLD DUE TO STRUCTURAL FAILURE
Control Measure: The scaffold contractor must ensure that the maximum bay size installed are as indicated and should not be exceeded. It is the responsibility of the scaffold contractor to remedy any defects.

RISK OF FALLING OBJECTS - INCORRECTLY TIED SCAFFOLD
Control Measure: The scaffold is to be tied as detailed and have a maximum tolerance of ±100mm

RISK OF FALLING OBJECTS - HIGH LEVEL PARAPET
Control Measure: Principle contractor to closely site manage, ensure clear signage is installed and where required temporary crash barriers (TCB) to be installed to prevent collision with the scaffold structure

RISK OF FALLING OBJECTS - INCORRECTLY TIED SCAFFOLD
Control Measure: The scaffold is to be tied as detailed and have a maximum tolerance of ±100mm

RISK OF FALLING OBJECTS - Cladding materials
Control Measure: Principle contractor to closely site manage, ensure clear signage is installed and where required temporary crash barriers (TCB) to be installed to prevent collision with the scaffold structure

RISK OF COLLAPSE OF SCAFFOLD DUE TO STRUCTURAL FAILURE
Control Measure: The design service loads indicated should be closely site managed to ensure that only 2 number of working levels are present at one time. The load conditions of the scaffold should be clearly identified on the scaffitag.

RISK OF FALLING OBJECTS - OVERLOADING OF SCAFFOLD
Control Measure: Principal contractor to employ a structural engineer to ensure the applied loads from the scaffold do not overload the existing structure. Creator Ltd to be contacted where structure is deemed unsafe to support scaffold structure.

RISK OF FALLING OBJECTS - OVERLOADING OF SCAFFOLD
Control Measure: Principal contractor to employ a structural engineer to ensure the applied loads from the scaffold do not overload the existing structure. Creator Ltd to be contacted where structure is deemed unsafe to support scaffold structure.

RISK OF COLLAPSE OF SCAFFOLD DUE TO STRUCTURAL FAILURE
Control Measure: The scaffold contractor must ensure that the maximum bay size installed are as indicated and should not be exceeded. It is the responsibility of the scaffold contractor to remedy any defects.

RISK OF FALLING OBJECTS - INCORRECTLY TIED SCAFFOLD
Control Measure: The scaffold is to be tied as detailed and have a maximum tolerance of ±100mm

RISK OF FALLING OBJECTS - HIGH LEVEL PARAPET
Control Measure: Principle contractor to closely site manage, ensure clear signage is installed and where required temporary crash barriers (TCB) to be installed to prevent collision with the scaffold structure