Item	Description	Unit	Num
No			(nr)
	The contractor is required to include for everything		
	necessary to complete the works in their entirety.		
	The contractor will be responsible for taking		
	his own site dimensions and should allow for this in		
	his prices.		
R201	Provide and install new double gate 2.4m high; as detail on	Nr	1
	drawing HTS/AS/01/2 withoutpanels on either side;		
	complete with supporting posts, width of the gate to suite		
	existing opening; overall opening size: 2800mm wide illustrated		
	in photograph 1;include for all associated ironmongery as		
	indicated on the drawing and specification ref: Q40 - Gates;		
	make good all work disturbed to match existing.		
R201	Provide and install new double gate 2.4m high; as detail on	Nr	1
	drawing HTS/AS/01/2 withoutpanels on either side;		
	complete with supporting posts, width of the gate to suite		
	existing opening; overall opening size: 2750mm wide illustrated		
	in photograph 3;include for all associated ironmongery as		
	indicated on the drawing and specification ref: Q40 - Gates;		
	make good all work disturbed to match existing.		
R172	Install metal railing; overhang barrier; as detail4; as detailed on	Nr	1
	drawing no. HTS/AS/01/1; welded to face of gate post and		
	rawbolted to top of lower level wall; 450mm wide x 450mm high.		
	See photo 1.		
R157	Install 50m x 2.4m high palisade fencing; galvanised mild steel;	m	50
	Q40/350. See photo 2.		
R96	Allow for decoration to the gates and posts; in accordance with	M2	26
	specification; finished colour black. Also for wall railings.		
	The cylinder locks and mastered keys are to be obtained from		
	the Community Ironworks, The Security Park, Cambrian Street,		
	Beswick, Manchester M11 3FY; or other approved supplier to be		
	agreed with the CA.		
R215	Allow for a one off "mastering" charge per cylinder (one off	Nr	2
	cost for each new master keyed cylinder) Note: each		
	subsequent replacement cylinder ordered will not incur the one		
	off mastering charge.(Double gate)		
R209	Allow for providing keys to all residents of properties on	Nr	11
	the alleyways enclosed; keys ordered at time of cylinder.		
R214	Provide padlock and core (double gate).	Nr	2

