PARKEON



PLANNING
ACK'D
REPLIED
RECD - 8 APR 2008
M
M
M
FOR ACTION
M

STRADA Accessibility



Create harmony for your city

A user oriented design



STRADA designed to offer ease of use and to comply to accessibility standards:

- Location of all interfaces (controls, display...) suited for a wide range of user's size
- Accessibility for wheelchair users possible either from front or side reach
- Non users are taken into account: protrusion managed

A flexible technical offer to adapt to various situations thanks to a pedestal providing easy management of terminal's final height

A friendly user interface

Pedestal installation depth: Manage height of the interfaces





Minimum and Maximum manageable heights:

- Display center: 1.3m - 1.435m
- Buttons center: 1.2m - 1.335m
- Coins/Card inlet, PinPad: height located between 0.885m and 1.335m
- Ticket release, coin return: height located over 0.885m and under 1.335m

PARKEON

DDA Compliancy



DDA specifications BS8300-2001, major requirements:

Height of interfaces and controls above the finish floor

- Must be between: 75cm min and 120cm max

Any protruding part of the terminal less than 10cm from the access route

A clear floor space must be provided in front of the machine: 1.85mx2.1m

2 solutions to comply to DDA:

Pedestal has to be installed buried

Or the terminal can be installed directly on flat ground

DDA Compliancy: a user oriented design





Display: center located at 1.3m

Buttons: center located at 1.2m

Coins/Card inlet, PinPad: height located between 0.75m and 1.2m

Ticket release, coin return: height located over 0.75m and under 1.2m

EN15291 Compliancy



EN15291 specifications-Jan2006, major requirements:

Height of interfaces and controls above the finish floor

- Must be between: 75cm min and 130cm max

Any protruding part of the terminal less than 10cm from the access route

A clear floor space must be provided in front of the machine: 1.5mx1.5m

2 solutions to comply to EN15291:

Pedestal has to be installed in order to add a maximum height of 10cm over the finish floor

Or the terminal can be installed directly on flat ground

EN15291 Compliancy: a user oriented design





Pedestal adjusted to raise by 10cm

Display: center located at 1.4m

Buttons: center located at 1.3m

Coins/Card inlet, PinPad: height located between 0.85m and 1.3m

Ticket release, coin return: height located over 0.85m and under 1.3m

PARKEON

ADA Compliancy

ADA specifications version 2004, major requirements:

- Height of interfaces and controls above the finish floor
  - Must be between: 15" (38cm) min and 48" (122cm) max
- Size of buttons > 0.77" (2cm) for the smallest dimension
- The force required to activate controls must be <5lb (22.2N)
- No control requiring spin of wrist
- Any protruding part of the terminal less than 3.93" (10cm)
- A clear floor space must be provided in front of the machine: 30"x48" (0.76mx1.22m)

2 solutions to comply to ADA:

- Pedestal has to be installed buried, on the front side of the machine
- Or the terminal can be installed directly on flat ground

ADA Compliancy: a user oriented design



Display: center located at 1.3m/51.18”

Buttons: center located at 1.2m/47.2”

Coins/Card inlet, PinPad: height located between 0.75m/29.5” and 1.2m/47.2”

Ticket release, coin return: height located over 0.75m/29.5” and under 1.2m/47.2”



Terminal's Height Management



The terminal's housing is offered in one height identical for Transfer and Rapid system:

- 1.475m/58in

Pedestal can be partly buried :

- Pedestal is protected against corrosion
- Size: Height 15.5cm/6.1in x Width 29.7cm x Depth 27cm

The overall terminal's finished height* can be managed thanks to the pedestal depth installation:

- Terminal's height management: from 0 to 13.5cm/5.3in
- Minimum height: 1.475m/58in
- Maximum height: 1.610m/63in

(* Without PTop/ solar panel and zone indicator)

Ground Installation

Pedestal enables Height management and 2 parts installation

Adaptation to different floors surfaces

- Pedestal position can be adjusted
- Concrete, asphalt, stone,...
- Sloped floors







PARKEON

Enhanced User Interface
Readability and flexibility

Optimized buttons organization for quick and easy understanding

- Large buttons
- grouped close to the screen
- natural reading concept left-right

A highly customizable interface

- large information sticker
- Number, position and color of



Payment Configurations Management



No pin-pad/Keypad



No Card



No Coin

PARKEON

Buttons and Keypad functions





Grey Button = Multilingual, select up to 4 languages

Yellow Button = 5 Users/tariffs selection

Blue Buttons = select parking duration

- "+" button: increment parking duration by step defined in the customization "card debit amount"
- "+" and "max": "max" allows to get directly to the max parking duration or to the time limit allowed
- "+" and "-": "-" allows decrement of duration



Secured Pin Pad for EMV Banking

Keypad for Pay By Space



Information Labels



- Labels fully customizable
- Labels can be easy exchanged on field after opening of the maintenance door
- Labels Protected behind a glass



PARKEON

Information Stickers

Area available for Customer sticker



Transaction guiding



Information Stickers

Transaction guiding:

Main role: identify quickly the interface suited for the transaction

Icons used to help foreign people or color blinded people to understand the function

Sticker suited for outdoor use

Resistance to first vandalism level