PLA
ACKD
REPLIED
RECD 28 MAR 2008
DATE
INITIAL
INITIAL
OBJECTION

Decra Plus Tile

Decra Plus Tiles have an 0.9mm galvanised steel core to provide the ultimate in vandal resistance. These exceptionally strong tiles have the same traditional shape as Decra Classic, with a granular surface finish which provides an attractive roofscape.







Data file

Pitch	
Minimum pitch	10°
Maximum pitch	90°
Dimensions	
Size of tile - overall	1324mm x 410mm
Size of tile - cover	1260mm x 368mm
Gauge	368mm
Linear cover width	1260mm
Coverage	0.464m² per tile
	2.157 tiles per m²
Weight	
Weight per m²	11.65kg
Weight per tile	5.40kg
Fixing	
Tile fixing	50mm x 2.99mm Coated Decra nail or Decra Plus fixing screws
Fixings per tile	4-no.
Battens required	
Battens	2.72 linear per m² (plus wastage)
Batten sizing	
Rafter centres (max.)	Batten size (recommended)
450mm	38mm x 25mm
600mm	50mm x 25mm
900mm	50mm x 50mm
1200mm	50mm x 50mm
1500mm	50mm x 65mm
Laying (recommended)	
Simple roof shapes	Straight bond
Complex roof shapes	Broken bond
Ordering	
Order code	PT_D1
Accessories	See page
Tile accessories	50
Ventilation	64
Underlays, membranes	66
Eaves protection	68
Tools	72

Colours

(Colours illustrated available from stock, others to order)

NOTE: Colour reproduction is as close as the limitations of the printing process allow. Please use a colour sample, available free from Technical Services, for selection purposes.



Terracotta Red



Charcoal Grey

Bespoke colours are available to order (subject to minimum quantity restrictions).

Police Preferred Secured by Design accreditation is available for the Decra Plus Tile with enhanced Decra security fittings. Contact Decra's Technical Department for further details.