AXIS® SYSTEM - THE FENCING SYSTEM FOR ALL REQUIREMENTS



AXIS® C



AXIS® D



AXIS® DR



AXIS® S



AXIS® SR

The AXIS® system from Dirickx, comprising welded mesh panel and post, is a unique type of fencing. Designed to enhance and protect, AXIS® is the ideal solution for all your requirements.

AXIS® is secure, hard-wearing and aesthetically pleasing, everything you are looking for.

UNIQUE FIXING SYSTEM:
No screws, no bolts. The panel attaches directly into the purpose made grooves along the full length of the post, making it impossible to remove a full panel once installed.

SUITABILITY:
Curves, corners, slopes: AXIS® is adaptable to all ground constraints.

HIGH QUALITY FINISH:
Galvanised wire with a bonded powder coating eliminates the risk of stripping or corrosion.

DESIGN:
A large range of panels (AXIS® D, DR, SR, C and S) and two different post options.

AESTHETICS:
Wide range of colours available.
Clear visibility through the fence lines.

FEATURES:
Cost effective.
Easy installation.
Durable and sturdy.
Adaptable for all uses.

ACCESSORIES:
A range of single and double leaf, manual and automated, swing, sliding and cantilevered gates to compliment the fencing. Barbed wire extensions. Kickboards. Wall Fix or Bolt Down post options.

THE AXIS® RANGE

FINISH: Galvanised & Polyester Powder Coated.

STANDARD RAL COLOURS: Green 6005 - White 9010 - Black 9005 - Light Grey 7035 - Blue 5012 - Red 3002 - Yellow 1021 *

NON STANDARD COLOURS: Available on request

(*) - Other standard colours are also available dependant on panel specification

AXIS® PANEL SPECIFICATION

MODEL		Ø WIRE mm	MESH mm	WIDTH m	HEIGHT* m	BEAMS	POST CENTRES m	POST TYPE
AXIS® C Crimped panel		Horizontal 5 Vertical 5	Height 200 Width 55	2.31 or 2.48	0.6 - 0.8 1.0 - 1.2 1.4 - 1.6 1.8 - 2.0 2.2 - 2.4	2 2 3 3 4	2.53 for height < 2.40 2.37 for height 2.40	AXIS®
AXIS® DR Reinforced double horizontal wire		Horizontal 8 Vertical 6	Height 200 Width 55	2.31 or 2.48	0.6 - 0.8 1.0 - 1.2 1.4 - 1.6 1.8 - 2.0 2.2 - 2.4 2.6		2.53 for height < 2.40 2.37 for height 2.40 and 2.60	AXIS®
AXIS® D Double horizontal wire		Horizontal 6 Vertical 5	Height 200 Width 55	2.31 or 2.48	0.6 - 0.8 1.0 - 1.2 1.4 - 1.6 1.8 - 2.0 2.2 - 2.4 2.6		2.53 for height < 2.40 2.37 for height 2.40 and 2.60	AXIS®
AXIS® SR Reinforced crimped panel		Horizontal 6 Vertical 5	Height 100 Width 55	2.31 or 2.48	0.6 - 0.8 1.0 - 1.2 1.4 - 1.6 1.8 - 2.0 2.2 - 2.4	2 2 3 3 4	2.53 for height < 2.40 2.37 for height 2.40	AXIS®
AXIS® S Small crimped panel		Horizontal 4 Vertical 4	Height 100 Width 55	2.48	1.0 - 1.2 1.5 - 1.7 1.9	2 3 4	AXOR®: 2.51	AXOR®

(*) + spikes : 25mm

AXIS® POST SPECIFICATION

MODEL		LENGTH m	SECTION mm	INTERVAL OF GROOVES mm
AXIS® Post		From 0.8 to 3.9		
AXOR® Post		From 0.7 to 2.7		