FENCING SPECIFICATION FOR: 3.0m high Sports Bronze Ballcourt

FENCING WITH FENCE TYPE SPORTS BRONZE & PROFIX SECURITY RHS POSTS.

GENERAL DESCRIPTION

Delivery and installation of a fence with panels.
- **Total length**: 500m Approx - FENCING CONTRACTOR TO ADVISE
- **Total height**: 3000 mm

Specifications:
Colour panels, posts: Green RAL 6005
Nominal height: 3000 mm
Height panels: 2000 mm + 1000mm
Width panels: 2515 mm
Length post: 3900 mm
Number of fixings for intermediate/end post: 8

WELDED MESH PANELS
Heavy welded mesh type **SPORTS BRONZE**
Manufactured from galvanized wire & polyester coated after welding.
Panels of 2515mm width.
Size of the mesh: 200 x 50 mm
Wire diameter: 2 x 8 mm & 1 x 6 mm
∑ Polyester coated on galvanized wire (60 g/m2)
Minimum polyester coating: 60 microns

Colour: Green RAL 6005
Height of the panels: 2000mm + 1000 mm

POSTS: PRO-FIX HIGH SECURITY RHS POSTS: Manufactured from 60x 60x3mm rectangular hollow section, 8mm cup square bolts c/w permacone security nut, 40 x 5mm PROFIX slotted clamp bars, complete with plastic top caps and M8 bolts with anti-tamper heads.

Minimum zinc coating: 55 microns
Hot dipped galvanized and Polyester coated on galvanized.
Minimum polyester coating: 60 microns
Post section: 80x80x3 mm

Colour: Green Ral 6005
Length: 3900 mm

ACCESSORIES
Number of fixings for intermediate post: 8
Complete with black plastic top caps, 40 x 5mm slotted clamp bars, M8 bolts with anti-tamper head.

INSTALLATION OF SECUREGUARD 358 FENCING SYSTEM:

Concrete foundations must not be leaner by mass than one part cement to ten parts 20mm nominal size graded aggregate, and are to be thoroughly compacted prior to the initial set.
Depth of hole: 950 mm
Size of foundations: 450 sq.
Depth of concrete: 950 mm

BARKERS SPORTS FENCING RANGE BRONZE
DESIGNED FOR LOW IMPACT SPORTS



SPORTSBRONZE

SPORTS BRONZE has been designed to provide a cost effective solution for most general sporting applications. Excellent for use in schools, urban sports grounds, health clubs and ball containment areas. Specifically designed for general/low impact sporting applications.

Panels
Manufactured using 6mm vertical and 2no 6mm horizontal wires welded at each intersection creating a strong and durable panel. The mesh aperture consists of a 200 x 50mm mesh spacing providing excellent see through visibility!

Posts
Standard post sections available are 60 x 60 x 2.5mm or 80 x 80 x 3mm. For increased fence height further post sizes are also available.

Heights
2m, 3m, 4m and 5m. Heights above 3m can be achieved using panel increment sections, enabling a quick and safe installation.

Fixings detail
Barkers Fencing anti-vibration **PROFIX Twin** clamp assembly provides a smooth and flush detail, protecting against personal injury and product damage.

barkersfencing.com Tel 01782 319264 | Fax 01782 599724 | sales@barkersfencing.com |