

ATRIUM GROUND FLOOR RECEPTION& STAFF ADMIN ROOMS (UNDER CENTRAL HOUSE BEDROOMS)

ROCHDALE CANAL



CEILING FINISHES KEY:

- TYPE 1 - 2x12.5mm THICK PLASTERBOARD SUSPENDED BENEATH UNDER SIDE OF FLOOR STRUCTURE*** CAVITY VOID ALLOWING SERVICES BELOW AND 12.5mm THICK STANDARD PLASTERBOARD T&J CEILING ON M/F FRAME WITH SKIM COAT TO RECEIVE PAINT FINISH. T.B.C BY G+P
- TYPE 2 - 1x15mm THICK PLASTERBOARD SUSPENDED BENEATH UNDER SIDE OF FLOOR STRUCTURE*** CAVITY VOID ALLOWING SERVICES BELOW AND 12.5mmTHICK STANDARD PLASTERBOARD T&J CEILING ON M/F FRAME WITH SKIM COAT TO RECEIVE PAINT FINISH. T.B.C BY G+P
- TYPE 3 - 1x15mm THICK FIRELINE PLASTERBOARD SUSPENDED BENEATH UNDER SIDE OF FLOOR STRUCTURE***. CAVITY VOID ALLOWING SERVICES BELOW AND 12.5mmTHICK STANDARD PLASTERBOARD T&J CEILING ON M/F FRAME WITH SKIM COAT TO RECEIVE PAINT FINISH. T.B.C BY G+P
- TYPE 4 - 15mm THICK MOISTURE RESISTANT P.BOARD T&J CEILING ON M/F FRAME WITH SKIM COAT TO RECEIVE PAINT FINISH. T.B.C BY G+P. FIRE SOFFIT TO MATCH THAT OF RELEVANT ROOM BEDROOM AND RAISED TO SIT BETWEEN THE BEAMS (CIRCA 200mm BELOW TIMBER PLANKS), WELL SEALED AROUND PERIMETER LINE USING FLEXIBLE SEALANT.
- TYPE 5 - 60 MINUTE FIRE RESISTANCE SOFFIT: (CENTRAL & DOMINION HOUSE) 1x15mm THICK FIRELINE PLASTERBOARD
  90 MINUTE FIRE RESIATNCE SOFFIT: (JOHNSON HOUSE) 2X15mm THICK FIRELINE PLASTERBOARD
  SUSPENDED BENEATH UNDER SIDE OF FLOOR STRUCTURE. CAVITY VOID ALLOWING SERVICES BELOW WITH REMOVABLE EGGCRATE SUSPENDED M/F CEILING SYSTEM PROVIDED BY ARCHITECTURAL GRILLE (REF. EC300 O.E.A), WITH 25X25mm APERTURES, P.P.C FINISH
- TYPE 6 - LAY-IN METAL PVC COATED TILES ON M/F SUSPENDED GRID
- No Hatch — EXISTING CEILING TO BE RETAINED. SUBJECT TO M&E & CONTRACTOR INSTALLATION PREFERENCES / LOGISTICS
- AREA OF CEILING FINISH SUBJECT TO CONFORMATION OF APPROACH AND INTERIOR DESIGN CONCEPT DETAILS T.B.C. BY SACO/G+P
- EXPOSED CONCRETE/METAL STAIR FLIGHT SOFFIT. PAINT FINISH (IF REQUIRED)
- 600x600mm GYPROC PROFILEX (OR SIMILAR) PLASTERBOARD CEILING ACCESS PANEL (0 hr F.R, U.N.O) WITH BEADED FRAME TO ACCEPT NOMINAL SKIM FINISH
- FEATURE L.E.D PIN SPOT (WITHIN EGGCRATE CEILING GRID) - REGGIANI - 35mm Ø YORI PENDANT - EXACT FINISH T.B.C BY G+P
- 18mm THICK WBP PLYWOOD PATTRESS IN MF ZONE, CIRCA 300mm WIDE TO ALL SHOWER ROOMS FOR GLASS SCREEN HEAD FIXINGS. 600x600 PATTRESS ABOVE PENDANT LIGHT FITTINGS. ALLOWANCE TO BE MADE FOR 1no. IN EACH LOUNGE ABOVE TABLE
- HOT WATER CYLINDER POSITIONED IN SHOWER ROOM CEILING VOID. SUSPENDED AND FIXED BETWEEN BEAMS USING UNISTRUT SYSTEM BELOW FIRE SOFFIT AND SACRIFICE CEILING FINISH. LOCATION ON PLAN SHOWN INDICATIVE SUBJECT TO INDIVIDUAL ROOM SURVEY & M&E CONFIRMATION.
- CURTAIN PELMET DETAIL TYPE 1 - REFER TO LRW A(70)05 SEPARATE DETAILS
- CURTAIN PELMET DETAIL TYPE 2 - REFER TO LRW A(70)05 SEPARATE DETAILS
- (2500) — PROPOSED CEILING HEIGHT MEASURED FROM FFL
- (TBC) — EXACT CEILING HEIGHT SUBJECT TO STRIPPED BACK SHELL MEASURED SURVEY/ SUBJECT TO CONFIRMATION
- (SEE KEY NOTE) — NEWLY PROPOSED ROOM WITHIN CENTRAL HOUSE BLOCK TO HAVE RE-INSTATED CEILING HEIGHTS AS PREVIOUSLY EXISTED. EXC SHOWER ROOMS

BLUE HIGHLIGHTED TEXT DENOTES SPEC / REQUIREMENT T.B.C BY SACO / G+P

GENERAL NOTES:

TO BE USED FOR TENDER ONLY

ALL WORKS ARE TO COMPLY WITH CURRENT HEALTH AND SAFETY LEGISLATION, H.S.E. RECOMMENDATIONS/GUIDANCE AND THE CURRENT C.D.M. REGULATIONS.

THIS DRAWING IS TO READ IN CONJUNCTION WITH LEACH RHODES WALKER ARCHITECTS GENERAL ARRANGEMENT (L CODE) DRAWINGS, TOGETHER WITH RELEVANT DETAILED (A CODE) DRAWINGS AND SPECIFICATIONS.

ALL PRODUCTS SPECIFIED ARE TO BE INSTALLED STRICTLY IN ACCORDANCE WITH THE MANUFACTURERS RECOMMENDATIONS, SPECIFICATION AND DETAILS.

REFER TO LRW A(35) & A(42) CODE DRAWING FOR DETAILS.

FIRE RATED SOFFIT SUBJECT TO FULL STRIP OUT TO OBTAIN EXISTING STRUCTURE SPECIFICATIONS.

PHELAN APPOINTED FIRE CONSULTANT TO CONFIRM FIRE RESISTANCE PERFORMANCES.

SCOTCH PARTNER TO CONFIRM IN RELATION TO ACOUSTIC PERFORMANCES.

**DOMINION HOUSE LEFT AREA CLOUDED DOES NOT ACHIEVE CUSTOM 30 MINUTE FIRE RESISTANCE FROM TIMBER FLOOR PLANKS. SEE PHOTOGRAPH ON LRW L(35)03 DRAWING.

***CEILING BUILD UP TO MATCH EXISTING OR BETTER THE PROPERTIES, AS AGREED WITH B.V FIRE CONSULTANT.

FIRE RATING SPECIFICATION AS PER B.V REPORT AND RECOMMENDATIONS.

FIRE RATING SPECIFICATIONS ARE IN CONJUNCTION WITH M.H.A TIMBER FLOOR PLANK & BEAM REPORTS.

FURTHER CORRIDOR LIGHTING T.B.C BY G+P & A.E

rev	description	drwn	auth	date

DO NOT SCALE OFF THIS DRAWING
© LEACH RHODES WALKER 2001

LeachRhodesWalker Architects
info@lrw.co.uk | www.lrw.co.uk
50 Dearmans Place Manchester M3 5LH
Manchester +44 (0)161 833 0211
London +44 (0)207 2012160
Bucharest +40 (21) 650 4024

client: SACO

project: THE ATRIUM MANCHESTER

project no	drawing no	rev
7664	L(35)02	

description - GROUND FLOOR REFLECTED CEILING PLAN

scale	date drawn	drawn by	authorised by
1:100@ A1	19.08.17	DG	RW

purpose of issue: planning ○ building regs ○ tender ● comment ○ approval ○ construction ○