

## High Quality Shutters and Doors

Tel: 0845 644 1225  
Fax: 0845 644 6251  
[sales@abacusshutters.co.uk](mailto:sales@abacusshutters.co.uk)

Request a  
Free Quote



[Home](#) [Security Roller Shutters](#) [Doors & Gates](#) [PVC Strip Curtains](#) [Posts & Bollards](#) [Repair & Maintenance](#) [Health & Safety](#) [Company Profile](#) [Site Map](#) [Contact Us](#)

### Commercial/Retail Vision Roller Shutters

Vision shutters, like traditional shutters, offer effective protection for a wide range of applications - the difference being that vision shutters enable you to see through them. This makes them the ideal choice for retail stores, shopping malls and art galleries where being able to see attractive window displays out-of-hours can be good for business.

Security guards are also able to see right inside premises with vision shutters, increasing the level of security and making them suitable for an even wider range of applications - like airports, for example.

With a range of different vision options -including punched, punched / lath glazed, perforated and tube and link portcullis - talk to Abacus to select the right vision shutters for your project.

**Vision Options** Punched or Perforated lath may be Interchanged with solid profiles when partial vision is required.  
Tube & Link Portcullis Grille

**Curtain Options** 75mm 20swg Perforated Steel Dome Lath.  
75mm 20swg Punched Steel Dome Lath  
Aluminium/Steel Tube & Link Portcullis.

**Shutter Housing** Constructed from 20swg galvanised steel sheet metal or roll formed aluminium in two sections - base and box lid. Box lid is removable for installation and maintenance purposes.

**Barrel** Constructed from 102mm mild steel tube incorporating either tubular motor or spring assembly with roller bearing at the non-drive end.

**End Plates** Die Cast aluminium or steel formed to suit a shutters weight and box housing.

**Side Guides** 50-101mm straight galvanised steel guides mounted on 50mm x 50mm x 5mm mild steel angles as standard.  
65mm straight galvanised steel guides on 75mm x 50mm x 6mm mild steel angles (if required).

**Operation** Operation is dependent upon shutter size - by either manual spring assist or electric 240v single phase tubular motor.

**Electrical Operation** Single phase powered by Ellard tubular motors, 240 volts with 0.5 > 2.5 amps of draw dependant upon shutter size.

**Electrical Optional Extras** Emergency manual override systems, battery back up units, key switches, key pads, remote controls and photo cells.

**Locking Options** With spring assisted shutters either a centre lock, bullet lock or

shoot bolt arrangement is used. For electric shutters, our unique  
drivedown autolock is fitted as standard.

#### **Installation**

Installation is carried out by our fully trained fitting teams.

#### **Safety Regulation**

To comply with the supply of machinery (safety) regulations  
1992. All powered shutters are CE Marked.

#### **Finish Options**

Shutters can be powder coated to any B.S. or R.A.L. colours you  
may require to compliment modern building designs.



SearchQuest: Internet Marketing: SEO

[Roller Shutter Doors](#) | [Shop Window Shutters](#) | [Steel Security Shutters](#) |