

K32 Panel Cubicles

To be read with preliminaries/ general conditions.

100 Note

1.0 Information to be read in conjunction with MOJO 74 drawing series.

112 Fully framed panel cubicles

1.0 Description: To backs of urinals and WCs within cubicles
2.0 Manufacturer: Delta Laminates
2.1 Product reference: Impact Linear (Co) Cubicles.
3.0 Frame
3.1 Type: Floor Anchored
3.2 Height: 2200mm

4.0 Panels

4.1 Height (overall): 2200mm
4.2 Floor clearance: 150mm
4.3 Core material: Compact Grade Laminate
4.3.1 Thickness: Min. 13mm
4.4 Facings:
4.4.1 Colour/ Pattern/ Species: EGGER Silk Grey U707

5.0 Doors

5.1 Height: To meet cubicle height
5.2 Core material: Compact Grade Laminate
5.2.1 Thickness: Min. 13mm
5.3 Facings:
5.3.1 Colour/ Pattern/ Species: EGGER Black U991
5.5 Ironmongery: Satin Anodised Aluminium
6.0 Other requirements: Satin Anodised Aluminium support fixings with cylindrical height adjusting pedestal support leg, face plate indicator with rear slide and keep with channel brackets and angle brackets, Aluminium head rail, hinges with cams to determine door swing either open or shut & coat hook.

150A Duct/ wall linings – panels and proprietary frames

1.0 Description: To WCs
2.0 Manufacturer: Delta Laminates
2.1 Product reference: Impact (Co) APS Duct Panelling System
3.0 Panels
3.1 Type: Floor Anchored
3.1.1 Width (coordinating): To be site measured
3.2 Core material: Compact Grade Laminate
3.2.1 Thickness: 13mm
3.3 Facings:
3.3.1 Colour/ Pattern/ Species: EGGER Silk Grey U707
4.0 Framing/ Support As per manufacturer's standard
5.0 Flashgap panels: As per manufacturer's standard
6.0 Skirting: As per manufacturer's standard

150B Vanity Units – panels and proprietary frames

1.0 Description: Sink Vanity Units

2.0	Manufacturer:	Delta Laminates
2.1	Product reference:	Impact (Co) APS Duct Panelling System
3.0	Facing Panels	
3.1	Type:	Floor Anchored
3.1.1	Width (coordinating):	To be site measured
3.2	Core material:	Compact Grade Laminate
3.2.1	Thickness:	13mm
3.3	Facings:	
3.3.1	Colour/ Pattern/ Species:	EGGER Silk Grey U707
4.0	Vanity Shelf	
4.1	Type:	Floor Anchored
4.1.1	Width (coordinating):	To be site measured
4.2	Core material:	Compact Grade Laminate
4.2.1	Thickness:	13mm
4.3	Facings:	
4.3.1	Colour/ Pattern/ Species:	EGGER Black U991
5.0	Framing/ Support	As per manufacturer's standard
6.0	Flashgap panels:	As per manufacturer's standard
7.0	Skirting:	As per manufacturer's standard

210 Samples

- 1.0 General: Before placing orders submit Panel frame colours
representative samples of the following:
- 2.0 Delivered materials/ products: To match samples.

250 Installation

- 1.0 Programming: Do not install cubicles or duct/ wall panels before building is weathertight, wet trades have finished their work,
- 2.0 Accuracy: Set out to ensure frames and/ or panels and doors are plumb, level and accurately aligned.
- 3.0 Modifications: Do not cut, plane or sand prefinished components except where shown on drawings.
- 4.0 Fixing: Secure components using methods and fasteners recommended by the cubicle/ panel manufacturer. Prevent pulling
- 5.0 Moisture and thermal movement: Make adequate allowance for future movement.