

This drawing is the property of Solus Solutions Ltd. Copyright is reserved by them and the drawing is issued on the condition that it is not copied, reproduced, retained or disclosed to any unauthorised person, either wholly or in part, without the consent in writing of Solus Solutions Ltd.

N.B. any variations between stated dimensions and site dimensions should be reported to the surveyor prior to work being executed.



30	A	RC104271509B000DM - recessed downlight, black finish - 9W LED, 2700K, CRI 90, 15° beam, IP65 - mains dimmable
25	B	495-12062124366p01 - back-mounted fixture, black finish - 20W LED, 2700K, CRI 90, 17° beam, 500mA - 1550 lumens - Pulse-DALI dimming
26	C	63S20VD.1RGBW27L16B7050.xxxx - Flexible LED strip, IP67 - 25x18V domed, RGBW (2700K), 16W/m - refer to drawing for lengths required - input cable for fitting is supplied in min. 3m length
10 + wall fittings	C1	RGBW COB LED, 12W - s/w surface profile for ceilings and recessed profile for walls - refer to drawing for lengths required (refer to "CINEMA-LIGHTING STRIPS" document for fittings installed to walls)
25	D	63S2520L25.1RGBW27S24E7030.xxxx - Flex 25 Wall Washer, IP67 - 25° RGBW (2700K), 24W/m - @2200mm length - installed in housing supplied by others - input cable for fitting is supplied in min. 3m length
73	F	63S2520L3055.2RGBW30S24E7050.3000 - Flex 25 Wall Washer, black - 30x55° RGBW (3000K), 24W/m - 3000mm length - input cable for fitting is supplied in min. 3m length
1	F1	63S2526L25.2RGBW30S24E7050.3750 - Flex 25 Wall Washer, black - 25° RGBW (3000K), 24W/m - 3750mm length - input cable for fitting is supplied in min. 3m length
16	G	Small suspended fitting - specification TBC - to be supplied by others
6	H	Small suspended fitting - specification TBC - to be supplied by others
7	I	Large suspended fitting - specification TBC - to be supplied by others
4	J	Wall light - specification TBC
3	K	Suspended fitting - specification TBC - to be supplied by others
5	L	RC110272809W000D - recessed adjustable downlight, white finish - 9W LED, 2700K, CRI 90, 28° beam
3	M	LED9624VP20PINK - LED tape, 9.6W, Pink, 24V, IP20 - with 600-4207A Alu corner profile - with 600-CR07 PMMA cover - refer to drawing for lengths required
28	N	LED9624VP20PINK - LED tape, 9.6W, Pink, 24V, IP20 - with test task bar - refer to drawing for lengths required
4	O	LED Strip at bar - specification to be confirmed
-	P	Power supply required for graffiti and neon wall/celling installation
8	T	Track, black finish - refer to drawing for lengths required
-		Festoon Lighting - 500mm cables between lamps - supplied by others

93	A	24V PSU - 24v driver
49	B	CBU-PWM4 - 4 channel Bluetooth PWM dimmer
44	B	CBU-PWM5 - 5 channel Bluetooth PWM dimmer

Ref	Date	Revision	By
G	31.07.25	Add. fittings at Bar & Private Area	KM
F	24.07.25	GA Rev: Neon omitted at bar area	KM
D	07.07.25	Notional wiring shown on ext. elevs	KM
C	07.07.25	Drivers added	KM
B	18.06.25	General Revisions	KM
C	10.06.25	C1 fittings added	KM
A	03.06.25	Fitting specs and layout updated	KM

Client :
Follow Friday
27 Trenchard Street
Bristol, BS1 5AN

Project :
Manchester Street Food

Title :
Proposed Lighting Layout

Drawing No : S-01437-00	Rev : G	Scale : 1:100/A1
Date : April 2025	Drawn by: KM	Checked by : KC

SOLUS SOLUTIONS LTD
UNIT 25E, ANNIESLAND BUSINESS PARK
NETHERTON ROAD, ANNIESLAND
GLASGOW, G13 1EU

T 0141 954 2771
F 0141 954 2772
OFFICE@SOLUSGB.COM
WWW.SOLUSGB.COM

Solus Solutions may provide layouts for emergency lighting to help ensure sympathetic integration into the architecture and general lighting scheme. It is the responsibility of the mechanical and electrical consultant/contractor to ensure that the emergency lighting scheme and specification meets with BS5266 and any local requirements.