


Typical Detail 01 - Small Openings for Previous Services




Typical Repair Detail 01 (Opening up to 150mm square)

Method statement for Repair


1. Prepare the concrete surface by removing loose material and scabble back the existing concrete to 1:10 slope. Also refer to Fosroc specification on substrate preparation.
2. Prime concrete edge using Renderoc Primer or similar approved.
3. Apply Fosroc Renderoc HB45 or similar approved.
4. Apply Fosroc Nitobond AR or similar approved after application for curing.

Note

- This repair detail is intended to repair the exposed reinforcement bars only. To repair to concrete cover to minimum required thickness, refer to Repair Detail 02.



Typical Detail 02 - Penetration on non-load bearing masonry walls



Typical Repair Detail 02

Method statement for Repair

Penetration Repair:

1. Provide temporary support to stabilise the buttress wall during repair works.
2. Scrape out mortar joints around the penetration.
3. Lever brickwork loose using hand tools, timber shims etc.
4. Clear backing and bedding mortar.
5. Reset brickwork using mortar that match existing.

General Notes

1. This drawing is to be read in conjunction with all relevant Architects & Engineers drawings & specifications.
2. The Contractor is to be responsible for all dimensions & for the correct setting out of the works on site.
3. Do not scale from this drawing.

Note: All propriety repair mortars to be applied in strict accordance with the manufacturer's details and specification.

P03	06.06.25	TL	NS	Details Revised
P02	29.04.25	TL	NS	Details Revised
P01	17.04.25	TL	NS	Initial Issue
Rev	Date	By	Chkd	Description

Eckersley
O'Callaghan

London Office 9th Floor, 236 Gray's Inn Rd, London WC1X 8HB
+44 (0) 20 7354 5402 eocengineers.com

Project Title

Sunlight House

Drawing Title

Phase 2 Basement Repair Works
Repair Detail Sheet 2 of 2

Project No

24131

Scale:

NTS [A1]

Drawn By

TL

Date

June 2025

Drawing Suitability

SO - Initial Issue

Drawing Number

SUN-EOC-V1-ZZ-DR-S-4302

Rev

P03