
















Switching Legend

-  Distribution Board (Existing)
-  Single Gang One Way
-  Two Gang One Way
-  Single Gang Two Way
-  Two Gang Two Way
-  Presence Detection
-  Electrical Circuit Lines (Representative)

LEGEND	DESCRIPTION	IMAGE	LEGEND	DESCRIPTION	IMAGE	LEGEND	DESCRIPTION	IMAGE
	SUSPENDED LINEAR LED 2800MM UP/DOWN LIGHT OPAL DIFFUSER, 3630 LUMENS, 25W DIMMABLE 4000K 125.2LL/CW		 	WALL MOUNTED LED UP/DOWN LIGHT LUMINAIRE 2860 LUMENS, 20W DIMMABLE 4000K 130LL/CW			SURFACE MOUNTED EXTERNAL CIRCULAR LUMINAIRE PLAIN COVER, 2070 LUMENS, 16W 4000K 103.5LL/CW	
	AS THORLUX FLEXBAR DIFFUSER OR EQUAL & CLIENT APPROVED			AS THORLUX KAST OR EQUAL & CLIENT APPROVED			AS COBALT OR EQUAL & CLIENT APPROVED	
	SUSPENDED LINEAR LED 2800MM UP/DOWN LIGHT OPAL DIFFUSER, 6050 LUMENS, 42W DIMMABLE 4000K 121LL/CW			WALL MOUNTED LED UP/DOWN LIGHT LUMINAIRE 10W DIMMABLE 2700K			WALL MOUNTED EXTERNAL CIRCULAR LUMINAIRE PLAIN COVER, 2070 LUMENS, 16W 4000K 103.5LL/CW	
	AS THORLUX FLEXBAR DIFFUSER OR EQUAL & CLIENT APPROVED			AS ENIGMA TUBULAR 30 OR EQUAL & CLIENT APPROVED			AS COBALT OR EQUAL & CLIENT APPROVED	
	SUSPENDED LINEAR LED 1400MM UP/DOWN LIGHT OPAL DIFFUSER, 1815 LUMENS, 12W DIMMABLE 4000K 121LL/CW			WALL MOUNTED LED DOWN LIGHT LUMINAIRE 7W 2700K 97LL/CW			WALL MOUNTED AREA FLOODLIGHT PHOTOCELL, 3225 LUMENS, 31W 4000K 92.1LL/CW	
	AS THORLUX FLEXBAR DIFFUSER OR EQUAL & CLIENT APPROVED			AS DELTALIGHT GALA XL LP OR EQUAL & CLIENT APPROVED			AS THORLUX STARBEAM OR EQUAL & CLIENT APPROVED	
	SUSPENDED LINEAR LED 1400MM UP/DOWN LIGHT OPAL DIFFUSER, 3025 LUMENS, 21W DIMMABLE 4000K 126LL/CW		 	CEILING MOUNTED CIRCULAR LUMINAIRE CLEAR COVER, 2705 LUMENS, 17W 4000K 142.4LL/CW			WALL MOUNTED AREA FLOODLIGHT PHOTOCELL, 12570 LUMENS, 88W 4000K 132.3LL/CW	
	AS THORLUX FLEXBAR DIFFUSER OR EQUAL & CLIENT APPROVED			AS THORLUX OVIX OR EQUAL & CLIENT APPROVED			AS THORLUX STARBEAM OR EQUAL & CLIENT APPROVED	
	SUSPENDED LINEAR LED 1400MM UP/DOWN LIGHT OPAL DIFFUSER, 4325 LUMENS, 30W DIMMABLE 4000K 127.2LL/CW		 	WALL MOUNTED CIRCULAR LUMINAIRE CLEAR COVER, 3685 LUMENS, 24W 4000K 136.542.4LL/CW				
	AS THORLUX FLEXBAR DIFFUSER OR EQUAL & CLIENT APPROVED			AS THORLUX OVIX OR EQUAL & CLIENT APPROVED				
	SURFACE LINEAR LED 1200MM LUMINAIRE 5270 LUMENS, 31W 4000K 150.6LL/CW		 	RECESSED LED FIXED DOWNLIGHT 2210 LUMENS, 16W DIMMABLE 4000K 110.5LL/W				
	AS THORLUX JUBILEE OR EQUAL & CLIENT APPROVED			AS THORLUX G3 OR EQUAL & CLIENT APPROVED				
	WALL MOUNTED CIRCULAR LUMINAIRE CLEAR COVER, 2705 LUMENS, 17W 4000K 142.4LL/CW			SURFACE LED DOWNLIGHT 1700 LUMENS, 11W DIMMABLE 4000K 121.4LL/W				
	AS THORLUX OVIX OR EQUAL & CLIENT APPROVED			AS THORLUX G3 PRO SURFACE OR EQUAL & CLIENT APPROVED				
	WALL MOUNTED CIRCULAR LUMINAIRE CLEAR COVER, 3685 LUMENS, 24W 4000K 136.542.4LL/CW			SUSPENDED LED PENDANT LUMINAIRE 806 LUMENS, 8W 2700K 100.8LL/CW				
	AS THORLUX OVIX OR EQUAL & CLIENT APPROVED			AS THORLUX TRADITIONAL OR EQUAL & CLIENT APPROVED				

/E DENOTES EMERGENCY LUMINARIES EQUIPPED WITH 3-HOUR INTEGRAL EMERGENCY BATTERY PACK - SELF TEST

