

Specifications Table for RXP-M

					RXP20M5V1B	RXP25M5V1B	RXP35M5V1B	RXP50M2V1B	RXP50M5V1B	RXP60M2V1B	RXP60M5V1B	RXP71M2V1B	RXP71M5V1B
Dimensions	Unit		Height	mm	550	550	550	734	734	734	734	734	734
			Width	mm	658	658	658	870	870	870	870	870	870
			Depth	mm	275	275	275	373	373	373	373	373	373
Weight	Unit			kg	26	26	28	46.0	46.0	50.0	50.0	50.0	50.0
Compressor	Type				Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor
Operation range	Cooling	Ambient	Min.	°CDB	-10	-10	-10	-10	-10	-10	-10	-10	-10
			Max.	°CDB	48	48	48	46	48	46	48	46	48
Sound pressure level	Cooling		Nom.	dBA	46	46	48	47	47	49	49	52	52
	Heating		Nom.	dBA	47	47	48	49	49	49	49	52	52
Refrigerant	Type				R-32	R-32	R-32	R-32	R-32	R-32	R-32	R-32	R-32
	Charge			kg	0.55	0.55	0.70	0.90	0.90	1.15	1.15	1.15	1.15
	Charge			tCO2Eq	0.37	0.37	0.48	0.61	0.61	0.78	0.78	0.78	0.78
	GWP				675.0	675.0	675.0	675	675	675	675	675	675
Piping connections	Piping length	OU - IU	Max.	m	15	15	15	30	30	30	30	30	30
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)
	Level difference	IU - OU	Max.	m	12	12	12	20	20	20	20	20	20
Standard Accessories	Installation manual				1	1	1	1	1	1	1	1	1
	Refrigerant charge label				1	1	1	1	1	1	1	1	1
	Multilingual fluorinated greenhouse gases labels				1	1	1	1	1	1	1	1	1
Give Feedback	Drain cap							3	3	3	3	3	3
	Drain plug				1	1	1	1	1	1	1	1	1
	Power supply	Phase			1~	1~	1~	1~	1~	1~	1~	1~	1~
		Frequency		Hz	50	50	50	50	50	50	50	50	50
		Voltage		V	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Standard Accessories	General safety precautions				1	1	1						