



Note:
Contractor is to verify all dimensions and levels on site prior to site works commencement. Under no circumstances are any dimensions or levels to be scaled from this drawing number for the purpose of manufacturing components. Contractor to report any discrepancies to the Designer.

DRAWING KEY:

- 2500mm high Railing Fence Comprising of: Posts 70 x 70mm RHS, 50 x 10mm flat top and bottom rails, 25mm CHS infill at 110mm centres. Posts set in concrete behind the concrete upstand at 2810mm centres
- 'EuroGuard Regular' fencing of 2410mm (H) x 3054mm (W) panels with welded mesh of 5mm dia and wire spacing of 195mm x 45mm. Posts to be rectangle hollow section with anti-tamper connectors, galvanized to BS EN 1461. Post dimensions subject to height of fence and to be confirmed by contractor, set at maximum 3034mm centres with over length set in suitable concrete bedding as per manufacturer's instructions. Fencing and posts to be powder-coated colour Green RAL6005.

REVISION		DESCRIPTION		DATE
--				
SCALE 1:500			SIGNATURE	DATE
		DRAWN	MP	NOV 24
ORIGINAL SIZE A1		CHECKED	MB	NOV 24
		APPROVED	MB	NOV 24
This drawing is copyright and may not be reproduced or made use of unless expressly agreed by M Bradbury Consulting Ltd				
CLIENT The Barlow RC High School Parrs Wood Road Didsbury Manchester M20 6BX				
PROJECT Boundary Fencing Replacement				
<div> 59 Wilmslow Road, Handforth, Cheshire, SK9 3EN WEB: www.bradbury-consulting.co.uk TEL: 01625 522 209</div>				
TITLE AS PROPOSED FENCING TYPES				
JOB NUMBER 2024.054				
DRAWING NUMBER 2024.054.005				