

Manhole schedule - Surface Water																			GENERAL NOTES:			
MH REF	CL (mAOD)	IL (mAOD)	DEPTH TO SOFFIT (mAOD)	DS PIPE DIA (mm)	MH DIA (mm)	MH TYPE	CATCHPIT	CATCHPIT DEPTH (mm)	COVER SIZE (mm)	COVER CLASS	COVER TYPE	RECESSED	BACK DROP	Back drop IL (m)	RESTRICTED ACCESS	COMMENTS	EASTING	NORTHING				
S1	85.49	84.37	0.89	225	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	Y	N	N/A	N	UNRESTRICTED;	387953.19	400670.32				
S2	86.25	84.04	1.98	225	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	388002.52	400680.34				
S3	86.34	83.91	2.21	225	1200	TYPE B	Y	300	600X600	D400	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	388010.34	400678.42				
S4	86.32	83.84	2.25	225	1200	TYPE B	Y	300	600X600	D400	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	388013.31	400664.08				
S5	85.70	84.65	0.90	150	600	PPIC	N	N/A	600X600	D400	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	387986.15	400636.57				
S6	85.92	84.50	1.20	225	600	PPIC	N	N/A	600X600	D400	SINGLE SEALED	Y	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	388002.50	400644.64				
S7	86.11	83.78	2.11	225	1200	TYPE B	N	N/A	600X600	D400	SINGLE SEALED	Y	N	N/A	N	UNRESTRICTED;	387999.46	400660.37				
S8	85.32	84.27	0.90	150	600	PPIC	N	N/A	600X600	D400	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	387968.42	400631.77				
S9	85.36	84.03	1.11	225	600	PPIC	N	N/A	600X600	D400	SINGLE SEALED	Y	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	387977.71	400636.54				
S10	85.55	83.38	1.95	225	1200	TYPE B	N	N/A	600X600	D400	SINGLE SEALED	Y	N	N/A	N	UNRESTRICTED;	387969.49	400654.24				
S11	85.22	84.44	0.63	150	450	PPIC	N	N/A	450X450	D400	SINGLE SEALED	Y	N	N/A	N	UNRESTRICTED;	387949.37	400656.91				
S12	85.50	84.36	0.99	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	Y	N	N/A	N	UNRESTRICTED;	387956.88	400657.88				
S13	85.34	83.37	1.75	225	1500	TYPE B	N	N/A	600X600	D400	SINGLE SEALED	Y	N	N/A	N	FLOW CONTROL CHAMBER MAX DISCHARGE RATE 20.3l/s CTL-SHE-0118-5600-0500-5600	387958.46	400651.98				
S14	85.74	85.01	0.58	150	450	PPIC	N	N/A	450X450	B125	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	388004.17	400615.39				
S15	85.46	84.51	0.80	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	387988.51	400608.87				
S16	85.51	84.41	0.88	225	600	PPIC	N	N/A	600X600	D400	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	387984.16	400617.97				
S17	86.07	85.16	0.76	150	450	PPIC	N	N/A	450X450	B125	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	388015.93	400621.04				
S18	86.08	84.83	1.03	225	600	PPIC	N	N/A	600X600	D400	SINGLE SEALED	N	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	388011.21	400630.73				
S19	86.57	85.33	1.09	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	388024.77	400637.35				
S20	86.82	85.13	1.54	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	388044.35	400641.43				
S21	86.83	84.92	1.69	225	600	PPIC	N	N/A	600X600	D400	SINGLE SEALED	N	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	388041.80	400654.72				
Manhole schedule - Foul Water																						
MH REF	CL (mAOD)	IL (mAOD)	DEPTH TO SOFFIT (mAOD)	DS PIPE DIA (mm)	MH DIA (mm)	MH TYPE	CATCHPIT	CATCHPIT DEPTH (mm)	COVER SIZE (mm)	COVER CLASS	COVER TYPE	RECESSED	BACK DROP	Back drop IL (m)	RESTRICTED ACCESS	COMMENTS	EASTING	NORTHING				
F1	86.06	85.14	0.82	100	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	388012.67	400618.96				
F2	85.99	85.09	0.80	100	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	388010.97	400618.14				
F3	85.76	84.87	0.74	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	387998.73	400612.25				
F4	85.69	84.86	0.68	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	387996.94	400611.39				
F5	85.39	84.31	0.98	100	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	387983.32	400604.84				
F6	85.46	84.26	1.10	100	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	N	UNRESTRICTED;	387985.09	400605.69				
F7	85.69	84.10	1.44	150	450	PPIC	N	N/A	450X450	B125	SINGLE SEALED	N	Y	84.81	Y	RESTRICTED ACCESS 350mm DIA MAX;	387992.94	400609.46				
F8	85.63	84.03	1.45	150	450	PPIC	N	N/A	450X450	D400	SINGLE SEALED	N	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	387988.43	400619.77				
F9	86.63	84.01	2.47	150	450	PPIC	N	N/A	450X450	D400	SINGLE SEALED	N	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	387989.89	400621.00				
F10	86.57	85.32	1.15	100	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	Y	95.95	Y	RESTRICTED ACCESS 350mm DIA MAX;	388019.47	400650.11				
F11	86.65	85.22	1.33	100	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	Y	85.95	Y	RESTRICTED ACCESS 350mm DIA MAX;	388023.56	400650.96				
F12	86.83	85.52	1.21	100	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	Y	86.17	Y	RESTRICTED ACCESS 350mm DIA MAX;	388037.18	400653.78				
F13	86.74	85.40	1.24	100	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	Y	86.10	Y	RESTRICTED ACCESS 350mm DIA MAX;	388032.63	400652.84				
F14	86.68	85.05	1.48	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	Y	86.02	Y	RESTRICTED ACCESS 350mm DIA MAX;	388028.19	400651.92				
F15	85.94	84.64	1.20	100	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	Y	85.16	Y	RESTRICTED ACCESS 350mm DIA MAX;	387992.40	400654.63				
F16	86.96	84.59	2.37	100	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	Y	85.16	Y	RESTRICTED ACCESS 350mm DIA MAX;	387988.31	400653.04				
F17	85.78	84.42	1.36	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	387984.02	400650.97				
F18	85.78	84.38	1.40	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	Y	85.06	Y	RESTRICTED ACCESS 350mm DIA MAX;	387979.73	400648.91				
F19	85.78	84.35	1.43	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	Y	85.06	Y	RESTRICTED ACCESS 350mm DIA MAX;	387975.43	400646.84				
F20	85.34	84.21	1.13	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	387969.96	400646.57				
F21	85.34	84.17	1.17	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	Y	84.62	Y	RESTRICTED ACCESS 350mm DIA MAX;	387965.67	400644.50				
F22	85.34	84.13	1.21	150	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	N	N/A	Y	RESTRICTED ACCESS 350mm DIA MAX;	387960.08	400642.22				
F23	86.22	84.92	1.30	100	600	PPIC	N	N/A	600X600	B125	SINGLE SEALED	N	Y	85.50	Y	RESTRICTED ACCESS 350mm DIA MAX;	388000.50	400667.43				
F24	86.15	84.85	1.30	10																		