

Method statement – Historical décor

Company: Jennor UK Ltd

Position: Main contractor

Date: 12.12.24

Project: Free trade CATB fit out ground & first floor



Paint products specified in relation to historical finishes and why?

Crown paints – Clean air

Location – Perimeter historical walls (Light colors)

To locations utilizing light colors to the perimeter walls, Crowns trade clean air paints will be applied by main contractor approved decorators using three coats with a roller and cut in top and bottom of the wall with a 3inch brush. This paint has been specified by the project team due to its cleanable/scrubbable factor for high traffic areas to reduce the requirement to touch up areas over time while also utilizing its breathable and clean Air technology to provide the most breathable paint for historical surfaces.

Crown paints – Matt emulsion

Location – Perimeter historical walls (Dark colors)

To locations utilizing dark, deep and rich colors not available in Crown trade clean air - The tenant and main contractor have agreed to reduce the spec to standard matt emulsion to avoid coating the perimeter walls in a paint that masks the historical fabric and instead promotes breathable properties through crowns trade standard emulsion. Again, apply three coats using roller cutting in top and bottom of each wall.

Crown paints – Water based satin.

Location – Woodwork

Woodwork finishes will receive two coats of water-based satinwood to all woodwork to promote the nonuse of harsh chemicals to perimeter woodwork commonly found in Oil-based paints.

PPE.

- Gloves
- Hi-vis.
- Boots
- Safety glasses

Safety measures undergone.

- All operatives to read and sign Jennor site induction prior to any works.
- All decorating trades to be noted of all historical fabrics and required finished.
- Sub-contractor to provide paper copy of RAMS & RAMS sign off email prior to start.
- Working at height to via scaffold or ladder with daily checks
- Working area to kept tidy of all materials and trip hazards.