

Air Bricks Cleaning

1. Regularly inspect the vent and remove any visible debris or dirt by hand.
2. Use a soft-bristled brush or a vacuum cleaner with a brush attachment to clean the grilles and openings to ensure optimal airflow.
3. If the vents are excessively dirty or clogged, gently wash them with mild soapy water and a sponge. Avoid using strong cleaning agents that could damage the brickwork.

Air Bricks Maintenance

1. Ensure vents are regularly inspected and cleaned to prevent clogging and restricted airflow.
2. If you notice any damage or deterioration in the vents, promptly repair or replace them to maintain optimal functionality.
3. Avoid using abrasive cleaning materials that could scratch or damage the vent surfaces.
4. For vents in damp areas, keep an eye out for mould or mildew growth and address it promptly with appropriate cleaning agents.

Tools

<u>Bristle type:</u>	Stiff, nylon bristles that can effectively scrub away dirt without damaging the air brick material.
<u>Size and shape:</u>	The brush head is designed to fit into the opening of most standard air bricks, allowing for thorough cleaning.
<u>Handle length:</u>	The handle is long enough to reach into the air brick without needing to remove it from the wall, depending on the design.

Alternatives to a dedicated air brick brush:

Small paintbrush

A small, stiff-bristled paintbrush can be used in a pinch.

Vacuum cleaner with brush attachment

For light cleaning, you can use a vacuum cleaner with a small brush head to remove surface dust.