

© This drawing is copyright protected and may not be reproduced in whole or part without written authority from the owner.

NOTES:

1. Do not scale from this drawing.
2. Always work to noted dimensions.
3. All dimensions are in millimetres unless otherwise stated.
4. All setting out, levels and dimensions to be agreed on site.
5. The dimensions of all materials must be checked on site before being laid out.
6. This drawing must be read with the relevant specification clauses and detail drawings.
7. Order of construction and setting out to be agreed on site.

KEY

REDLINE BOUNDARY

HARDWORKS

P1 — **NATURAL STONE PAVING - TYPE 1**
To feature paving areas
Material: UK sourced sandstone
Finish: Rubbed
Size: 100mm(W)x100-250mm(L)x depth TBC by engineer.

P2 — **NATURAL STONE PAVING - TYPE 2**
To edges of footways
Material: UK sourced sandstone
Finish: rock faced
Size: 100mm(W)x100(L)x depth TBC by engineer.

P3 — **PERMEABLE RESIN BOUND GRAVEL**
To pedestrian footways
Product: 'Natural aggregate paving'
Colour: Winter Bronze
Size: Refer to engineer's details for depth
Supplier: SureSet Or acceptable equivalent.

P4 — **CORKEEN PLAY SURFACING**
To areas of play or gym equipment
Product: Corkeen
Colour: As supplied
Supplier: Corkeen or acceptable equivalent.

P5 — **TIMBER BOARDWALK - TYPE 1**
To northern park walkway
Material: Composite decking
Product:Lasta-Grip®
Colour:Coppered Oak
Supplier: Millboard or similar approved

P6 — **TIMBER BOARDWALK - TYPE 2**
To match existing Cotton Field Park
Material: Hardwood timber decking
Finish: Castle topped

S1 — **NATURAL STONE STEPS**
To terraced gardens.
Material: Pennant Sandstone with integrated high contrasting nosing
Size: 400mm(W) x1000mm(L) x 150mm(D) modules.
Supplier: Hardscape or similar approved

P7 — **SELF BINDING GRAVEL**
Product: CEDEC - footpath gravel
Colour: Red
Dimensions: 65mm compacted to 50mm depth
Supplier: CED or other equal and approved
Note: Geotextile membrane below the sub-base to prevent weeds

P8 — **NATURAL STONE PAVING - TYPE 3**
Natural stone paving to match specification of phase 1 works along pedestrian boulevard.

P9 — **NATURAL STONE PAVING - TYPE 4**
Yorkstone flag paving to adopted footways along Great Ancoats Streets.
Size: (MCC specification):
600mm width x random lengths
600-900mm
- Laid: Stretcher bond

P10 — **WHITE LINING WORKS**
To Hugh Oldham Way
Allowance for white lining works for crossing point to new gateway of Cotton Field Park.

T1 — **TACTILE PAVING TYPE 1**
Corduroy paving to top and bottom of steps
Material: Pennant Sandstone
Finish: Corduroy
Size:400mm(W)x400mm(L)x60mm(D)

T2 — **TACTILE PAVING TYPE 2**
Cycle hazard paving to end of cycle lane in S278 works. Subject to S278 details

T3 — **TACTILE PAVING TYPE 3**
Blister hazard paving to pedestrian crossing. Subject to S278 details

Revision	Date	Description	Drawn	Apprvd.
P09	01/11/24	Planning Issue	CS	SB

PLANIT
Manchester | London | Liverpool | Leeds | Standish
Manchester
2 Back Grafton Street,
Altrincham,
Cheshire,
WA14 1DY,
W: planit-ie.com
E: info@planit-ie.com
T: 0151 363 1230

Client Manchester City Council

Project Former Central Retail Park

Drg Title Hardworks

Created on	Created by	Approved by
03/01/24	CS	SB

Scale	Size	Workstage	Status
1:400	A1	Stage 3	

Drg No.	Suitability	Revision
3363-PLA-00-ZZ-DR-L-1000	S4	P09

© Planit I.E. Limited