

Health and Safety Management Systems	Oldham Service Station 571 Oldham Road, Manchester, M40 5AF
COSHH Assessment -	Grease

Substance and Activity – Grease for Lubrications

Description of Substance – semi solid	Hazard Identification (symbols) CARCINOGENIC, HARMFUL, DANGEROUS TO THE ENVIRONMENT, EXPLOSIVE 
---------------------------------------	--

X Employees (E) X Sub-contractors (S) ☐ General Public (GP) ☐ Official Visitors (OV) ☐ Others (O)

SIGNIFICANT HAZARDS ASSOCIATED WITH THE ACTIVITY	PERSONS AT RISK	L	S	RISK
Accidental product into eyes.	E, S	1	2	Low (2)
Repeated/prolonged contact with skin causes dermatitis and may lead to cancer.	E, S	1	3	Medium(3)
Note :				

RISK CONTROL MEASURES	PPE RIQUIREMENTS
Always handle with care and wearing appropriate PPE	Goggles or face shield to BS EN 166
Avoid contact with skin. Always wear appropriate PPE. Wear barrier creams.	Overalls (covering arms) Nitrile gloves to BS EN 374

FIRST AID MEASURES	
Eyes	Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
Ingestion	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice
Inhalation	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice
Skin	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds
Other	

EMERGENCY ACTION	
Spillage	Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers
Fire	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

STORAGE REQUIREMENTS	
Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Storage Temperature: 0 - 50°C / 32 - 122°F The storage of this product may be subject to the Control of Pollution (Oil Storage) (England) Regulations. Further guidance maybe obtained from the local environmental agency office.	

DISPOSAL REQUIREMENTS	
Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses	

COSSH ASSESSMENT KEY					HS8-36_COSHH Assessment: 19 March 2015 Diesel	
Risk assessment = S X L		1 = Slight	2= Serious	3= Major		
= LIKELIHOOD	3 = Likely	Medium(3)	High (6)	High (9)	1-2 = Low -No urgent action required	Low
	2 = Possible	Low (2)	Medium (4)	High (6)	3-4 = Medium - controls to be implemented	Medium
	1 = Rare	Low (1)	Low (2)	Medium (3)	6-9 High- Special controls to be implemented	High