

ELLIS2


twoway



Arcluce Code

0478006A+840+21

Ex Code



TECHNICAL INFORMATION

Light source: LED, 4000K, 18W, 2700lm, CRI>80

Indirect light source: LED, 4000K, 18W, 2700lm, CRI>80

Light efficiency: 98lm/W

Power luminaire: 40W, 3900lm

LED life time: > 50000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optic: medium 29° ±? = 20°

Indirect optic: medium 29° ±? = 20°

Color: Aluminium - 21

Weight: 5.5 kg

Size:
A: 200mm
B: 455mm
C: 210mm

CE

IP65

IK07



0,09m²

850°

Appliance

- Extruded aluminium body.
- Die-cast aluminium trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Knife-switch for automatic power disconnection when opened.
- PMMA lenses for LEDs.
- Reflector made of 99,98 anodized aluminium with non-iridescent specular finishing.
- Screen made of 10mm thermal-shock resistant tempered glass.
- It complies with standards EN 60598-1 and EN 60598-2-1.

Installation

- Wall mounted.
- M20 engineering plastic cable gland.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Light Control".