PRY-2CM

TECHNICAL SPECIFICATION

This Range

Beautiful range of porcelain tiles, suitable for interior applications, in 8.5mm thickness.

Suitable for:

Heavy Footfall | Pool Edging | Stairs | Paving

Sizes

900 x 600 x 20mm Rectified
600 x 600 x 20mm Rectified

Colours

Prysand	
 **Prygrey**	
 **Pygraphite**	

Technical Details - 20mm

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	≤ 0,5%	**Compliant**
Breaking Strength	ISO 10545-4	≥ 2500N	**Compliant**
Modulus of Rupture	ISO 10545-6	≤ 40N/mm2	**Compliant**
Surface Abration	ISO 10545-8	Sand Grey Graphite	**Class4** **Class4** **Class3**
Stain Resistance	ISO 10545-14	Classe / Class 3 Min.	**Compliant**
Chemical Resistance (*)	ISO 10545-13	As indicated by manufacturer	**Compliant**
Frost Resistance	ISO 10545-12	No alteration	**Resistant**
Slip Resistance	BS 7976:2002	Declared value	+68ptv
Thickness	ISO 10545-2	+/-0.5	**Compliant**

(*) Excluding hydrofluoric acid and its derivatives. (**) The width of grout joints must be established by the installation supervisor, unless grout widths are regulated by national laying standards.

Packing Details

Size	No./ Pal	Kg/Pal	Mq/Pal
900 x 600 x 20mm Rectified	42	1085	22.49
600 x 600 x 20mm rectified	62	1075	22.32

PrySand

PryGrey

PryAnthracite

204 Duggins Lane, Tile Hill, Coventry,
CV4 9GP
02475 092 859
www.keystoneco.co.uk