



## Luminaire Specification

|                      |                                  |                                                      |                                  |
|----------------------|----------------------------------|------------------------------------------------------|----------------------------------|
| <b>Diffuser</b>      | Frosted                          | <b>Diffuser</b>                                      | Flat                             |
| <b>Driver</b>        | 24VDC - To be ordered separately | <b>Finish</b>                                        | Aluminium                        |
| <b>Material</b>      | Aluminium                        | <b>LED CRI/CCT</b>                                   | 3000°K CRI>90                    |
| <b>Mounting Type</b> | Recessed                         | <b>LED Type</b>                                      | 38.4W/m - 2835 HD - 2x240 LEDs/m |
| <b>LED Binning</b>   | 3 Step MacAdam ellipse           | <b>Length</b>                                        | 1000 mm                          |
| <b>IP Rating</b>     | IP20                             | <b>Configured Power /<br/>Delivered Lumen Output</b> | 38.40W / 2764lm                  |
| <b>Driver</b>        | 24VDC - To be ordered separately | <b>LED Cut Point</b>                                 | 25mm                             |
| <b>CRI</b>           | >90Ra                            |                                                      |                                  |
| <b>LED Binning</b>   | 3 Step MacAdam ellipse           |                                                      |                                  |

## Ordering Information

### CANOPY LINEAR

6765356.5C303838.1000

Weiss Large 65x35mm - Flat : Aluminium : 3000°K CRI>90 : 38.4W/m - 2835 HD - 2x240 LEDs/m : 1000 mm