

OUTDOOR WALL

BIM LAMP 10W-3000K-U&D-IP65-CHARCOAL GREY

BL05102002

OUTDOOR > Outdoor Wall Light

Indoor or outdoor wall light, up and down lighting (2x5W). Angle of light diffusion adjustable thanks to shutters. Ideal for creating an atmosphere that is both modern and friendly.



Application domain

- Outdoor residential
- Garden
- Outdoor illumination
- Bedroom
- House Corridor
- Entrance Halls
- Outdoor lighting



Electric data

Total power (W)	10
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	I
Dimmable	No

Photometric data

Color temperatures	3000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM<5
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	430lm (3000K)
ULOR	-

Technical data

Dimensions (mm)	96 x 120 x 100
Weight (kg)	0.58
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	Dark gray
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-25... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Light beam spread	20° X 90°
Tiltable	No
Connection type	Bornier avec repiquage
Linked products	<ul style="list-style-type: none">• BL05102001 - BIM APP 10W-3K-U&D-IP65-B