STL110 COMPRESSOR STATION



Description

Our specialist team of project engineers have designed and tailor-made a solution to meet our customers' specific compressed air requirements.

Designed from a range of standard and bespoke components, every detail has been looked at to ensure the customer is receiving the highest quality compressor station on the market. Stanwell are also proud to provide a dedicated team of in-house and mobile service engineers to ensure our service is maintained throughout the life of our compressors.

Technical Specification

- Start Current: 8 Amps
- Max Run Current: 2.6 Amps
- Consumption: 0.56 KW at 230 Volts (-6% +10%)
- Nominal Pressure: 7 Bar
- Sound Level: 68-70db (A)
- Protection Class: IP23 F Class Windings
- 100% Continuous Rating At: 7 Bar
- Max Ambient Temperature: 40 deg. C
- Assembled Weight: 21Kg
- Receiver Volume: 24L
- Air Outlets: 3/8 JG
- Receiver Recharge Time: 48 Seconds between 4.5 Bar & 7 Bar
- Max No. of Pumps Driven: 14-16 (depending on top pressure)

Features

- Lightweight Stainless Steel Receiver
- All fittings are Non Corrosive
- Oil free operation
- Automatic Condensate Removal
- Available with Wall Mounting Bracket
- Complies with PED 97/23 CE and Machinery Directive 98/37EC
- Fail Safe Overload Protection
- Winding Thermal Cut-out

The Stanwell Technic Compressor Station Includes a 5 Year Warranty

STANWELL
TECHNIC LIMITED

Hope Bank Works, New Mill Road, Honley, Holmfirth, West Yorkshire, HD9 6PT
t: (+44) 01484 660500 f: (+44) 01484 660501 e: sales@stanwelltechnic.co.uk w: www.stanwelltechnic.co.uk