

ROLLED LEAD SHEET

BLM's Rolled Lead Sheet is manufactured to British Standard BS EN 12588 and made from 100% recycled raw material.

The British Standard ensures the alloy used contains a minimum amount of Lead and the correct amount of trace elements. It also guarantees a consistent thickness (+/- 5%) and grain structure, so its performance can be accurately predicted to provide maximum lifespan for correctly fitted Lead Sheet used in construction.

We supply Rolled Lead Sheet in any width from 150mm to 1580mm in Codes 3,4 and 5 and up to 1275mm in Codes 6,7 and 8 in standard roll lengths of 3 and 6 metres.

Non-standard lengths and thicknesses are available upon request. Please be aware that extra charges and extended lead times may be applied.

British Standard Rolled Lead is produced to a calculated theory weight with a tolerance of +/- 5%. Theory weights of standard rolls can be found on the BLM Weight Chart.

Peace of Mind

BLM's Rolled Lead Sheet comes with a 50 year warranty providing it is installed in accordance with the LSTAs Rolled Lead Sheet Manual and BS 6915.

Lead Sheet applications also achieve a rating of A or A+ in the BRE Green Guide.



- If the width you require is not in stock it is worth ordering a wider piece to avoid delay.
- Save on cutting charges by ordering a standard length and cutting it yourself.
- Large orders of Lead can be delivered direct to site at no extra cost.
- Lead Sheet should be fitted in accordance with BS 6915 as detailed in Rolled Lead Sheet - The Complete Manual by the LSTA.

Helpful Tips