

Q40 Fencing & Gates Specification

To be read in conjunction with Preliminaries/General conditions

Description:	Sports perimeter fencing system
Standard:	BS1722-14: 2017 BS EN ISO 1461:2009 BS EN 13438:2013
Manufacturer:	CLD Fencing Systems info@cld-systems.com Tel. 01270 764751 www.cld-systems.com

Product Reference: **CLD Dulok Sports Rebound Double Wired Panel Fencing System**

Panel type:	Mesh and wire. Single vertical and double horizontal wires. Galvanised and powder-coated to minimum 60 microns.
Panel width:	2506mm
Wire diameter:	6mm verticals and 8mm horizontals
Mesh size:	66.5 x 50mm
Available heights Select as required:	1230mm, 2030mm as full rebound panels. 3030mm to 6060mm as combination of rebound and Dulok standard panels heights.
Nominal height:	1.2 to 6m
Finish:	Polyester powder-coated to minimum 60 microns. Any RAL colour including marine grade and metallics.
Top edge projection:	30mm on one side
Panel installation:	Bottom of panel minimum 50mm above ground
Security topping options:	n/a
Posts:	RHS, galvanised after manufacture and polyester powder-coated to match fencing
Post dimensions:	60mm x 40mm to 120mm x 60mm depending on height of panel
Maximum post Centres:	2520mm
Fixings:	40mm x 5mm full length clamp bar. M8 x 40mm stainless steel pin hex dome-head security screws. Sheardrive™ if required instead of pin hex. Rubber grommets available for noise reduction.

Foundations:	Set posts in holes minimum 300mm diameter x 800mm deep (depending on fence height) Contractor/ client is responsible for the foundation size suitable for the ground conditions
Warranty:	Minimum of 15 years against manufacturing defects.
Notes:	All dimensions are nominal, for further information please contact CLD Fencing Systems. Information is correct at time of production. As part of our policy of continuous improvement, we reserve the right to alter product specification without notice.