ASSURED TRAFFIC SOLUTIONS LTD

Lane Narrows

York Street
Manchester
M1 7DF

30 / 40mph Lane Closure

DETAIL B

3m

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 3m.
Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 3m.
Dual carriageway national speed limit - 750mm traffic cones, spacing 3m, relaxation 3m.

Notes:
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
2) 45° tapers have 1.5m spacing, no relaxations.
3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C2

6m

Single carriageway 40mph or less - 450mm traffic cones.
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

Qty: 2 Ref: 517 Road narrows on one side only ahead - right	
Qty: 2 Ref: 517 Road narrows on one side only ahead - left	
Qty: 3 Ref: 573 Direction to hazard left	
Qty: 2 Ref: 573 Direction to hazard right	
Qty: 2 Ref: 610 Keep right	
Qty: 5 Ref: 7001 Road works ahead	
Qty: 1 Ref: 7018 Pedestrian diversion Left	PEDESTRIANS
Qty: 1 Ref: 7018 Pedestrian diversion Right	PEDESTRIANS
Qty: 1 Ref: 7105 Lane closure barrier	

YORK STREET
DONALD ST
MAKIN ST
CHARLES STREET
Bracken House
Works
SP
PEDESTRIANS
PEDESTRIANS
6.75M

No parking cones to be installed 12-24 hours before works take place

CABIN
SAFETY ZONE
TRAFFIC CONES
PEDESTRIAN BARRIER
NO PARKING CONES
PEDESTRIAN RAMP
TELECOMMS MAST
TERRAPLAS
MARSHAL

Client Ref	C3343
Easting , Northing	384232 , 397480
Latitudinal Safety Zone	0.5m
Longitudinal Safety Zone	0.5m
Taper cone spacing	1.2m
Longways cone spacing	6m

30

Drawing Number	Drawn by / Date		Ammended by / Rev no / Date		
AB3953	AB	07/03/24	N/A	1	00/00/00