

Features:



- High performance energy efficient surface-mount-device (SMD) LED
- IP67 (dust tight & protected against temporary immersion in water up to 1 metre)
- Available in 3000K (warm white), 4000K (cool white) or 6000K (daylight) as standard
- CRI 80
- To be used in conjunction with 24VDC (constant voltage driver) - to be ordered separately
- 126 LEDs per metre
- 120° chip
- Supplied in rolls of 5m
- Strips can be cut every 55mm (at cutting points)
- Average 30,000 hours LED life - L70 B50
- Suitable for temperature range -25°C to +45°C

Options:

- Dimming versions available:
 - DALI dimming
 - Other dimming protocols available - please consult our technical department


Accessories:

- Mounting clip
- Plastic end cap

Beam Angles:



Technical Drawings





Neon Flex				Ordering Code
Wattage	Colour Temperature	Voltage	Source Lumens	
10.8W/m	3000K	24V	1284lm/m	Z40-141-081-300
10.8W/m	4000K	24V	1376lm/m	Z40-141-081-400
10.8W/m	6000K	24V	1340lm/m	Z40-141-081-600

Accessories	Ordering Code
Mounting clip (x1)	A40-16-01-00
End cap (x1)	A40-16-02-00

Drivers	Ordering Code	Combined DALI Dimming Drivers	Ordering Code
40W Driver, 24V constant output	D00-240-00-024	50W DALI Driver, 24V constant output	D00-250-03-024
60W Driver, 24V constant output	D00-260-00-024	75W DALI Driver, 24V constant output	D00-275-03-024
100W Driver, 24V constant output	D00-260-00-024	100W DALI Driver, 24V constant output	D00-2100-03-024
320W Driver, 24V constant output	D00-2320-00-024	360W DALI Driver, 24V constant output	D00-2360-03-024