

External Roof Profile

Euroseam

Data Sheet

EC 75-400 Euroseam



euroclad
group

External Roof Profile – Euroseam

Application

Euroseam is an external standing seam profile designed to be supported by our stainless steel or aluminium halters, dependent on application. This profile can be specified independently, or as the external finish of our Elite 4, 5, 8, and 9 Roof System Ranges. Euroseam is available in a variety of coatings, and can be rolled off-site or on-site depending upon project requirements.

Please download the latest technical drawing/s [here](#).

Standard Specification

- EC 75-400 Euroseam roof profile available in 0.9mm aluminium
- All coating options achieve BROOF(T4) to BS EN 13501-5:2016. Contact the Technical Team for more information
- Profile lengths can be supplied to site up to 14 metres using conventional transport methods
- Profile lengths can be supplied to site up to 22 metres using special transport methods at additional cost
- Profile lengths above 14 metres can also be rolled on-site to meet specific project requirements

Coatings

The Euroseam profile is specifiable in a number of coated aluminium options. PVDF, Polyester Polyamide (ARS) and Duragloss 5000 are all available, with the choice dependent upon the end use and environment of the building. Euroseam can also be supplied in uncoated Stucco Emboss on request.

Contact our [Technical Team](#) for further information regarding the above.

Product Parameters

Parameters	
Cover Width (Nominal)	397mm
Profile Pitch	397mm
Profile Depth	75mm
Runout Leg (Minimum)	56mm
On-site Rolling Availability	Yes
Natural Self Curve Min Radii Concave*	60m
Natural Self Curve Min Radii Convex*	45m
Smooth Curve Availability	Yes
Smooth Curve Minimum Sheet Length	2.0m
Smooth Curve Minimum Internal Radii	8.0m
Crimped Curve Availability	No
Weight (0.9mm)	3.67 kg/m ²

Build a Better Future Together

Euroclad Group Limited

Wentloog Corporate Park
Wentloog Road, Cardiff CF3 2ER
United Kingdom

Phone: +44 (0) 2922 010101

Email: rsc.technical@eurocladgroup.com

www.eurocladgroup.com



Please scan
the QR code or
[click here](#) for
the most up to
date version of
this document.



Care has been taken to ensure that the contents of this publication are accurate, but Euroclad Group Ltd and its subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use or application of products or methods of working are for information only and Euroclad Group Ltd and its subsidiaries accept no liability in respect thereof.

Colorcoat®, Colorcoat Prisma®, Confidex® and Galvalloy® are registered trademarks of Tata Steel UK Limited.