

ABA Consulting		Page 1
Unit A, Racecourse Business ... Dovefields, Uttoxeter Staffordshire, ST14 8GB	Brunswick Mill south Area bld SW model 01	
Date 23/09/2023 15:01 File	Designed by BD Checked by	
Innovyze	Network 2020.1	

STORM SEWER DESIGN by the Modified Rational Method

Design Criteria for Storm

Pipe Sizes STANDARD Manhole Sizes STANDARD

FSR Rainfall Model - England and Wales

Return Period (years)	1	PIMP (%)	100
M5-60 (mm)	18.000	Add Flow / Climate Change (%)	0
Ratio R	0.361	Minimum Backdrop Height (m)	0.200
Maximum Rainfall (mm/hr)	50	Maximum Backdrop Height (m)	1.500
Maximum Time of Concentration (mins)	30	Min Design Depth for Optimisation (m)	1.200
Foul Sewage (l/s/ha)	0.000	Min Vel for Auto Design only (m/s)	1.00
Volumetric Runoff Coeff.	0.750	Min Slope for Optimisation (1:X)	500

Designed with Level Soffits

Time Area Diagram for Storm

Time (mins)	Area (ha)	Time (mins)	Area (ha)
0-4	0.048	4-8	0.009

Total Area Contributing (ha) = 0.057

Total Pipe Volume (m³) = 0.791

Network Design Table for Storm

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design
1.000	24.311	0.200	121.6	0.019	5.00	0.0	0.600	o	150	Pipe/Conduit	
1.001	10.417	0.100	104.2	0.019	0.00	0.0	0.600	o	150	Pipe/Conduit	
1.002	1.909	0.100	19.1	0.019	0.00	0.0	0.600	o	150	Pipe/Conduit	
1.003	8.109	0.100	81.1	0.000	0.00	0.0	0.600	o	150	Pipe/Conduit	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
1.000	45.19	5.45	52.800	0.019	0.0	0.0	0.0	0.91	16.1	2.3
1.001	44.56	5.62	52.600	0.038	0.0	0.0	0.0	0.98	17.4	4.6
1.002	44.52	5.64	52.500	0.057	0.0	0.0	0.0	2.32	40.9	6.9
1.003	44.10	5.76	52.400	0.057	0.0	0.0	0.0	1.12	19.7	6.9

ABA Consulting		Page 2
Unit A, Racecourse Business ... Dovefields, Uttoxeter Staffordshire, ST14 8GB	Brunswick Mill south Area bld SW model 01	
Date 23/09/2023 15:01 File	Designed by BD Checked by	
Innovyze Network 2020.1		

Simulation Criteria for Storm

Volumetric Runoff Coeff	0.750	Additional Flow - % of Total Flow	0.000
Areal Reduction Factor	1.000	MADD Factor * 10m ³ /ha Storage	2.000
Hot Start (mins)	0	Inlet Coefficient	0.800
Hot Start Level (mm)	0	Flow per Person per Day (l/per/day)	0.000
Manhole Headloss Coeff (Global)	0.500	Run Time (mins)	60
Foul Sewage per hectare (l/s)	0.000	Output Interval (mins)	1

Number of Input Hydrographs	0	Number of Storage Structures	1
Number of Online Controls	1	Number of Time/Area Diagrams	0
Number of Offline Controls	0	Number of Real Time Controls	0

Synthetic Rainfall Details

Rainfall Model	FSR	Profile Type	Summer
Return Period (years)	1	Cv (Summer)	0.750
Region	England and Wales	Cv (Winter)	0.840
M5-60 (mm)	18.000	Storm Duration (mins)	30
Ratio R	0.361		

©1982-2020 Innovyze

ABA Consulting		Page 3
Unit A, Racecourse Business ... Dovefields, Uttoxeter Staffordshire, ST14 8GB	Brunswick Mill south Area bld SW model 01	
Date 23/09/2023 15:01 File	Designed by BD Checked by	
Innovyze	Network 2020.1	

Online Controls for Storm

Hydro-Brake® Optimum Manhole: 3, DS/PN: 1.002, Volume (m³): 1.6

Unit Reference	MD-SHE-0109-5000-0800-5000
Design Head (m)	0.800
Design Flow (l/s)	5.0
Flush-Flo™	Calculated
Objective	Minimise upstream storage
Application	Surface
Sump Available	Yes
Diameter (mm)	109
Invert Level (m)	52.500
Minimum Outlet Pipe Diameter (mm)	150
Suggested Manhole Diameter (mm)	1200

Control Points	Head (m)	Flow (l/s)
Design Point (Calculated)	0.800	5.0
Flush-Flo™	0.241	5.0
Kick-Flo®	0.537	4.2
Mean Flow over Head Range	-	4.3

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake® Optimum as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated

Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)
0.100	3.7	1.200	6.0	3.000	9.3	7.000	13.9
0.200	5.0	1.400	6.5	3.500	10.0	7.500	14.4
0.300	5.0	1.600	6.9	4.000	10.6	8.000	14.8
0.400	4.8	1.800	7.3	4.500	11.3	8.500	15.2
0.500	4.5	2.000	7.7	5.000	11.8	9.000	15.7
0.600	4.4	2.200	8.0	5.500	12.4	9.500	16.1
0.800	5.0	2.400	8.4	6.000	12.9		
1.000	5.5	2.600	8.7	6.500	13.4		

ABA Consulting		Page 4												
Unit A, Racecourse Business ... Dovefields, Uttoxeter Staffordshire, ST14 8GB	Brunswick Mill south Area bld SW model 01													
Date 23/09/2023 15:01 File	Designed by BD Checked by													
Innovyze	Network 2020.1													
Storage Structures for Storm Tank or Pond Manhole: 3, DS/PN: 1.002 Invert Level (m) 52.500 <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Depth (m)</th><th>Area (m²)</th><th>Depth (m)</th><th>Area (m²)</th></tr></thead><tbody><tr><td>0.000</td><td>10.0</td><td>0.700</td><td>10.0</td><td>0.701</td><td>0.0</td></tr></tbody></table>			Depth (m)	Area (m²)	Depth (m)	Area (m²)	Depth (m)	Area (m²)	0.000	10.0	0.700	10.0	0.701	0.0
Depth (m)	Area (m²)	Depth (m)	Area (m²)	Depth (m)	Area (m²)									
0.000	10.0	0.700	10.0	0.701	0.0									
©1982-2020 Innovyze														

