

Summary for Input Data



Property Reference	Plot 01	Issued on Date	22/01/2024
Assessment Reference	2B3P - Bungalow	Prop Type Ref	Benchill Road
Property			

SAP Rating	92 A	DER	0.07	TER	9.86
Environmental	100 A	% DER < TER			99.29
CO ₂ Emissions (t/year)	0.01	DFEE	40.54	TFEE	40.86
Compliance Check	See BREL	% DFEE < TFEE			0.77
% DPER < TPER	54.00	DPER	24.29	TPER	52.82

Assessor Details	Mr. Steven Johnson	Assessor ID	Z708-0001
Client			

SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northwest	
Property Tenture	1	
Transaction Type	6	
Terrain Type	Urban	
1.0 Property Type	Bungalow, Detached	
Which Floor	0	
2.0 Number of Storeys	1	
3.0 Date Built	2023	
3.0 Property Age Band	L	
4.0 Sheltered Sides	0	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	N/A	kJ/m²K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	No	
Smart gas meter fitted	No	

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Basement:	0.00 m	0.00 m ²	0.00 m
Ground floor:	34.25 m	72.16 m ²	2.33 m
1st Storey:	0.00 m	0.00 m ²	0.00 m
2nd Storey:	0.00 m	0.00 m ²	0.00 m
3rd Storey:	0.00 m	0.00 m ²	0.00 m
4th Storey:	0.00 m	0.00 m ²	0.00 m
5th Storey:	0.00 m	0.00 m ²	0.00 m
6th Storey:	0.00 m	0.00 m ²	0.00 m
7th Storey:	0.00 m	0.00 m ²	0.00 m

8.0 Living Area	29.00	m ²
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Res	Shelter	Openings	Area Calculation Type
	External Wall 1	Timber Frame	Other	0.16	0.00	79.80	67.36	0.00	None	12.44	Calculate Wall Area

9.2 Internal Walls	Description	Construction	Kappa (kJ/m ² K)	Area (m ²)
	Internal Wall 1	Other	75.00	30.00

10.0 External Roofs	Description	Type	Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Code	Shelter Factor	Calculation Type	Openings
	External Roof 1	External Plane Roof	Plasterboard, insulated at ceiling level	0.09	9.00	72.16	72.16	None	0.00	Calculate Wall Area	0.00

11.0 Heat Loss Floors	Description	Type	Storey Index	Construction	U-Value (W/m ² K)	Shelter Code	Shelter Factor	Kappa (kJ/m ² K)	Area (m ²)
	Heatloss Floor 1	Ground Floor - Solid	Lowest occupied	Other	0.11	None	0.00	0.00	72.16

Summary for Input Data

12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m²K)
Window	BFRC, BSI or CERTASS data	Window	Double glazed		Air Filled	0.40	Wood	1.00	1.40
Door	Manufacturer	Solid Door			Air Filled	0.00	Wood	0.70	1.00

13.0 Openings

Name	Opening Type	Location	Orientation	Area (m²)	Pitch
Opening	Window	External Wall 1	North West	2.26	0
Opening	Window	External Wall 1	South East	5.99	0
Opening	Window	External Wall 1	South West	0.63	0
Opening	Window	External Wall 1	North East	1.42	0
Opening	Door	External Wall 1	North West	2.14	0

14.0 Conservatory

15.0 Draught Proofing

 %

16.0 Draught Lobby

17.0 Thermal Bridging

17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)		8.62	0.00	0.00	No
E3 Sill		5.70	0.00	0.00	No
E4 Jamb		19.30	0.00	0.00	No
E5 Ground floor (normal)		34.25	0.00	0.00	No
E10 Eaves (insulation at ceiling level)		17.75	0.00	0.00	No
E12 Gable (insulation at ceiling level)		16.50	0.00	0.00	No
E16 Corner (normal)		9.34	0.00	0.00	No

Y-value W/m²K

Description

18.0 Pressure Testing

Designed AP₅₀ m²/(h.m²) @ 50 Pa

Property Tested?

Test Method

19.0 Mechanical Ventilation

Mechanical Ventilation

Mechanical Ventilation System Present

Approved Installation

Mechanical Ventilation data Type

Type

MV Reference Number

Configuration

Manufacturer SFP

Duct Type

MVHR Efficiency

Wet Rooms

SFP from Installer Commissioning Certificate

MVHR System Location

Duct Installation Specification

20.0 Fans, Open Fireplaces, Flues

21.0 Fixed Cooling System

22.0 Lighting

No Fixed Lighting

Name	Efficacy	Power	Capacity	Count
Lighting 1	75.00	4	300	10

24.0 Main Heating 1

Percentage of Heat %

Summary for Input Data

Database Ref. No.	106465
Fuel Type	Electricity
SAP Code	0
In Winter	232.53
In Summer	170.70
Model Name	EDLA04EV3
Manufacturer	Daikin Europe NV
System Type	Heat Pump
Controls SAP Code	2210
Delayed Start Stat	No
HETAS approved System	No
Oil Pump Inside	No
FI Case	0.00
Flue Type	None or Unknown
Fan Assisted Flue	No
Is MHS Pumped	Pump in unheated space
Heating Pump Age	2013 or later
Heat Emitter	Underfloor
Underfloor Heating	Yes - Pipes in thin screed
Flow Temperature	Enter value
Flow Temperature Value	55.00
Boiler Interlock	No

25.0 Main Heating 2	None
----------------------------	------

26.0 Heat Networks	None
---------------------------	------

28.0 Water Heating	
Water Heating	Main Heating 1
SAP Code	901
Flue Gas Heat Recovery System	No
Waste Water Heat Recovery Instantaneous System 1	No
Waste Water Heat Recovery Instantaneous System 2	No
Waste Water Heat Recovery Storage System	No
Solar Panel	No
Water use <= 125 litres/person/day	Yes
Summer Immersion	No
Cold Water Source	From mains
Bath Count	1
Supplementary Immersion	No
Immersion Only Heating Hot Water	No

28.1 Showers					
Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To
Shower	Combi boiler or unvented hot water system	11.00		Yes	Instantaneous System 1

28.3 Waste Water Heat Recovery System	
--	--

29.0 Hot Water Cylinder	Hot Water Cylinder
Cylinder Stat	Yes
Cylinder In Heated Space	Yes
Independent Time Control	Yes
Insulation Type	Measured Loss

Summary for Input Data

Cylinder Volume	<input type="text" value="179.00"/>	L
Loss	<input type="text" value="1.40"/>	kWh/day
Pipes insulation	<input type="text" value="Fully insulated primary pipework"/>	
In Airing Cupboard	<input type="text" value="No"/>	

31.0 Thermal Store

32.0 Photovoltaic Unit

Export Capable Meter?	<input type="text" value="Yes"/>
Connected To Dwelling	<input type="text" value="Yes"/>
Diverter	<input type="text" value="No"/>
Battery Capacity [kWh]	<input type="text" value="0.00"/>

PV Cells kWp	Orientation	Elevation	Overshading	FGHRS	MCS Certificate	Overshading Factor	MCS Certificate Reference	Panel Manufacturer
4.20	South West	30°	None Or Little	No	No	1.00		

34.0 Small-scale Hydro

	<input type="text" value="None"/>	
Electricity Generated	<input type="text" value="0.00"/>	
Apportioned	<input type="text" value="0.00"/>	kWh/Year
Connected to dwelling's electricity meter	<input type="text" value="Yes"/>	
Electricity Generation	<input type="text" value="Annual"/>	

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Recommendations

Lower cost measures

None

Further measures to achieve even higher standards

None