QUAY

Features:

- Column mounting 60mm spigot entry with vertical or horizontal orientation
- IP66 (dust tight & strong water jet proof)
- IK09 (10 joules) shock resistance
- Available in 4000K (cool white)
- CRI >70
- Average 100,000 hrs LED life – L90 B10 @ 25°
- Suitable for 4-8 metre columns
- Asymmetrical narrow or asymmetrical wide optical reflector
- Excellent thermal management with heat dissipating housing
- Tiltable from -15° to +15°
- 1–10V (analogue) dimming, DALI (digital) dimming, 5 step double level dimming, integrated thermal protection and surge protection as standard

Options (on special request):

- 3000K (warm white) and 5000K (daylight) LED colour temperatures available
- Alternative RAL finishes (minimum order quantities may apply)

Material:

- Body: die-cast aluminium
- Lens: tempered safety glass

Colour:

02 Black

Beam Angles:

Technical





Photometrics



Asymmetrical Narrow



Asymmetrical Wide

Quay						Ordering Code	
Wattage	Colour Temperature	Delivered Lumens	Luminous Efficacy	Weight (Kg)	Windage (m^2)	Asymmetrical Narrow	Asymmetrical Wide
32W LED	4000K	4915lm	154lm/W	7.5	0.07	75-152-071-402	75-152-072-402
64W LED	4000K	9970lm	156lm/W	7.5	0.07	75-154-071-402	75-154-072-402
96W LED	4000K	15025lm	157lm/W	7.5	0.07	75-156-071-402	75-156-072-402