



energycounsel
engineering sustainable buildings

Energy Statement

Ref: Z58150

**Proposed 25No. New Build
Dwellings**

at

**Land Opposite 83-87 Vine Street,
Gorton,
Manchester
M18 8SR**

for

Kirkland Developments Ltd



FS 560187

Energy Counsel
Viridor House
No.3 Bolholt Terrace
Bury/Gtr Manchester

BL8 1PP
Tel: +44 (0)161-762 1055
Fax: +44 (0)161-761 1094

Matthew.Gibson@energycounsel.co.uk
www.energycounsel.co.uk

Document Status – Final

Ref: Z58150-REV1			Date
Produced by:	<i>Gideon Griffiths</i>	Gideon Griffiths OCDEA NDEA Air Tester	5 th May 2023
Checked by:	<i>Matthew Adams</i>	Matthew Adams BEng(Hons) LCEA NDEA LCC	5 th May 2023
Approved by:	<i>Matthew Gibson</i>	Matthew Gibson CEng CEnv BEng(Hons) MIET MEI SocEnv OCDEA Air Tester	9 th May 2023

Disclaimer

This report has been prepared by Energy Counsel with all reasonable skill, care, and diligence within the terms of the Contract with the client, incorporating our Standard Terms and Conditions of Business and taking into account the resources devoted to it by agreement with the Client.

We disclaim any responsibility to the client and others in respect of any matters outside the scope of the above.

This report is confidential to the client, and we accept no responsibility of whatsoever nature to third parties to whom this report, or any part thereof, is made known. Any such party relies on the report at their own discretion and risk.

Contents

1. Introduction	7
1.1. Location	8
2. Policy Drivers for Energy Efficiency and Renewable Energy	12
2.1. National Policy	12
2.2. Local Policy	13
3. Methodology	18
4. Baseline Energy Assessment	20
4.1. Predicted Baseline Energy Requirements	21
5. Passive Design and Energy Efficiency	21
5.1. Passive Design Measures	21
5.2. Energy Efficient Systems	21
6. District & Communal Heating Networks	23
6.1. Decentralised Heating Networks	23
6.2. New Heating Networks – Options	24
7. Renewable Energy Technologies	25
7.1. Photovoltaics (PV)	25
7.2. Solar Thermal HW Panels	26
7.3. Ground Source Heat Pump (GSHP)	27
7.4. Air Source Heat Pump/Exhaust Air Heat Pump	28
7.5. Micro Wind Power	28
7.6. Biomass	29
8. Energy Assessment of Proposed Scheme	31
9. Conclusion	32
9.1. Low/ Zero Carbon Technologies (LZT) Chosen	32
9.2. Low/ Zero Carbon Technologies (LZT) Discounted	33
9.3. Summary Headlines	34
10. Appendices	35
10.1. LZT Feasibility Table	35
10.2. Specification for Energy Assessments (ADL1 2021 – SAP 10)	36
10.3. Index of Tables and Figures	39

Executive Summary

This Energy Statement (ES) has been developed to support the proposed development of 25No. residential dwellings at Vine Street, Gorton, Manchester. As discussed with MCC planners, the original Energy Statement submitted for Outline planning is now out of date as it is based on the old Building Regulations Part L 2013. The design team will request that Planning condition 30 is rephrased to accept this updated/ revised energy statement. This ES includes the same information as before, including the carbon reduction figures, aimed to achieve and how the Councils energy targets are exceeded when applying new Building Regs Part L 2021. This ES will be submitted with the reserved matters application.

This Energy Statement reflects predictive performance of the dwellings under new building regulation part L 2021 and replaces the original Energy Statement submitted, based on the older building regulation part L 2013. Planning condition 30 states:

“30. The development hereby approved shall be carried out in accordance with the Energy and Sustainability Statement dated 1st December 2020 received by the City Council, as Local Planning Authority, on the 11th December 2020. A post construction review certificate/statement shall be submitted for approval, within a timescale that has been previously agreed in writing, to the City Council as Local Planning Authority.”

The statement will evaluate the technical and economic feasibility of using both passive and low and zero carbon technologies and will assess the practical levels of CO₂ reduction possible for this development to comply with the following planning requirements:

- National Planning Policy Framework (2021)
- Manchester City Council’s Core Strategy 2012 - 2027 (2012) policies EN4 - EN7
- Principles of The Guide to Development in Manchester SPD

The following low and zero carbon technologies have been evaluated:

- | | |
|--|-------------------------------|
| • Biomass | • Geothermal |
| • Wind | • Combined Heat & Power (CHP) |
| • Biogas | • Solar Hot Water |
| • Air Source Heat Pumps & Exhaust Air Heat Pumps | • Solar Photovoltaic |


The approach for the Vine Street residential development is to embed sustainability into the heart of the development through a range of design measures based on the 'Be Lean, Be Clean, Be Green' design hierarchy. Measures will include:

1. Enhanced building fabric to meet Building Regulations ADL1 2021 (ratified 15/06/2022)
2. Enhanced air tightness and thermal bridging
3. Efficient extract ventilation system
4. Heating and hot water to the dwellings will be provided by highly efficient air to water heat pumps
5. Efficient lighting strategy primarily using LED type fittings

For the purpose of the assessment, we have evaluated a selection of dwelling types in SAP 10 Standard Assessment Procedure) to provide an accurate estimate of predicted energy/ CO2 emissions. We have completed SAP calculations based on a representative dwelling type to provide an estimation of the total energy/emissions on site.

Summary

The development has been provided with energy savings through the use of passive improvement measures such as improved energy efficiency. This passive approach to compliance will complement the integrated approach to the sustainable energy objectives of the national and local policies. The use of heat pumps for hot water in the dwellings achieves the necessary levels of carbon reduction.



The principles of a Be Lean, Be Clean, Be Green philosophy have been applied, resulting in a site wide average of **62%** carbon emissions improvement and a **24%** primary energy improvement over Building Regulations Part L1 2021, as indicated in Table 1. A full design specification that confirms inputs used within the SAP calculations is provided within the appendices of this report.

Table 1 - Proposed development CO₂ emissions against Building Regulations Part L1 2021

	Total CO ₂ Emissions (kgCO ₂ /yr)	Total Primary Energy (kWh/yr)
Target Dwelling Performance	24,624	7,751
Proposed Dwelling Performance	9,190	5,848
Total Reduction	15,434	1,903
Percentage Improvement (above ADL1 2021)	62.68%	24.55%

A fabric-first approach to meeting Manchester City Core Strategy energy policy has been undertaken for the Vine Street residential development, defined within the 'Be Lean, Be Clean, Be Green' energy hierarchy. The proposed design provides compliance with Building Regulations ADL1 2021, and with the application of heat pumps for heating and hot water ensures reductions which exceed Manchester City Council's Core Strategy.

1. Introduction

The proposed development consists of 25No. residential dwellings located at Vine Street, Gorton, Manchester. The development is required to achieve compliance under Building Regulations Approved Document Part L1 (2021) and planning condition 30.

Supporting information is provided within this report for the proposed energy strategy to be considered on site in accordance with the following planning policies:

- Manchester City Council's Core Strategy 2012 - 2027 (2012) policies EN4 - EN7
- Principles of The Guide to Development in Manchester SPD
- National Planning Policy Framework (2021)

Throughout this report, passive design techniques, energy efficient equipment and appropriate low carbon technologies will be appraised in line with the 'Be Lean, Be Clean, Be Green' philosophy of relevant planning documents and the Energy Hierarchy.

An assessment of CO₂ emissions will be made based on the calculation methodology dictated by the Standard Assessment Procedure (SAP) and in line with the requirements of Manchester City Council's planning policy.

1.1. Location

The proposed development Vine Steet, Gorton, in Manchester is highlighted by the red line boundary shown in Figure 1.



Figure 1 - Location of proposed Vine Street residential development

The site will be accessed off Vine Street, Manchester. Existing residential development exists on 2 sides of the development with a small industrial unit to the east and a railway line to the North.



Figure 2 – Site plan for the proposed Vine Street residential development

The proposed development consists of 25No. dwellings, as indicated in Figure 2 above. Plot types and numbers are defined across the site as shown below:

Dwelling Type	Description	Number of Units
2b3p House	2 Bed 3 Person House	15
3b4p House	3 Bed 4 Person House	9
4b5p House	4 Bed 5 Person House	1
		25

Floor Plans




Figure 3 House Types A1, A2, A3 & B1






Figure 4 – House Types B2, B3, B4 & B5



First floor



First floor




Ground floor
2b3p
72 sq m
PLOT 25
B6




Ground floor
3b4p
87.5 sq m
PLOT 9
PLOT 14
C

Figure 5 – House Types B6 & C




First floor



First floor



Ground floor
4b5p
101 sq m
PLOT 15
D



Ground floor
3b4p
88 sq m
PLOT 16
E1

88 sq m
PLOT 17
PLOT 19
E2 **E2(H)**

Figure 6 – House Types D, E1 & E2

2. Policy Drivers for Energy Efficiency and Renewable Energy

This section presents a range of planning policy that is applicable to the Vine Street residential development, at both a national and a local level.

2.1. National Policy

The National Planning Policy Framework was published in July 2021 and sets out the government's planning policies for England and they should be applied. Table 2 sets out the relevant energy standards for new developments and provides an indication of the design response to be provided.

Table 2 – Key National Planning Policy Requirements and Design Responses

Section	Policy Requirements	Design Response
14. Meeting the challenge of climate change, flooding and coastal change	<p>The planning system should support the transition to a low carbon future in a changing climate, taking full account of flood risk and coastal change.</p> <p>It should help to:</p> <p>Shape places in ways that contribute to radical reductions in greenhouse gas emissions, minimise vulnerability and improve resilience; encourage the reuse of existing resources, including the conversion of existing buildings; and support renewable and low carbon energy and associated infrastructure.</p>	<p>This development will follow the principles set out in Manchester City Council's Core Strategy 2012 – 2027 (2012), using a 'Be Lean, Be Clean, Be Green' approach in reducing operational carbon emissions.</p> <p>An overview of current decentralised energy schemes in Manchester and an assessment on the potential for future schemes in relation to this development is provided in Section 6 of this report.</p> <p>This sustainability and renewable energy statement appraises site specific information to determine the most appropriate approach to minimise energy consumption.</p>

2.2. Local Policy

The adopted Manchester Core Strategy 2012-2027 (2012) and the Supplementary Planning Document and Planning Guidance (2007) provide a set of guidelines for new development within Manchester. All relevant energy policy within these documents is provided within this section together with a design response.

Table 3 – Key Local Planning Policy Requirements and Design Responses

Manchester Core Strategy 2012 – 2027 (2012)		
Section	Policy Requirements	Design Response
EN 4 - Reducing CO₂ Emissions by Enabling Low and Zero Carbon Development	<p>All development must follow the principle of the Energy Hierarchy, being designed:</p> <ul style="list-style-type: none"> • to reduce the need for energy through design features that provide passive heating, natural lighting and cooling • to reduce the need for energy through energy efficient features such as improved insulation and glazing • to meet residual energy requirements through the use of low or zero carbon energy generating technologies <p>Wherever possible new development and retrofit projects, including energy generation plant, must be located and designed in a manner that allows advantage to be taken of opportunities for low and zero carbon energy supplies.</p> <p>Where possible new development and retrofit projects will be used as a mechanism to help improve energy efficiency and provide low and zero carbon energy supplies to existing buildings.</p> <p>Where appropriate new development and retrofit projects will be required to connect to and/or make contributions to low or zero carbon energy schemes and/or to incorporate provision to enable future connection to any existing / potential decentralised energy schemes. The use of building materials with low embodied carbon in new development and refurbishment schemes.</p>	<p>The proposed Vine Street development will follow the principles of the Energy Hierarchy by adopting a passive fabric-first approach to design rather than adopting the use of renewable technologies.</p> <p>A full energy strategy is provided in Section 8 of this report, following an appraisal of a range of site-specific measures in line with the 'Be Lean, Be Clean, Be Green' approach.</p> <p>A review of district heating opportunities is provided in Section Error! Reference source not found. of this report, in line with current local development.</p>

<p>Policy EN 5 – Strategic Areas for low and zero carbon</p>	<p>Within Manchester it is considered that the following strategic areas, indicated on the key diagram, will have a major role to play in achieving an increase in the level of decentralised, low and zero carbon energy supplies available:</p> <ul style="list-style-type: none"> • The Regional Centre, which also includes the Oxford Road Corridor and Eastlands • District Centres and associated major development sites • Airport Strategic Site • Strategic housing location • Strategic employment locations <p>Within these areas new development, regeneration and retrofit projects, will be expected to take place in the context of more detailed proposals for decentralised low and zero carbon energy infrastructure in the form of energy proposals plans. The Council will work with all relevant stakeholders, which may include developers, landowners, residents, community groups, private sector partners, utilities companies, neighbouring authorities and other public sector bodies, as appropriate, to bring forward such plans.</p> <p>Where investment or development is being undertaken into or adjacent to a public building/asset or district heating network, full consideration shall be given to the potential role that these can have in providing an anchor load within a decentralised energy network or in creating opportunities for CO2 reduction funded by contributions.</p>	<p>The proposed Vine Street development does not fall within a Strategic Area for decentralised development, as defined within the Manchester City Council Core Strategy 2012 – 2027.</p> <p>The proximity of the site to current decentralised energy networks is illustrated within Section 6.1 of this report.</p>
<p>Policy EN 6 - Target Framework for CO2 reductions from low or zero carbon energy supplies</p>	<p>Developments smaller than 10 units but involving the erection of a building or substantial improvement to an existing building will be expected to meet the minimum targets for the defined areas below, where viable.</p> <p>The target framework relates to three broad development locations and their potential for low and zero carbon, decentralised energy. The areas are defined as follows:</p> <ul style="list-style-type: none"> • Target 1 Network development areas: Locations where the proximity of new and existing buildings, the mix of uses and density of development provide the right conditions to support district heating (and cooling). 	<p>The proposed development consists of 25No. units and is therefore within the threshold of a major development.</p> <p>The site does not sit within an area defined for development of low and zero carbon, decentralised energy. An overview of the site</p>

	<ul style="list-style-type: none">Target 2 Electricity intense areas: Locations where the predominant building type has an all-electric fit-out such as retail units and leisure complexesTarget 3 Micro-generation areas: Locations where lower densities and a fragmented mix of uses tend to mean that only building scale solutions are practical. <table><tr><th>Target</th><th>% Minimum Requirement</th></tr><tr><td>Target 1: Network development area</td><td>CHP/district heating anchor or connection or where not feasible a 15% increase on Part L 2010.</td></tr><tr><td>Target 2: Electricity intense buildings</td><td>+15% increase on Part L 2010</td></tr><tr><td>Target 3: Micro generation area</td><td>+15% increase on Part L 2010</td></tr></table>	Target	% Minimum Requirement	Target 1: Network development area	CHP/district heating anchor or connection or where not feasible a 15% increase on Part L 2010.	Target 2: Electricity intense buildings	+15% increase on Part L 2010	Target 3: Micro generation area	+15% increase on Part L 2010	<p>in relation to current decentralised networks in the region is provided in Section 6.1. A fabric first approach is proposed for this development.</p> <p>Renewable technologies have not been specified for this development due to financial viability and ongoing maintenance issues. A+15% increase on Part L 2010 has been achieved within the design.</p>
Target	% Minimum Requirement									
Target 1: Network development area	CHP/district heating anchor or connection or where not feasible a 15% increase on Part L 2010.									
Target 2: Electricity intense buildings	+15% increase on Part L 2010									
Target 3: Micro generation area	+15% increase on Part L 2010									
Policy EN 7 – Energy Infrastructure opportunities	<p>There will be a general presumption in favour of low and zero carbon decentralised energy schemes, subject to the following considerations:</p> <p>That any new generating plant capable of producing heat and cooling as well as electricity should be located in a way that facilitates future connection to a local distributed energy system.</p> <ul style="list-style-type: none">That any energy centre, including generating plant, standby/boiler plant and substations, shall be located and designed to a high quality so as to integrate with and contribute to the townscape.Biofuels should be obtained from sustainable sources and processes and in a way that minimises transport impacts, following a sequential approach in order to minimise CO2 emissions – firstly prioritising local and regional sources, followed by national, European and international.Consideration should be given to biofuel delivery by rail and waterways where possible. Where large-scale fuel or feedstock delivery is required by road the energy centre must be located in or adjacent to light industrial, industrial or leisure uses with any impact on local residential amenity minimised.	<p>An overview of the site in relation to current decentralised networks in the region is provided in Section 6.1.</p> <p>Due to the relatively small scale of the development, the development of an energy centre would not be a feasible design solution.</p> <p>A fabric first approach to the development is a much preferred method with the use of highly efficient heat pumps to provide hot water to the dwellings.</p>								

	<ul style="list-style-type: none"> The cumulative impact of energy schemes will be taken into account when considering applications, to include modelled impacts on air quality and landscape character, with reference to Policy EN16. Flood risk, through the Manchester-Salford-Trafford Strategic Flood Risk Assessment. <p>In determining proposals for development, consideration will be given to the need to safeguard strategic energy sites and network routes, both proposed or existing, where these have been identified as having strategic significance for the delivery of low or zero carbon energy infrastructure or, would be required in order to achieve the successful regeneration of an area in line with targets for reducing carbon emissions.</p>	
Supplementary Planning Document and Planning Guidance (2007)		
Section	Policy Requirements	Design Response
4.5 – Energy Efficiency	<p>Part 1 Policy E1.5 encourages high standards of energy efficiency in new development. In the Environmental Standards Statement, developers should show how they have considered the steps necessary to reduce energy demand at the earliest stages of design. Developers should aim to reduce CO2 emissions by at least 25% more than the requirements of the current Building Regulations, which at present are Building Regulations: Approved Document L (2006) – ‘Conservation of Fuel and Power.’ The following design principles will assist developers in achieving energy efficiency targets:</p> <ul style="list-style-type: none"> Minimise reliance on energy-using equipment for heating, cooling, lighting and natural ventilation Position trees and soft landscaping on and around the development and within buildings to provide natural shading, insulation and air conditioning Integrate energy efficient micro-generation and community heating schemes, such as combined heat and power (CHP) Site layout and building design principles should maximise the capture and use of daylight and passive solar energy, whilst avoiding excessive solar gain in summer <p>Specify energy and water efficient appliances and systems</p>	<p>In line with the principles of the Be Lean, Be Clean, Be Green design philosophy, the Vine Street development seeks to provide a sufficient design solution that provides compliance with Building Regulations Part L1A. An early-stage overview of these calculations is provided in Section 8.</p>

<p>4.6 – Renewable Energy</p>	<p>To reduce energy demand and the harmful impact of using energy from non-renewables, in line with UDP Part 1 Policy E1.5, developers should aim for at least 20% of final site energy demand to be met by on-site renewable energy technologies. Renewable energy targets can be achieved more readily by undertaking the measures suggested above reducing the total energy demand of the building. It is possible to produce developments that use 50% and even 100% energy from renewable sources.</p> <p>To achieve this, developers should:</p> <ul style="list-style-type: none"> • Assess opportunities for integrating small and large scale renewable energy generation systems to improve the energy security of occupants and the neighbourhood, including siting of energy generation businesses on-site and export of surplus energy • Use a mix of technologies to help generation patterns match demand • Investigate energy generation opportunities before designing building envelopes or fixing their location, to optimise utilisation of wind, solar and geothermal resources • Consider final energy demand rather than building energy consumption in the selection and sizing of generation equipment • Explore opportunities to tackle waste and energy issues collectively through use of anaerobic digesters linked to CHPs (Combined Heat and Power devices) <p>Consider private wire networks as an alternative to grid connection and availability charges on larger developments.</p>	<p>A full appraisal of low and zero carbon technologies is provided in Section 7 of this report.</p> <p>Achieving compliance with Building Regulations Part L1A will be demonstrated through a passive fabric-first approach.</p> <p>This ensures that the highest standards of fabric efficiency and energy efficiency are achieved, rather than applying renewable technologies to the development.</p>
--------------------------------------	---	---

3. Methodology

The first step of the full energy strategy assessment has been to undertake a baseline energy assessment. The baseline energy assessment consists of calculating the total CO₂ emissions of the development to meet Building Regulations and then compare the proposed improvement measures against this baseline. Building Regulations Part L1 2021 (SAP) applies to each of the 825No. dwellings and provides carbon emissions from regulated energy.

The building can then be benchmarked/ thermally modelled using the energy hierarchy:

<p>1. Be Lean</p> <p><i>A reduction in energy use as a result of passive design and energy efficiency</i></p>
<p>Thermal performance of envelope (U values) Glazing design Airtight construction Efficient mechanical ventilation Variable speed fans and pumps Efficient lighting</p>
<p>2. Be Clean</p> <p><i>A focus on supplying energy to the development through efficient means</i></p>
<p>Connect to low carbon heat networks Develop site wide heat network from single energy centre On site district heating network Provide energy efficient individual heating</p>
<p>3. Be Green</p> <p><i>The installation of renewable technologies to meet energy demand where possible</i></p>
<p>Consider the feasibility of renewable energy technologies Assess the integration of renewable technologies based on the above measures</p>

The development must be provided with energy savings through the use of thermal improvements to fabric (a 'fabric first' approach), followed by other clean energy solutions (energy efficiency improvements, district heating, etc.) and finally the use of renewable energy technologies, where

practical. This hierarchy complements the integrated approach to the sustainable energy objectives of Manchester City Council's Planning Policies.

The planning policies require a full review of the technical and economic feasibility of the following renewable technologies:

- Biomass heating
- Biomass combined heat and power
- Solar hot water
- Solar photovoltaic
- Ground source heat pumps
- Air source heat pumps / exhaust air heat pumps
- Wind power

To achieve the targets set the development must achieve a balance between fabric, heating and control, ventilation and air leakage improvements, the amount of zero or low carbon technology installed and the capital, life cycle and running costs, maintenance, and operation, etc.

Feasible renewable energy technologies have been considered during the assessment to ensure the most suitable renewable energy is chosen for the demands of this scheme. The pros and cons of each technology with respect to this site are considered as part of this statement.

4. Baseline Energy Assessment

Energy Counsel have based the analysis on current Building Regulations ADL1 2021 (SAP 10), taking into account solutions that must not only be energy efficient but also practical, reliable and user friendly. Energy Counsel have carried out preliminary SAP 10 calculations for the dwellings. Under Building Regulations Part L1 2021, dwellings must comply with all three metrics set by the notional building shown below.

- Dwelling Emissions Rate (DER) must be lower than or equal to the Target Emissions Rate (TER)
- Dwelling Primary Energy Rate (DPER) must be lower than or equal to the Target Primary Energy Rate (TPER)
- Dwelling Fabric Energy Efficiency Rate (DFEE) must be lower or equal to the Target Fabric Energy Efficiency Rate (TFEE)

SAP 10 is the Governments Standard Assessment Procedure (SAP) for calculating the energy aspects of a dwelling. SAP is a measure of fuel costs for heating, hot water and lighting for a dwelling. SAP 10 can also be used to ascertain the energy requirements of a development.

To assess the baseline carbon emissions, we must make an estimation of the energy demands through Building Regulations in order to set a target upon which the actual development can be compared.

4.1. Predicted Baseline Energy Requirements

The predicted baseline CO₂ emission and primary energy demands for the development:

Table 4 - Baseline dwelling carbon emissions and primary energy

Our Ref	Dwelling Type	No. of Type	Floor Area m ²	TER (Kg CO ₂ / yr/m ²)	TPER (kWh/yr/m ²)	Total Target Carbon Emissions (Kg CO ₂ /yr)	Total Target Primary Energy (kWh/yr)
Z58150	A2	2	88	10.44	54.38	1,841	455
Z58151	A3	1	88	11.99	62.64	1,057	285
Z58152	B2	14	72	13.18	69.04	13,276	4,688
Z58153	B6	1	72	13.34	69.92	960	341
Z58154	C	2	87	12.42	64.97	2,167	594
Z58155	D	1	101	11.90	62.22	1,199	273
Z58156	E1	1	87	11.90	62.15	1,038	283
Z58157	E2	3	87	11.79	61.60	3,086	833
Total		25				24,624	7,751

The baseline carbon emissions rate for the development is **24,624 KgCO₂/yr** and the baseline primary energy rate is **7,751 kWh/yr**.

5. Passive Design and Energy Efficiency

The approach of the development is to embed sustainability into the heart of the design from the outset of the project design process. The design will be developed with sustainable solutions, taking into account the relevant policies and strategies of Manchester City Council. The development will seek to consider all aspects and principles of sustainable development, taking into account environmental, social and economic impacts.

5.1. Passive Design Measures

The philosophy for the site is to achieve as much of the necessary reduction in carbon emissions through the use of passive design techniques and energy efficient measures as possible, before resorting to the use of LZCs. This ensures that the highest standards of building fabric and energy efficiency are achieved, rather than offsetting a poorer performance with LZC contributions.

This will be undertaken through a fabric first energy efficient design approach with high levels of thermal efficiency and a reduction in energy demand through efficient lighting design.

5.2. Energy Efficient Systems

Options have been reviewed for improving the energy efficiency of the development by installing an efficient hot water and heating system. The dwellings will benefit from high efficiency air source heat pump to deliver heating and hot water. The unit used will meet the planning requirements relating to noise levels.

Dwellings will also be provided with a metering scheme based on their electricity usage.

The AEC noise impact assessment indicates which plots are subject to higher background noise levels predominantly from the existing train line. A low energy high efficiency system 4 mechanical ventilation with heat recovery system (MVHR) will serve all dwellings excl plots 4-9. The MVHR will have low specific fan power (SPF) and high heat recovery (90%), in line with the requirements of Building Regulations Part F (2021). The vent system will be capable of summer bypass and will assist with the requirements of Part O – overheating. Ventilation will be provided throughout the rest of the dwelling by openable windows most spaces. Plots 4-9 are shielded from the train line and therefore the ventilation system can utilise system 3 mechanical ventilation for these plots.

6. District & Communal Heating Networks

This section outlines how consideration of energy supplied efficiently from a district heating network can be provided to the dwellings in line with the energy hierarchy.

6.1. Decentralised Heating Networks

The energy policy reaffirms the view that energy generated by centralised power stations and transmitted through the national grid is highly inefficient and wasteful.

One of priorities for reducing CO₂ emissions is to reduce the reliance on centralised power stations. This means increasing the use of local, low-carbon energy supplies through de-centralised energy systems.

Decentralised plant generally means any heating and hot water and/or electricity generation provided on a district wide (DHN) or site wide (CHN) basis. DHN and CHN can typically include combined heat and power equipment (CHP). CHP is an engine which, when running, generates electricity and heats water which can then be distributed around a development.

A number of heat network opportunities across the region are at various stages of development. Benefits of district heating networks can include:

- Provision of low carbon / lower cost heat to domestic and commercial customers
- Diversification of the energy mix
- Reductions in region-wide carbon emissions
- Targeting and reduction of fuel poverty
- Potential long-term revenue streams for local authorities
- Alignment with regeneration programmes
- Driving the growth of the low carbon services sector

There are currently no existing district heating networks within proximity to the site. The nearest district heating network is located at Manchester Grove Village Housing just under 4 miles West of the site.

6.2. New Heating Networks – Options

Consideration has been given to adopting a centralised or decentralised energy strategy. A decentralised energy option would typically be an energy centre distributing heat, hot water and electricity to the development from a single source either as a DHN or CHN. This typically would include boilers and a CHP type unit or district heat pumps, sized to provide the whole development. Sometimes multiple energy centres are used to split the loads, provide resilience and to serve different buildings.

The proposed heating and hot water demand from the development of 25No. dwellings is not sufficient to justify a DHN or CHN. The existing site is spatially constrained, there is insufficient space to locate the equipment and associated plant, and connection to a DHN would be cost prohibitive.

7. Renewable Energy Technologies

Energy Counsel have reviewed options for the use of on-site renewable energy/ Low or Zero Carbon Technology (LZT) in line with Manchester City Council policy aspirations.

This renewable energy statement/strategy reviews the technical and economic feasibility of the following technologies –

- Solar Photovoltaic
- Solar Hot Water
- Ground Source Heat Pumps
- Air Source Heat Pumps / Exhaust Air Heat Pumps
- Micro Wind Power
- Biomass

7.1. Photovoltaics (PV)

Photovoltaic panels convert sunlight into electricity to run lights and appliances. Photovoltaic panels use cells to convert light into electricity. A PV cell normally consists of 1 or 2 layers of a semi conducting material such as silicon. When light shines on a cell it generates energy causing electricity to flow, the higher the light intensity is, the more electricity flows.

The amount of energy PV cells generate is referred to as Kilowatt Peak (KWp). PV arrays now come in a variety of shapes and colours, ranging from grey 'solar tiles' that look like roof

tiles to panels and transparent cells that you can use on conservatories and glass to provide shading as well as generating electricity. The roof must be strong enough to take the weight of the panels, especially if the panel is placed on top of existing tiles. For flat roofs the panels can be mounted on A-frames to give the optimum angle.

The optimum panel inclination for solar collection is 35°, oriented due south; however panels that are inclined between 35° and 45° and oriented south of west or east are generally suitable. If solar




Figure 7 - Performance of photovoltaic panel orientation

collectors are oriented away from due south then a larger surface area will be required to generate a set amount of energy. The effect of non-optimal orientation is illustrated by the graph to the right:

The cost to install PV is typically £1,500 – 2,000 per kWp for 'on-roof' panel systems.

Although Photovoltaic panels are viable they have not been proposed on these dwellings. Reasons are set out in Section 9.1.



Figure 8 - Photovoltaic array on a pitched roof

Solar panel heating uses the radiant energy from the sun to heat hot water, most commonly for domestic hot water needs. There are two types of collectors used for solar water heating – flat plate collectors and evacuated tubes collectors. The systems function successfully in all parts of the UK, as they can work in diffuse light conditions. The collector should be mounted on a 10-60 degrees pitch facing south, although other variations can be used, south is the most efficient.

The cost of installing the system is dependent on the distance between the solar collector and the hot water storage and therefore costs vary. The closer the collectors are to the hot water storage; the less pipe work is required.




Figure 9 - The principles of a solar thermal system

Annual maintenance checks are recommended. The solar collectors are connected to a condensing boiler via a HW cylinder with twin coil.

A typical installation in the UK has a panel size of 3-5m² which is used in conjunction with a HW storage tank of 180-300litres, of which a minimum of 90-150 litres must be dedicated to solar hot water storage.

They are a 'simple' and guaranteed technology which will act as a pre-heat for the Hot Water and Heating usage. Payback between capital cost and energy saving can normally be achieved within 12 – 20 years, subject to usage and dwelling type.

The use of solar thermal panels are applied best in conjunction with individual heating systems for each dwelling. The orientation of the development is fine for the utilisation of solar water heating to provide domestic hot water however it will not achieve significant carbon savings. Carbon savings of approximately 4-5% are achievable with this technology. The dwellings are unlikely to require sufficient hot water storage to deem solar thermal a feasible technology for this site. For the reasons aforementioned we do not consider this a viable option for this scheme.

7.3. Ground Source Heat Pump (GSHP)

GSHPs have been developed specifically for the housing market and are now considered to be an established reliable technology. The GSHP would be sized to cater for the heating and domestic hot water requirements. Typically, they are more suited to dwellings as a centralised system would be installed with multiple bore holes to a depth of up to 125 metres depending on the ground conditions. GSHPs use a heat exchanger to extract heat from the earth.

The efficiency of ground source heat pumps is measured by Co-efficient of Performance (CoP), this is




Figure 10 - Principles of a GSHP system

the ratio of units of heat output for each unit of electricity used to drive the compressor and pump for the ground loop. Average CoP is around 2-4 although some systems may produce a greater rate of efficiency. This means that for every unit of electricity used to pump the heat, 2-4 units of heat are produced, making it an efficient way of heating a building. If grid electricity is used for the compressor and pump, then

there is the opportunity to consider a range of energy suppliers to benefit from the lowest running costs, for example by choosing an economy 10 or economy 7 tariff.

Due to the scale of these dwelling units, GSHPs are not considered an appropriate design solution.

7.4. Air Source Heat Pump/Exhaust Air Heat Pump

Air source heat pumps (ASHP) and exhaust air heat pumps (EAHP) work in a similar way to GSHP. Air source heat pumps can be fitted on the external façade or in the roof space. An air source heat pump uses small amounts of electricity to take in large quantities of air and extract heat. The efficiency of ASHP is measured by Coefficient of Performance (CoP); this is the ratio of units of heat output for each unit of electricity used to drive the system. Average CoP is around 2-4 although some systems may produce a greater rate of efficiency.




Figure 11 - Principles of an ASHP system

Exhaust air heat pumps such as the NIBE F370 work in a similar manner to ASHP units but have only indoor units (no outdoor compressors) and in addition they also recover heat from their integral exhaust air ventilation system. These units work well on dwelling blocks and dwellings where mains gas is unavailable or unsuitable for a development. They are expensive in terms of capital cost of the equipment, installation and the enhanced structural requirements.

Hot Water Heat Pumps are considered the most appropriate technology for this scheme and can be utilised to deliver efficient hot water throughout the dwellings. The introduction of this technology ensures that carbon emissions reductions can be provided in line with Manchester City Council's Core Strategy.

7.5. Micro Wind Power

Wind power is one of the cleanest and safest methods of generating electricity. However, wind power is unfeasible due to the fact the development is in an urban area and local wind conditions would not be sufficient to provide enough power. Most small wind turbines generate Direct Current (DC) electricity. Systems that are not connected to the national grid require battery storage and an inverter to convert DC electricity into Alternating Current (AC) which is mains electricity.

There are two types of wind turbine available:

- Roof mounted – These are mounted on the roof of dwellings
- Mast mounted – Which are free standing

Important issues to consider when using wind turbines are:

- Wind speed increases with height so it's best to have the turbine high on a mast or tower.
- The ideal site is a smooth top hill with a flat, clear exposure, free from excessive turbulence and obstructions such as large trees, dwellings or other buildings.
- Small scale wind power is particularly suitable for remote off grid locations where conventional methods of supply are expensive or impractical.
- Where the local annual average wind speed is 6 m/s or more.
- Where there are no significant nearby obstacles such as buildings, trees or hills that are likely to reduce the wind speed or increase turbulence



Figure 12 - Mounted wind turbine

As this development is in an urban area there will be obstacles which reduce wind speed. The average wind speed in this area is 4.7 m/s at a height of 10 metres, which is less than the 6 m/s required. Therefore, micro wind is not a viable technology for this development. Please refer to section 9.1 for more details.

7.6. Biomass

Biomass is a generic name for any fuel produced from organic sources and falls into mainly two categories:

- Woody biomass- forest products, untreated wood products, energy crops and wood pellets
- Non-wood biomass – liquid biofuels (such as biodiesel, bioethanol) or animal waste industrial municipal products and high energy crops such as rape seed, sugar cane and maize.

For domestic properties the fuel used is normally wood pellets, wood chips or wood logs. For larger applications, biomass boilers replace conventional fossil fuel boilers and come with an automated feed by screw drives from hoppers.

Biomass systems require more cleaning than gas or oil boilers and they must be capable of being taken out of service for cooling and cleaning whilst maintaining the building heating supply particularly in

communal heating systems. Centralised gas boilers are therefore still required to support the biomass boiler, which would be the lead boiler. The size of the dedicated plant rooms is substantial. Fuel availability, delivery and storage are also important issues to consider.

Air quality issues are also an important factor when looking to install biomass. The cost of the fuel depends on the type, delivery distances and whether it is obtained as simple waste product or from another organisation. The cost of wood pellets is currently a little more expensive than mains gas, and woodchip is approx. 30% cheaper, however prices are fluctuating rapidly in the bio-fuel market at the present time creating uncertainty over their take up.



Figure 13 - Biomass boiler and hopper

Biomass CHP is still relatively new to the UK market and is more suitable to large developments where energy demand does not require significant modulation. There are technical issues with small scale Biomass CHP and until these can be resolved and proven the take up of these systems in the UK and Europe has been slow.

Overall carbon savings of 40%+ are achievable with biomass technology. Biomass is more suited to a communal heating system; there is insufficient space to accommodate the equipment and fuel storage to facilitate a biomass boiler. Furthermore, there are noise and air quality issues associated with this type of technology. For this reason, biomass is discounted.

8. Energy Assessment of Proposed Scheme

The Vine Street residential development has adopted the principles of the 'Be Lean, Be Clean, Be Green' approach. The most practical and economically feasible solution for the development is a good quality thermally insulated fabric, air-tight envelope, passive improvements and the use of highly efficient heat pumps supported by efficient ventilation system.

Table 5 - Proposed carbon emissions from Vine Street residential development

Our Ref	Dwelling Type	No. of Type	Floor Area m ²	DER (Kg CO ₂ /yr/m ²)	DPER (kWh/yr/m ²)	Total Target Carbon Emissions (Kg CO ₂ /yr)	Total Target Primary Energy (kWh/yr)
Z58150	A2	2	88	4.18	44.43	737	371
Z58151	A3	1	88	4.55	48.20	401	219
Z58152	B2	14	72	4.85	51.48	4,885	3,495
Z58153	B6	1	72	4.87	51.65	350	252
Z58154	C	2	87	4.57	48.34	797	442
Z58155	D	1	101	4.38	46.23	441	202
Z58156	E1	1	87	4.55	48.20	397	219
Z58157	E2	3	87	4.51	47.76	1,180	646
Total		25				9,190	5,848

The carbon emissions are **9,190** kgCO₂/yr. This is a total carbon reduction of **15,434**kgCO₂/yr from the baseline emissions of **24,624** kgCO₂/yr. This equates to a **62%** carbon reduction.

The primary energy rate is **5,848** kWh/yr. This is a primary energy reduction of **1,903**kWh/yr from the baseline primary energy rate of **7,751** kWh/yr. This equates to an **24%** primary energy reduction.

The development proposal achieves carbon efficiency reductions through a highly efficient thermal fabric, energy efficient lighting and ventilation, improved thermal bridging, low air leakage and highly efficient heat pumps for heating and hot water heating to reduce emissions in line with Manchester City Council's Core Strategy.

9. Conclusion

Following the 'Be Lean, Be Clean, Be Green' hierarchy, the proposed design solutions on the Vine Street development are predicted to:

- 1) Reduce the total carbon emissions by 62% compared to new building regulations ADL 2021. New building regs 2021 are a 31% improvement on 2013 regs, which in turn were a 6% improvement on 2010 regs upon which the energy policies are based. Therefore, the overall improvement of this project, based on 2006 standards is 99% betterment (62+31+6). This proposal significantly exceeds the 15% betterment required to meet the energy policy EN6.
- 2) The heat pumps are the proposed renewables/ low carbon technology. Their contribution to the overall energy reduction under the 'be green' energy hierarchy is approx. 50%.
- 3) Reduce the total primary energy by 24% compared to new building regulations ADL 2021. This is a new metric under Part L 2021. The metric confirms that the design significantly exceeds new building regulation part L.

The approach for the Vine Street residential development is to embed sustainability into the heart of the development through a range of design measures based on the 'Be Lean, Be Clean, Be Green' design hierarchy. Measures will include:

- 1) Enhanced building fabric to meet the new Building Regulation ADL1 2021 (15/06/2021)
- 2) Enhanced air tightness and thermal bridging
- 3) Efficient extract ventilation system
- 4) Heating and hot water will be provided by highly efficient heat pumps
- 5) Efficient lighting strategy primarily using LED type fittings

9.1. Low/ Zero Carbon Technologies (LZT) Chosen

- Air Source Heat Pumps (ASHP) are viable and are considered most suitable for this development for the following reasons:
 - a) The ASHP achieves a 50%+ reduction in CO2 emissions based on the SAP 10 ADL1 2021 standards, which confirms a highly efficient, well performing solution.
 - b) Every dwelling benefits directly from the ASHP's performance.
 - c) ASHP is a low carbon technology considered under the 'Be Green' energy hierarchy. Heating and hot water will be provided at seasonal efficiencies greater than 300%.

9.2. Low/ Zero Carbon Technologies (LZT) Discounted

- **Solar Thermal Hot Water** is viable however it is discounted for the following reasons:
 - a) The hot water demand is relatively low on small houses and therefore the solar effectiveness is reduced.
 - b) A heat pump is proposed and therefore the efficiency of hot water delivery is already very good (300-350%).
 - c) CO₂ savings from this technology are not as effective for the cost of the systems.
 - d) Increased maintenance and operating costs. These include annual service, heat transfer fluid changes and filter changes.
 - e) The total cost would equate to approximately £3k per dwelling, with payback in excess of 25+ years.
- **Photovoltaics (PV)** is a viable option however it has been discounted for the following reasons:
 - a) Any PV on the roof will require fire consultant to assess risk with possible fire protection and fire stopping to avoid fire hazard.
 - b) The total cost would equate to approximately £3.5k per apartment for a 1kWp system. Financially the scheme cannot afford a full heat pump solution and PV.
 - c) Increased maintenance and operating costs. These including an annual service and cleaning – refer to access issues below.
 - d) CO₂ savings are beneficial and could be considered as a future retrofit solution to meet zero carbon.
 - e) Access to the roof is difficult, requires RAMS and is higher risk item.
- **Biomass** has been discounted for the following reasons:
 - a) Transportation of the fuel to site has “built in” significant CO₂ emissions.
 - b) Storage and transportation for deliveries would be required.
 - c) It would require a centralised larger plant space for storing fuel, which on this constrained site is not viable.
 - d) It poses problems in terms of air quality issues.
- **Micro-wind** have been discounted for the following reasons:
 - a) Micro turbines do not work on this type of development due to problems with wind turbulence and mounting of the units.
 - b) The wind speeds in the area are not conducive to wind power electricity generation and there would be issues with turbulence, wind shading, noise and air traffic.

- **Ground Source Heat Pumps (GSHP)** are not viable for site due to the following reasons:
 - a) The size of the development is very small for a GSHP system. Costs increase for smaller developments.
 - b) Ground conditions are unknown which is a large risk item.
 - c) Site spatial requirements are limited and unfeasible for vertical bore holes or horizontal slinky type units.
 - d) There is no site space to accommodate an associated communal plant room.
 - e) The total cost would equate to approximately £14k per dwelling, with payback in excess of 25+ years.

An overview of LZT technologies is provided in the appendices of this report.

9.3. Summary Headlines

- A fabric-first approach to meeting Manchester City Core Strategy energy policy has been undertaken for the Vine Street residential development, defined within the 'Be Lean, Be Clean, Be Green' energy hierarchy. The proposed design provides compliance with Building Regulations ADL1 2021, and with the application of heat pumps for heating and hot water ensures reductions which exceed Manchester City Council's Core Strategy.
- The use of high-efficiency heat pumps reduces carbon emissions by 62% and provides a primary energy reduction of 24% when compared to new building regulations Part L 2021. The overall improvement of this project, based on 2006 standards is a 99% CO₂ emission betterment (62+31+6). This proposal significantly exceeds the 15% betterment required to meet the energy policy EN6 and the performance of the previous planning condition 30.

An overall 62% improvement in CO₂ emissions and a 24% improvement in primary energy above the Building Regulations baseline is proposed to support our application and to meet policy requirements.

	Total CO₂ Emissions (kgCO₂/yr)	Total Primary Energy (kWh/yr)
Target Dwelling Performance	24,624	7,751
Proposed Dwelling Performance	9,190	5,848
Total Reduction	15,434	1,903
Percentage Improvement (above ADL1 2021)	62.68%	24.55%

10. Appendices

10.1. LZT Feasibility Table

Technology	Technical Feasibility	Carbon Savings	Estimated Costs	Financial Viability
Solar photovoltaics	A photovoltaic array is not required for the dwellings as carbon emissions reductions in line with BRegs Part L1 2021 are already achieved.	A 1kWp system could save around 213 kg of CO ₂ / year per dwelling	Average cost for such a system is around £1.5K per dwelling.	Current potential income generation is around £120 minimum per annum per dwelling with a fuel cost saving of around £40 / year per dwelling.
Wind	Average wind speeds on the site according to the <u>NOABL</u> Wind Speed Database are 4.4m/s. To be technically feasible a minimum of 6m/s is required, therefore this site is not considered feasible.	N/A	N/A	N/A
Micro Hydro	There is no capa for micro hydro on this site since there are no local water courses available.	N/A	N/A	N/A
District Heating	There are no existing or planned district heating networks to facilitate connection at this stage.	N/A	N/A	N/A
Solar Hot Water	This technology has been discounted as the level of hot water usage in each dwelling does not merit a storage system, which poses space issues.	Around 270 kg of CO ₂ / year per dwelling.	£3-5K per dwelling	Income generation from RHI in a 4-person household would be in the region of £340 / year (per dwelling) with a fuel saving of around £65 / year per dwelling
Heat Pumps	GSHP: Ground conditions on site are unknown, and installation of coils are likely not economically viable for this project. ASHP: Provided to all dwellings for heating and hot water. HWHP: Provided to all dwellings for hot water	GSHP: 2,100 to 3,300 kg CO ₂ / year per dwelling ASHP: 1,700 to 2,700 kg CO ₂ / year per dwelling. HWHP: 1,700 to 2,700 kg CO ₂ / year per dwelling.	GSHP @ £13-20K per dwelling ASHP: £7-11K / dwelling ASHP: £3K / dwelling	GSHP: £2,590 minimum annual RHI income generation per dwelling with fuel saving of £440 / year minimum per dwelling ASHP: RHI removed. Fixed £5000 grant fund per property. HWHP: N/A
Biomass	The small scale of this development would not facilitate the installation of biomass boilers due to the space required for pellet storage.	N/A	N/A	N/A

10.2. Specification for Energy Assessments (ADL1 2021 – SAP 10)

Item	Brief Description	Notes	Confirm
	The following information is required for the design submission (as per requirements of approved doc L1A).	Please note submission is now in two stages. A) Design , B) As installed	
1. Dwelling Type			
1.1	New Building Regulations 2021 applies	The Contractor is responsible for meeting Building Regs 2021 compliance including part L (energy), F (ventilation), O (overheating), G (water consumption), E (sound) and S (Elec Vehicle Charging)	
1.2	Full address and Post code of site to be provided from Royal Mail		
1.3	Electricity is supplied by standard tariff rather than economy 7, 10 or 24.	<i>Assumed Standard tariff</i>	
1.4	It is assumed that the dwellings have a Medium thermal mass parameter.	Construction method to be confirmed by Contractor and Building Regs SAPs to be adjusted accordingly	
2. Floor Construction Details			
2.1	Ground floor is slab on ground or B&B with 150mm PIR insulation, with 75mm screed to achieve the U-value stated opposite.	U-Value = 0.12 W/m ² K P/A ratio dependent λ of PIR = 0.022	
3. Wall Construction Details			
3.1	Main external walls will be insulated to achieve the U-value stated opposite	U-Value = 0.17 W/m ² K To meet Jigsaw Standard	
3.2	Party walls are fully filled, cavity closed and sealed to achieve the U-value opposite	U-Value = 0.0 W/m ² K	
4. Roof Construction Details			
4.1	Conventional roof types are insulated with 500mm mineral wool to achieve the U-value indicated opposite.	U-Value = 0.09 W/m ² K	
5. Openings			
5.1	External doors are installed to achieve the U-value stated opp	U-Value circa 1.2 W/m ² K	
5.2	All windows and patio type doors/windows with Low-e glass hard coating to achieve the U-Value stated opposite. For plots with System 4 MVHR <u>NO</u> trickle vents are reqd. For plots 4-9 trickle vents will be required.	Uw=1.3 W/m ² K frame and glazing (new part F regs standard) g-value South & West = 0.4 g-value East and North = 0.5	

		All windows to be BFRC Approved wherever possible.	
6. Ventilation			
6.1	Design stage SAP calculation presumes an air permeability of 4m3/m2/hr at 50pa will be achieved on Types A2, A3, E1, E2 3m3/m2/hr at 50pa will be achieved on Types B2, B6, C & D	Every dwelling tested and certificated To meet Jigsaw Standard and EPC B rating wherever possible.	
6.2	System 4 MVHR supplied to all units excl plots 4-9. Window opening will comply with the AEC NIA.	Allow for MVHR - Vent Axia Sentinel Kinetic Advance S. PCDB: 500447. No trickle vents required for these plots.	
6.3	System 3 dMEV supplied to plots 4-9. Window opening will comply with the AEC NIA.	Allow for dMEV – Greenwood CV3 GIP Trickle vents required for these plots.	
6.4	No open flues or fireplaces or flue-less gas fires are present		
7. Space Heating			
7.1	There is only one main heating system installed to all dwellings	No secondary heating.	
7.2	The central heating pump and cylinder are inside the dwelling.	Within the heated space	
7.3	Heating is provided by individual air source heat pumps as indicated opposite.	Vaillant aroTHERM Plus 5kW + Arostor HW cylinder	
7.4	The heating system is controlled by time and temperature zone control	Multiple thermostats (per floor)	
8. Water Heating			
8.1	Showers – All showers will be supplied from the Hot Water cylinder via a pump.	All showers to be flow regulated to <8litres/minute.	
8.2	Water usage per person per day is ≤100 Litres.	To meet this standard using Part G: calculations pls allow for the following: All taps <3l/min flow regulated Baths <110litres to overflow Showers <8litres/min flow regulated WCs dual flush 4/2.6l Dishwashers and washing machines will be included but are not specified	
8.3	Hot Water is provided from the main air source heat pump heating system	200L pre-plumbed Arostor cylinders	
9. Renewables			
9.1	No renewables are proposed to meet client standards.	PV could be retrofitted at a later date to assist with Future Homes Standard or Zero Carbon Homes	

10. Other			
10.1	The Contractor will be responsible for undertaking thermal bridging calculations for each detail to provide a comprehensive set of calculations to meet building regs compliance ADL I 2021. They will be responsible for meeting a maximum overall Y value of 0.04W/mK (summation of all the junctions)	<p>All info contained below 10.2-10.4 is to assist the Contractor in the development of their own detailing. The most significant Building Junctions to consider:</p> <p>Psi values required for all junctions applicable to each dwelling type incl: SAP Table K1:</p> <p>E2, E3, E4, E5, E6, E7, E10, E12, E16, E17, E18, P1, and P4 will be adopted.</p> <p>Y-Value of 0.040 to be achieved</p>	
10.2	Low energy (LE) lights are installed throughout.	All lighting to meet a min efficacy of 80 lumens/circuit watt. The Contractor will provide a drawing and schedule of all proposed light fittings with efficacies detailed.	
10.3	All dwellings will require further analysis to comply with part O	Part O overheating assessment required for all dwellings. CIBSE TM59 recommended	
10.4	<p>Provide all design and as built evidential requirements to meet building regulations compliance standards.</p> <p>Refer to EC guide on photographic evidence as attached.</p>	The evidence must be submitted to the OCDEA and Building Control at least 3 weeks before handover for their review and sign off	
10.5	Every home will require Electric Vehicle Charging to meet Bldg Regs Part S.	7kw 32 amp located on box section post or on external wall of house	

10.3. Index of Tables and Figures

Figure 1 - Location of proposed Vine Street residential development.....	8
Figure 2 – Site plan for the proposed Vine Street residential development	9
Figure 3 – House Types A1, A2, A3 & B1.....	10
Figure 4 – House Types B2, B3, B4 & B5	10
Figure 5 – House Types B6 & C	10
Figure 6 – House Types D, E1 & E2	10
Figure 7 - Performance of photovoltaic panel orientation.....	25
Figure 8 - Photovoltaic array on a pitched roof	26
Figure 9 - The principles of a solar thermal system	26
Figure 10 - Principles of a GSHP system.....	27
Figure 11 - Principles of an ASHP system.....	28
Figure 12 - Mounted wind turbine.....	29
Figure 13 - Biomass boiler and hopper	30
 Table 1 - Proposed development CO ₂ emissions against Building Regulations Part L1 2021.....	 6
Table 2 – Key National Planning Policy Requirements and Design Responses.....	12
Table 3 – Key Local Planning Policy Requirements and Design Responses	13
Table 4 - Baseline dwelling carbon emissions and primary energy	21
Table 5 - Proposed carbon emissions from Vine Street residential development	31