



STANDARD CIRCULAR SILENCER INSERTION LOSS DATA

@ +20oC and 5m/sec FACE VELOCITY

SILENCER SIZE	CODE	P.A	OCTAVE BAND CENTRE FREQUENCIES (Hz)							
			63	125	250	500	1K	2K	4K	8K
* 200-550 dia	CDA.1D	ALL	2	4	6	10	14	10	7	8
	CDA.2D	A	4	8	13	17	23	17	12	11
		B	4	8	12	17	23	17	12	10
		C	4	7	10	15	19	16	12	9
	CDAP.1D	A	4	6	8	12	21	21	18	15
		B	4	6	8	11	18	19	17	14
		C	4	6	8	11	14	16	11	10
	CDAP.2D	A	7	10	12	24	29	29	27	23
		B	7	10	12	21	26	26	24	22
		C	7	10	11	18	21	20	17	15
	600-800 dia	CDA.1D	ALL	3	4	9	15	8	7	6
		CDA.2D	A	6	8	13	22	14	13	9
1000-1500 dia		B	6	8	13	22	13	12	9	
		C	6	8	12	20	18	13	11	9
	CDAP.1D	A	4	6	8	17	25	21	18	11
		B	4	6	8	17	23	20	18	10
		C	4	6	8	16	18	16	13	10
	CDAP.2D	A	8	11	16	30	35	31	29	22
		B	8	11	16	27	32	31	29	19
		C	8	11	16	24	23	22	21	17
	1600-2000 dia	CDA.1D	ALL	3	4	9	14	13	7	6
		CDA.2D	A	6	8	14	22	20	13	9
		B	6	8	13	21	18	12	11	9
		C	6	8	12	19	16	11	10	7
1600-2000 dia	CDAP.1D	A	4	6	11	21	20	16	13	11
		B	4	6	11	20	18	15	13	11
		C	4	6	11	17	16	14	12	10
	CDAP.2D	A	8	11	18	30	32	30	24	16
		B	8	11	18	26	27	26	22	16
		C	8	11	18	21	20	22	20	15
	CDA.1D	ALL	4	5	10	14	11	6	6	5
		A	8	9	14	19	18	12	11	9
		B	8	9	14	19	17	11	10	9
		C	8	9	13	18	14	10	9	8
	CDAP.1D	A	5	7	12	21	20	13	12	9
		B	5	7	12	19	18	13	11	9
		C	5	7	12	15	16	12	10	8
	CDAP.2D	A	10	14	21	26	29	28	18	15
		B	10	14	21	25	27	25	16	14
		C	10	14	21	21	20	20	15	14

P.A = Fan Impeller Pitch Angle.

A = upto 12 degrees

B = upto 20 degrees

C = upto 45 degrees

The Above Data Is Offered As Being Indicative Only

For Guaranteed Data (when applicable) Please Consult With (DBA) Technical Services Ltd.