


Technical Specification

Control Point	Head (m)	Flow (l/s)
Primary Design	0.850	5.000
Flush-Flo	0.255	4.990
Kick-Flo®	0.562	4.130
Mean Flow		4.315



hydro-int.com/patents



Head (m)	Flow (l/s)
0.000	0.000
0.029	0.477
0.059	1.683
0.088	3.162
0.117	4.330
0.147	4.745
0.176	4.876
0.205	4.951
0.234	4.985
0.264	4.989
0.293	4.975
0.322	4.948
0.352	4.913
0.381	4.872
0.410	4.823
0.440	4.761
0.469	4.678
0.498	4.562
0.528	4.401
0.557	4.181
0.586	4.212
0.616	4.308
0.645	4.401
0.674	4.492
0.703	4.581
0.733	4.668
0.762	4.754
0.791	4.837
0.821	4.919
0.850	5.000

DESIGN ADVICE



The head/flow characteristics of this SHE-0108-5000-0850-5000 Hydro-Brake Optimum® Flow Control are unique. Dynamic hydraulic modelling evaluates the full head/flow characteristic curve.

The use of any other flow control will invalidate any design based on this data and could constitute a flood risk.

Hydro
International

DATE	12/07/2023 14:07
Site	BENNETT STREET
DESIGNER	Robin Foster
Ref	SHB5-1

SHE-0108-5000-0850-5000
Hydro-Brake Optimum®