

THIS DRAWING SHALL BE PRINTED IN COLOUR
TO FULLY UNDERSTAND CONCEPTUAL
REQUIREMENTS SHOWIN WITHIN

Four white Carrier air conditioning units are mounted on a wall. Each unit features a large circular fan grille and the Carrier logo. They are arranged in a 2x2 grid.

GN.01
Cinema
79 m²

GF.08
Exec visitors

GF.09
Reception

2x AC UNITS RELOCATED

EXISTING PRIMARY CONTAINMENT TO BE UTILISED FOR NEW DATA CABLES AND POWER CABLES TO FLOOR BOX LOCATIONS

OUTLINE OF NEW DUCTWORK FOR INFORMATION ONLY ON THIS DRAWING

EXISTING & CONDENSER UNITS TO BE STRIPPED OUT ALONG WITH ASSOCIATED PIPING WORK

EXISTING VENTILATION DUCTWORK

OUTLINE OF COUNCIL CHAMBER ABOVE

5.6

5.5

5.4

5.3

5.2

5.1

5.0

4.9

4.8

4.7

4.6

4.5

4.4

4.3

4.2

4.1

4.0

3.9

3.8

3.7

3.6

3.5

3.4

3.3

3.2

3.1

3.0

2.9

2.8

2.7

2.6

2.5

2.4

2.3

2.2

2.1

2.0

1.9

1.8

1.7

1.6

1.5

1.4

1.3

1.2

1.1

1.0

0.9

0.8

0.7

0.6

0.5

0.4

0.3

0.2

0.1

0.0

TEMPORARILY REMOVE EXISTING DUCTWORK AND REINSTALL WHEN WORKS COMPLETE

EXISTING ROOM AND ROOM 08 LOCATION

Diagram illustrating two types of smoke detectors:

- Round Surface Mount:** A circular detector mounted on a support bracket, connected to a new ductwork system, installed on a ceiling slab. Labels include: Round Surface Mount, PIR Smoke Detector, Support Bracket, New Ductwork, and Ceiling Slab.
- Rectangular Circular Hanging:** A rectangular detector mounted on a support bracket, connected to a new ductwork system, installed on a ceiling slab. Labels include: Rectangular Circular Hanging Luminaire, Support Bracket, New Ductwork, Drop ACD, and Ceiling Slab.

6	Exposure to live electrical parts.
---	------------------------------------

It is assumed that all works shall be undertaken by a competent contractor working in accordance to an approved method statement

230543-CPW-ZZ-00-DR-N-110001 S0 T01